

# CAMSO EMT 538R



WHEEL  
LOADERS



MOTOR  
GRADERS



ARTICULATED  
DUMP TRUCKS



## OPTIMIZED PERFORMANCE IN WINTER CONDITIONS

Built to provide enhanced traction all-year long in mud, snow and ice. Its radial construction provides great service life and ride quality for optimized snow removal performance.

[camso.co](http://camso.co)

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO EMT 538R



### HEAVY-DUTY DUAL STAR RATED CARCASS

- Enhances stability and versatility for loader, earthmover and grader applications

### OPEN SHOULDER TREAD PATTERN DESIGN

- Enhances tread cleanout for improved traction in mud and snow



### REINFORCED SIDEWALL RIB

- Enhances protection against sidewall damage and punctures

### WINTER-RESISTANT RUBBER COMPOUND WITH DEEP LUG SIPING

- Provides many biting edges for excellent traction on snow and ice

TIRE SIZE	RIM SIZE RECOMMENDED	ACTUAL TIRE DIMENSIONS					LI	SS	SERVICE	APPLI-CATION	MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]									
		O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32 <sup>nd</sup> ] [in]	S.L.R. [mm] [in]	R.C. [mm] [in]					2.00 29	2.50 36	3.00 43	3.50 50	4.00 57	4.50 64	5.00 71	5.50 79	6.00 86	6.50 93
17.5R25	14.00/1.5	1346	448	27	606	4059	176	A2	LOADER*	10 km/h	3650	4250	4850	5600	6000	6500	7100	7500	8000	8500
		53	17.6	34	23.9	159.8				5 mph	8050	9350	10700	12300	13200	14300	15700	16500	17600	18700
		1346	448	27	606	4059	167	B	EM**	50 km/h	-	-	3550	4000	4375	4750	5150	-	-	-
		53	17.6	34	23.9	159.8				30 mph	-	-	7850	8800	9650	10500	11400	-	-	-
		1346	448	27	606	4059	153	A8	GRADER*	40 km/h	2650	3075	3650	-	-	-	-	-	-	-
		53	17.6	34	23.9	159.8				25 mph	5840	6800	8050	-	-	-	-	-	-	-
20.5R25	17.00/2.0	1502	538	29	656	4530	186	A2	LOADER*	10 km/h	4750	5600	6300	7100	8000	8750	9500	10000	10900	11500
		59.1	21.2	37	25.8	178.3				5 mph	10500	12300	13900	15700	17600	19300	20900	22000	24000	25400
		1502	538	29	656	4530	177	B	EM**	50 km/h	-	-	4750	5300	5800	6500	6900	-	-	-
		59.1	21.2	37	25.8	178.3				30 mph	-	-	10500	11700	12800	14300	15200	-	-	-
		1502	538	29	656	4530	161	A8	GRADER*	40 km/h	3450	4125	4625	-	-	-	-	-	-	-
		59.1	21.2	37	25.8	178.3				25 mph	7600	9100	10200	-	-	-	-	-	-	-
23.5R25	19.50/2.5	1604	614	33	703	4838	195	A2	LOADER*	10 km/h	6000	7100	8250	9250	10300	11200	12150	12850	13600	14500
		63.1	24.2	42	27.7	190.5				5 mph	13200	15700	18200	20400	22700	24700	26800	28300	30000	32000
		1604	614	33	703	4838	185	B	EM**	50 km/h	-	-	6000	6700	7500	8250	9000	-	-	-
		63.1	24.2	42	27.7	190.5				30 mph	-	-	13200	14800	16500	18200	19800	-	-	-
		1604	614	33	703	4838	170	A8	GRADER*	40 km/h	4500	5300	6000	-	-	-	-	-	-	-
		63.1	24.2	42	27.7	190.5				25 mph	9900	11700	13200	-	-	-	-	-	-	-

AUTHORIZED DISTRIBUTOR:

camso.co

