

SOLIDEAL AIR 570

BY CAMSO



INDUSTRIAL
PNEUMATIC



LOW ROLLING RESISTANCE SOLUTION FOR ELECTRIC TRUCKS

Best all-around pneumatic tyre for electric forklifts. Engineered to deliver low rolling resistance and reduced vibrations for optimal performance.

camso.co

PERFORMANCE

TYRE LIFE



PUNCTURE RESISTANCE



STABILITY



**ROAD
FREE
COMPANY**

FORMERLY
CAMOPLAST
SOLIDEAL

SOLIDEAL AIR 570

BY CAMSO

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾		ACTUAL TYRE DIMENSIONS				INFLATION PRESSURE (bar)	LOAD INDEX & SPEED SYMBOL	LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)				
				Recommended	Alternative	Overall diameter (mm)	Section width (mm)	Original tread depth (mm)	Static loaded radius (mm)			Up to 25 km/h		Up to 35 km/h		
												Load wheel	Steering wheel	Load wheel	Steering wheel	
5.00-8	8	JS2	90 - 8	3.00	-	466	129	11	-	8,25	106	A5	1235	950	1190	880
15 x 4 1/2-8	12	JS2	90 - 8	3.25	-	395	111	9	-	10,00	100	A5	1040	800	1000	740
16 x 6-8	10	V3-02-5	130 - 8	4.33	-	429	137	10	-	8,00	107	A5	1270	975	1220	900
18 x 7-8	14	V3-02-07	130 - 8	4.33	-	470	161	11	-	9,00	121	A5	1885	1450	1815	1340
18 x 7-8	16	V3-02-07	130 - 8	4.33	-	472	162	11	-	10,00	125	A5	2145	1650	2065	1525
6.00-9	10	JS2	125 - 9	4.00	-	539	159	13	-	8,50	118	A5	1715	1320	1650	1220
21 x 8-9	16	JS2	180 - 9	6.00	-	528	198	13	-	10,00	134	A5	2755	2120	2650	1960
23 x 9-10	16	JS2	180 - 10	6.50	-	596	215	14	-	8,00	137	A5	2990	2300	2875	2130
23 x 9-10	18	V3-02-07	180 - 10	6.50	-	589	213	14	-	9,00	139	A5	3160	2430	3040	2250
28 x 9-15	14	TR75A	180 - 15 HD	7.00	-	704	207	14	-	10,00	146	A5	3900	3000	3750	2775
28 x 9-15	18	V3-02-08	180 - 15 HD	7.00	-	704	207	14	-	10,00	144	A5	3635	2795	3495	2585

FLAT TREAD PROFILE

- Enhances stability and provides even tyre wear

RIB PATTERN AND LOW-ABRASION COMPOUND

- Provides low rolling resistance for best energy efficiency



SMOOTH CONTINUOUS CENTRE LUG

- Reduces vibration and provides enhanced steeringability

REINFORCED CARCASS AND SIDEWALL

- Provides additional puncture resistance to prevent flat tyres

Remarks

(1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyre are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tyre availability in your region.

AUTHORIZED DISTRIBUTOR:



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camso.co



FORMERLY
CAMOPLAST
SOLIDEAL