



**Competitive performance,
for less**

Engineered to perform as well as the competitive products for lower out of pocket expense, means 15% lower cost per hour, on average.

TECHNICAL SPECIFICATIONS

MODEL	TRACK WIDTH (IN)	CAMSO PART #	TREADBARS				GUIDE LUGS		CARCASS		
			QTY	HEIGHT (IN)	TIP WIDTH (IN)	PITCH (IN)	QTY	LENGTH (IN)	PLIES	MAIN CABLE SIZE (MM)	THICKNESS (MM)
CAT 35-55	16	A16AH03302	96	2,1	2,0	6,8	36	5,5	3	5,4	29
	18	A18AH03303	96	2,1	2,0	6,8	36	5,5	3	5,4	29
	25	A25AH03304	72	2,1	2,0	9,0	36	5,5	3	4,3	29
	30	A30AH03305	72	2,1	2,0	9,0	36	5,5	4	4,3	32
CAT 65-95	25	A25AB03311	74	2,3	1,6	9,3	36	5,0	3	4,3	34
	30	A30AB03312	74	2,3	1,6	9,3	36	5,0	3	4,3	34
AGCO MT700	16	A16AR03293	92	2,3	1,6	7,8	46	4,7	3	5,4	31
	18	A18AR03294	92	2,3	1,6	7,8	46	4,7	3	5,4	31
	25	A25AR03295	92	2,3	1,6	7,8	46	4,7	3	5,4	31
	30	A30AR03306	92	2,3	1,6	7,8	46	4,7	3	5,4	31
AGCO MT800	27,5	A27AS03296	100	2,3	1,6	8,0	52	4,7	3	5,4	31
	30	A30AS03297	100	2,3	1,6	8,0	52	4,7	3	5,4	31
JOHN DEERE JD 8000T	16	A16AT03307	96	2,1	2,0	6,9	48	4,1	3	5,4	31
	18	A18AT03308	96	2,1	2,0	6,9	48	4,1	3	5,4	29
	25	A25AT03314	96	2,1	2,0	6,9	48	4,1	3	4,3	29
	30	A30AT03309	96	2,1	2,0	6,9	48	4,1	3	4,3	29
JOHN DEERE JD 9000T	30	A30AU03313	92	2,3	1,6	8,4	54	4,5	4	4,3	34
	36	A36AU03353	92	2,3	1,6	8,4	54	4,5	4	4,3	34
JOHN DEERE JD 8RT	16	A16AY03298	100	2,3	1,6	7,3	46	4,5	3	5,4	31
	18	A18AY03299	100	2,3	1,6	7,3	46	4,5	3	5,4	31
	25	A25AY03300	100	2,3	1,6	7,3	46	4,5	3	5,4	31
	30	A30AY03310	100	2,3	1,6	7,3	46	4,5	3	5,4	31
JOHN DEERE JD 9RT	30	A30AV03301	88	2,3	1,6	9,0	50	4,5	3	5,4	31

**Warranty
48 months /2000 hours**

Tracks are prorated based on actual tread wear rather than on time, so customers receive fair value on warranty replacement tracks compared to competing products that base their warranties on months of service. Some conditions apply. Refer to the warranty certificate for details.

For more info, visit camsco.co/agriculture



FORMERLY
CAMOPLAST
SOLIDEAL

PRINTED IN CANADA

**INTRODUCING THE NEXT GENERATION
OF TRACKS FOR STANDARD AG APPLICATION
CAMSO AG 2500**



FORMERLY
CAMOPLAST
SOLIDEAL

Driven by quality

When it comes to standard AG applications, the Camso AG 2500 has got you covered.

The 2500 track series are built with the same process, standards and quality you expect from Camso products.



NEW CAMSO AG 2500 FRICTION DRIVE

AVAILABLE FOR ALL FRICTION DRIVE TRACTORS
INCLUDING JOHN DEERE 8RT, 9RT AND THE AGCO
MT700 AND MT800 PLATFORMS

High-grade rubber compounds

Improves resistance to cutting, gouging and tearing


Slows rubber wearing, aging and cracking

Combination of up to 6 specific compounds (treads, carcass, guide lugs)

Optimized guide lug geometry

Designed to OEM specifications

More guiding surface with Camso tracks



Tread bar

Long-lasting treads, up to 25 % better than the competition

Provides optimal traction, ride quality and life

Camso's unique single curing process

A finished product with increased durability and performance

No material displacement during the manufacturing process

