CTS TRACTOR

Reduce your compaction zones and increase traction

Engineered to easily convert tractors to tracks. With excellent traction and flotation in wet or soft ground conditions, it's a perfect choice for tillage and rice fields.

Offset -11



Rear Track Width 30"



Front Track Width 24"

Sprocket

To get the most power to the ground

 Positive drive sprocket designed to engage up to 8 drive lugs

Main frames

Simplifies maintenance operations

Oil bath drive hubs

Suspension

Improves ground contact on uneven terrain to help transfer power to the ground

 Patented double oscillating bogie wheels



Hydraulic tensioning system

Maximizes tractive performance hydraulic tensioning system with nitrogen-charged accumulator

 Maintains track tension for each system independently

Track

Improves traction

 Designed with a large track footprint to reduce ground pressure and high traction tread pattern

Wheels

Simplifies maintenance operations

- Heavy duty wheel hubs with oil bath lubrication
- No greasing or repacking of bearings

CAMSO CTS TRACTOR

TRACK SYSTEM FRONT

24D18C

Track width	24"
Track system height	53.8"
Track system length	82.1"
Flat plate area per pair (in²)	2,568





30D23MC

30"
64.6"
85.2"
3,402



Camso provides comprehensive warranty coverage for a period of 12 months from date of purchase, for Conversion Track System (CTS) against defects in materials and workmanship. Some conditions apply. Refer to the warranty certificate for details. For more info, visit **camso.co/agriculture**



TRACTOR APPLICATIONS

CONVERSION TRACK SYSTEM FOR TRACTOR

CAMSO **CTS TRACTOR**

Reduces compaction zones and increases traction

Engineered to easily convert tractors to tracks with minimum maintenance. It's the simplest MFWD conversion track system in the market. With excellent traction and flotation in wet or soft ground conditions, it's a perfect choice for tillage and rice fields.



PERFORMANCE

