

CAMSO ADT 753R

FORMERLY SOLIDEAL SRAT



ARTICULATED
DUMP TRUCKS



RADIAL PERFORMANCE MEETS HIGH TRACTION

A premium and versatile solution for tough articulated dump truck applications. Combining excellent traction, stability and durability, it's an excellent solution for a wide variety of surface conditions.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO ADT 753R



NON-DIRECTIONAL TREAD PATTERN WITH OPTIMIZED LUG-TO-VOID RATIO

- Increases traction and durability in off-road conditions

DEEP TREAD DEPTH

- Enhances traction in off-road conditions

HEAVY-DUTY DUAL-STAR CARCASS


- Optimizes stability for articulated dump truck applications

PREMIUM RUBBER COMPOUNDS

- Reduces heat build-up

TIRE SIZE	TYPE	RIM SIZE	TIRE DIMENSIONS			APPLICATION	SI	LI	INFLATION PRESSURE [KPa] [PSI] AND LOAD CAPACITY [kg] [lb]											
			O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]				KPa	200	250	300	350	400	450	500	550	600	650	
			PSI	29	36				44	51	58	65	73	80	87	94				
20.5R25	TBLS	17.00/2.0	1485	524	31	Loader*/**	A2	186/193	kg	4750	5600	6300	7100	8000	8750	9500*	10000	10900	11500**	
						EM*/**	B	168/177	kg	-	-	4750	5300	5800	6500	6900	7300 (5.25)**	-	-	-
			58.46	20.63	39.1	Grader*/**	A8	161/170	kg	3450	4125	4625*	-	-	-	-	-	-	-	-
23.5R25	TBLS	19.50/2.5	1615	614	29	Loader*/**	A2	195/201	kg	6000	7100	8250	9250	10300	11200	12150*	12850	13600	14500**	
						EM*/**	B	176/185	kg	-	-	6000	6700	7500	8250	9000	9250 (5.25)**	-	-	-
			63.58	24.17	36.5	Grader*/**	A8	161/170	kg	4500	5300	6000*	-	-	-	-	-	-	-	-
26.5R25	TBLS	22.00/3.0	1736	688	37	Loader*/**	A2	202/209	kg	7500	9000	10300	11500	12850	14000	15000*	16000	17000	18500**	
						EM*/**	B	184/193	kg	-	-	7500	8500	9500	10300	11200	11500 (5.25)**	-	-	-
			68.35	27.09	46.6				184/193	lb	-	-	16500	18700	20900	22700	24700	25400 (76)**	-	-
29.5R25	TBLS	25.00/3.5	1871	777	38	Loader*/**	A2	208/216	kg	-	-	-	-	15500	17000	18000*	19500	20600	22400**	
						EM*/**	B	191/200	kg	-	-	9250	10300	11500	12500	13600	14000 (5.25)**	-	-	-
			73.66	30.59	47.9				191/200	lb	-	-	20400	22700	25400	27600	30000	30900 (76)**	-	-

LUG-TO-VOID RATIO



- CAMSO ADT 753R
- CAMSO WHL 753R NEW
- CAMSO WHL 753R 25% WORN

The Camso ADT 753R optimized lug-to-void ratio provides enhanced traction while its premium compounds and E3 depth minimizes heat build-up.

AUTHORIZED DISTRIBUTOR:

camso.co



FORMERLY CAMOPLAST SOLIDEAL