

CAMSO LM L3



WHEEL LOADERS



MULTI-SURFACE PERFORMANCE

Delivers optimized performance on all surfaces. With enhanced side impact resistance and improved stability, it reduces flats and improves ride quality in all types of applications.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO LM L3



HEAVY-DUTY CARCASS

- Increases side impact resistance and stability

STEPPED TREAD DESIGN

- Enhances tread cleanout for improved traction

NON-DIRECTIONAL TREAD PATTERN WITH OPTIMIZED LUG-TO-VOID RATIO


- Ensures even tread wearing for greater durability

DEEP AND FLAT TREAD PROFILE

- Reduces tread crowning for improved durability

TIRE SIZE	PR	ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	TRA CODE	MAXIMUM TIRE LOAD [lb] VERSUS INFLATION PRESSURE [PSI]										
		O.D [in]	O.W [in]	O.T.D [32nd]				36	39	43	46	50	54	57	61	64	68	71
15.5-25	12	50.5	16.4	33	168	A2	L3	9400	9900	10300	10750	11250	11800	12350	-	-	-	-
					142	A8	G3	-	-	-	-	-	-	-	-	-	-	
					149	B	E3	7150	-	-	-	-	-	-	-	-	-	
15.5-25	16	50.6	16.0	33	175	A2	L3	9400	9900	10300	10750	11250	11800	12350	12800	13250	13600	14150
					146	A8	G3	6200	6600	-	-	-	-	-	-	-	-	
					156	B	E3	7150	8050	8850	-	-	-	-	-	-	-	
17.5-25	12	54.3	18.4	33	171	A2	L3	11150	11800	12350	13000	13600	-	-	-	-	-	
					145	A8	G3	-	-	-	-	-	-	-	-	-	-	
					153	B	E3	-	-	-	-	-	-	-	-	-	-	
17.5-25	16	54.8	18.1	33	177	A2	L3	11150	11800	12350	13000	13600	14150	14700	15250	15650	16100	
					150	A8	G3	6850	7400	-	-	-	-	-	-	-	-	
					158	B	E3	8500	8950	9400	-	-	-	-	-	-	-	
17.5-25	20	53.7	18.8	35	181	A2	L3	11150	11800	12350	13000	13600	14150	14700	15250	15650	16100	16550
					164	B	E3	8500	8950	9400	9800	10250	10700	11050	-	-	-	
					181	A2	L3	14800	15650	16550	17450	18200	-	-	-	-	-	
20.5-25	16	59.2	21.5	40	156	A8	G3	-	-	-	-	-	-	-	-	-	-	
					167	B	E3	11350	12050	-	-	-	-	-	-	-	-	
					186	A2	L3	14800	15650	16550	17450	18200	18850	19600	20300	20950	-	
20.5-25	20	59.5	21.7	38	170	B	E3	11350	12050	12700	13250	-	-	-	-	-	-	
					191	A2	L3	18750	19850	20950	22100	22950	24050	-	-	-	-	
					177	B	E3	14450	15350	16100	-	-	-	-	-	-	-	
23.5-25	24	64.2	24.8	47	196	A2	L3	18750	19850	20950	22100	22950	24050	24950	25850	26700	27600	
					180	B	E3	14450	15350	16100	16900	17650	-	-	-	-		
					198	A2	L3	24300	25400	26600	27900	29150	-	-	-	-		
26.5-25	20	69.0	27.2	50	181	B	E3	18200	-	-	-	-	-	-	-	-		
					203	A2	L3	24300	25400	26600	27900	29150	30000	30900	32000	33100	34200	
					188	B	E3	18200	19300	20400	21300	22100	-	-	-	-		
26.5-25	28	69.6	27.2	50	207	A2	L3	28350	30000	30900	33100	34200	35300	37550	38650	-	-	
					193	B	E3	22100	22750	24050	25400	-	-	-	-	-		

■ CAMSO LM L3 ■ CAMSO LM L2



Durability and stability are key issues for loader applications on mixed and hard surfaces. Camso LM L3 enhances tread life and impact resistance with a high lug-to-void ratio and engineered non-directional tread pattern. Additionally, a heavy-duty carcass improves stability.

AUTHORIZED DISTRIBUTOR:

camso.co



FORMERLY CAMOPLAST SOLIDEAL