

CAMSO TM R4



COMPACT
WHEEL LOADERS



DURABLE OFF-ROAD PERFORMANCE

Provides incomparable durability and traction for heavy-duty applications. Enhanced tread cleanout and lug stability combined to maximize performance.

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO™ R4



HAULER STEPPED TREAD DESIGN

- Enhances tread cleanout for improved traction

OPTIMIZED LUG-TO-VOID RATIO

- Enhances longevity and tread puncture resistance



HEAVY-DUTY CARCASS

- Provides excellent stability and side impact resistance

TAPERED TREAD LUGS

- Improves lug stability for even wearing

TIRE SIZE	PR	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	TRA CODE	APPLICATION	MAXIMUM TIRE LOAD [lb]						
											On other vehicles			On counterbalanced lift trucks			
											Inflation pressure [PSI]	10 km/h 6 mph	15 km/h 9 mph	50 km/h 30 mph	Inflation pressure [PSI]	Load wheel	Steering wheel
18-19.5	16	14x19.5	-	44.0	17.9	40	160	A8	R-4	DRIVE	64	13900	13200	8950	79	14200	11900
405/70-20 (16/70-20)	14	13x20	13SDC	42.7	15.9	34	154	A8	R-4	FREE	50	11600	11000	7450	79	11850	9950
				42.7	15.9	34	142			DRIVE	50	8200	7800	5250	79	11850	9950
18-22.5	16	14x22.5	-	47.6	17.5	44	163	A8	R-4	DRIVE	64	15050	14300	9700	79	15400	12900
400/80-24 (15.5/80-24)	16	13x24	13SDC	49.0	16.2	47	156	A8	R-4	CONSTANT	57	11050	10000	8500	-	-	-
				49.0	16.2	47	156			CYCLIC	57	13250	11850	8500	-	-	-
400/80-24 (15.5/80-24)	20	13x24	13SDC	48.7	16.1	47	162	A8	R-4	CONSTANT	71	13100	11850	10050	-	-	-
				48.7	16.1	47	162			CYCLIC	71	15750	14050	10050	-	-	-
440/80-24 (16.5/85-24)	22	DW14Lx24	DW13 DW13L DW15L	52.3	17.8	42	168	A8	R-4	CONSTANT	71	15679	14074	11850	-	-	-
				52.3	17.8	42	168			CYCLIC	71	19136	16420	11850	-	-	-
440/80-24 IND	-	DW15L	DW14L/ DW16L TW14L/ TW15L/ TW16L	49.6	17.9	39	159	A8	R-4	CYCLIC	71	16105	14475	10320	-	-	-
				49.6	17.9	39	159			CONSTANT	71	13990	12060	10030	-	-	-
460/70-24 IND (17.5L-24)	-	DW15L	DW14L/ DW16L TW14L/ TW15L/ TW16L	49.8	17.9	39	159	A8	R-4	CYCLIC	58	14475	12930	8775	-	-	-
				49.8	17.9	39	159			CONSTANT	58	12060	10900	8775	-	-	-

IMPROVED MOUNTABILITY



Increased tension on rim prior to inflation compared to competition designed to prevent air leakage during inflation process.

AUTHORIZED DISTRIBUTOR:

camso.co



FORMERLY CAMOPLAST SOLIDEAL