

CAMSO MPT 773



BACKHOE
LOADERS



WHEEL
LOADERS



RELIABLE PERFORMANCE IN HARSH APPLICATIONS

Provides excellent durability and stability on hard surface. Protects from chipping and chunking in abrasive and rocky settings

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO MPT 773



ENGINEERED MONO-BLOCK TREAD DESIGN

- Provides resistance against rubber chipping and chunking

SELF-CLEANING STEPPED TREAD

- Maximizes cleanout for improved off-road traction

IMPACT GUARD SIDEWALL DESIGN

- Deflects debris to better protect sidewalls and reduce stress cracking

HIGH LUG-TO-VOID RATIO

- Provides excellent durability and tread impact resistance

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	TRA CODE	SERVICE	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]							
			Recommended	Alternative	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32 nd]						Static	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12.5 mph	25 km/h 16 mph	30 km/h 19 mph	35 km/h 22 mph	40 km/h 25 mph
14.00-25	12	TT	10.00/1.5	-	1371	390	30	172	A2	L-3	Loader-Dozer	4.25	10100	6300	5500	5300	5050	4850	4650	4400
					62	22265	13890	12125	11685	11135	10690	10250	9700							
					54.0	15.4	38	150	B	E-3	Earthmover	2.75	-	-	3750	3675	3625	3550	3475	3450
					40	-	-	8265	8100	7990	7825	7660	7605							
14.00-25	20	TT	10.00/1.5	-	1363	384	30	182	A2	L-3	Loader-Dozer	7.00	13600	8500	7400	7150	6800	6550	6300	5950
					102	29985	18740	16315	15765	14990	14440	13890	13120							
					53.7	15.1	38	161	B	E-3	Earthmover	4.75	-	-	5200	5100	5000	4900	4800	4775
					69	-	-	11465	11245	11025	10805	10580	10525							

AUTHORIZED DISTRIBUTOR:

camso.co

