

CAMSO BHL 732



BACKHOE
LOADERS



BEST OFF-ROAD TRACTION AND DURABILITY

The ultimate mixed soft surface backhoe tire solution. Deepest traction tread with enhanced protective features to maximize durability in softer conditions.

camsoco

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO BHL 732



MASSIVE DIRECTIONAL TREAD LUGS WITH EXTENDED CENTRE BLOCKS

- Maximizes off-road traction and durability

WRAPAROUND STEPPED TREAD DESIGN

- Maximizes tread cleanout for best off-road traction



EXTRA THICK VOID GUARD

- Maximizes tread impact protection to reduce risk of punctures

HEAVY-DUTY SIDEWALL WITH ENHANCED RIM PROTECTION

- Provides enhanced sidewall and rim flange protection, reducing impact damage and flat tires

TIRE SIZE	RIM SIZE RECOMMENDED (PERMITTED)	ACTUAL TIRE DIMENSIONS					LOAD INDEX SPEED SYMBOL	APPLICATION	MAXIMUM TIRE LOAD [kg] [lb]						
		O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32 nd]	S.L.R. [mm] [in]	R.C. [mm] [in]			INFLATION PRESSURE [bar] [PSI]	Static	*5 km/h 3 mph	**10 km/h 6 mph	25 km/h 16 mph	40 km/h 25 mph	50 km/h 31 mph
12.5/80-18 IMP	W9 (11)	983	305	25	441	2932	142 A8	FREE ROLLING	3.70	4375	-	3710	3155	2650	2385
		38.7	12.0	32	17.4	115.4			54	9635	-	8175	6950	5840	5255
		983	305	25	441	2932	129 A8	DRIVE	3.70	4350	-	2590	2200	1850	1665
		38.7	12.0	32	17.4	115.4			54	9590	-	5710	4855	4080	3670
19.5L-24 IND	DW16L (TW16L)	1328	500	25	602	3952	151 A8	CYCLIC	2.30	7935	5760*	5175**	3830	3450	3140
		52.3	19.7	31	23.7	155.6			33	17495	12700*	11410**	8445	7605	6920
		1328	500	25	602	3952	151 A8	CONSTANT	2.30	7935	5005	4315	3655	3450	3140
		52.3	19.7	31	23.7	155.6			33	17495	11035	9515	8060	7605	6920
21L-24 IND	DW18L (TW18L)	1383	531	38	633	4100	155 A8	CYCLIC	2.20	8915	6470*	5815**	4300	3875	3525
		54.4	20.9	48	24.9	161.4			32	19655	14265*	12820**	9480	8545	7770
		1383	531	38	633	4100	155 A8	CONSTANT	2.20	8915	5620	4845	4110	3875	3525
		54.4	20.9	48	24.9	161.4			32	19655	12390	10680	9060	8545	7770
16.9-28 IND	DW15L (DW14L; TW14L; TW15L)	1425	440	35	653	4250	152 A8	CYCLIC	2.60	8165	5930*	5325**	3940	3550	3230
		56.1	17.3	44	25.7	167.3			38	18000	13075*	11740**	8685	7825	7120
		1425	440	35	653	4250	152 A8	CONSTANT	2.60	8165	5150	4440	3765	3550	3230
		56.1	17.3	44	25.7	167.3			38	18000	11355	9790	8300	7825	7120

All tires listed are tubeless.

* Cyclic: One way distance up to 150 m (500 feet)

** Cyclic: One way distance up to 600 m (2000 feet)

AUTHORIZED DISTRIBUTOR:

camso.co

