

CAMSO AWP 583S



SCISSOR LIFTS



BUILT FOR SAFETY AND DURABILITY

Purpose-built to maximize productivity for indoor scissor lift application, this non-marking cured-on tire solution ensures long service life while ensuring safe lift operation.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO AWP 583S



OPTIMIZED TREAD DESIGN WITH SIPING

- Enhance water evacuation for better maneuverability

GREY NON-MARKING COMPOUND

- Provides low ground disturbance for indoor applications



ENGINEERED RUBBER COMPOUND WITH NATURAL RUBBER

- Optimizes tread life on hard surfaces

DURABLE CAST STEEL WHEEL

- Provides ultimate wheel durability

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS		
		Outside Diameter [mm] [in]	Overall Width [mm] [in]	Tread Width [mm] [in]
10x3(8)	76.2x203	254	76.2	74
		10.0	3.0	2.9
12x4.5(255)	114.3x255	305	114.3	112
		12.0	4.5	4.4
12.5x4.25(267)	107x267	318	107	105
		12.5	4.2	4.1
323x100(280)	100x280	323	100	93
		12.7	3.9	3.7
15x5(318)	127x318	381	127	125
		15.0	5.0	4.9
15x5(320)	127x320	381	127	125
		15.0	5.0	4.9
406x125(354)	125x354	406	125	121
		16.0	4.9	4.8

Wheels are painted in RAL 7012

Please contact your local sales representative for more information regarding machine fitments.

AUTHORIZED DISTRIBUTOR:

camso.co

