CAMSO MEX HXD





EXTREME RESISTANCE TO SEVERE CONDITIONS

A purpose-built solution for miniexcavators in harsh or extreme heavy-duty applications. Engineered to provide resistance against damage and catastrophic failure, they'll maximize your uptime. camso.co

PERFORMANCE





CAMSO **Mex hxd**

PATENTED 3S INTERNAL IRON CORE

 Prevents detracking and minimizes vibrations for better ride quality and lower maintenance cost

PREMIUM RUBBER COMPOUND AND EXTRA THICK CARCASS

 Improves damage resistance and promotes even tread wear for the longest track life

HIGH-TENSILE, RUBBER SEALED STEEL CABLES PROTECTED BY HEAVY-DUTY CARCASS AND TREAD

Resists carcass punctures and cable corrosion to extend service life

CURBSHIELD TECHNOLOGY WITH HEAVY-DUTY CARCASS

 Maximizes service life prior to track degradation process triggered by edge cutting leading to iron core corrosion and lower maintenance cost


| | DITOU | TOFAD | | METAL PIECE | CARCASS | LUG | METAL PIECE | METAL PIECE |
|-------|-------|-------|---------|-------------|-----------|--------|------------------------|---------------|
| WIDTH | PITCH | TREAD | GUIDING | NAME | THICKNESS | HEIGHT | TYPE | SPECIFICATION |
| 230 | 48 | AH | I | KA | 26.5 | 24.5 | 3S | STANDARD |
| 300 | 55 | AH | I | SA | 35 | 27.5 | 35 | NARROW |
| 300 | 55 | AH | I | WA | 35 | 27.5 | 35 | WIDE |
| 350 | 73 | AH | J | EA | 40 | 25 | 3S RAIL TYPE | STANDARD |
| 400 | 72.5 | АН | I | WA | 43 | 27.5 | 3S | NARROW |
| 400 | 72.5 | AH | I | EA | 43 | 27.5 | 35 | WIDE |
| 400 | 72.5 | АН | J | EA | 45.5 | 27.5 | 3S RAIL TYPE | STANDARD |
| 400 | 73 | АН | J | EA | 41 | 25 | 3S RAIL TYPE | STANDARD |
| 400 | 75.5 | AH | J | WA | 47 | 27.5 | 3S OFFSET RAIL TYPE | STANDARD |
| 450 | 71 | AH | I | JA | 48 | 30 | 35 | STANDARD |
| 450 | 76 | AH | I | JA | 48 | 30 | 35 | STANDARD |
| 450 | 81 | AH | I | OA | 46.5 | 30.5 | 35 | NARROW |
| 450 | 81 | AH | I | AA | 46.5 | 30.5 | 35 | WIDE |
| 450 | 83.5 | АН | J | UA | 47 | 27.5 | 3S OFFSET RAIL TYPE | STANDARD |
| 485 | 92 | AH | I | D | 62.5 | 27 | OFFSET | STANDARD |
| 500 | 92 | AB | I | D | 58 | 30 | STANDARD | STANDARD |

TREAD PATTERNS




TREAD WEAR TEST (150 hours)





Camso tracks are designed with much thicker tread than most OEM tracks. Maintaining more rubber around the carcass offers more protection on carcass puncture and edge cutting. This all translates in longer service life and less downtime. The end result of this test is: Camso MEX HXD offers 30% more service life.



Throughout the entire test, the **vibration level was 42% lower with the Camso tracks** than the OEM quality track regardless the speed and the direction.



camso.co