

# CAMSO MPT 753



TELEHANDLERS



COMPACT WHEEL  
LOADERS



BACKHOE  
LOADER



## THE NEXT GENERATION IN VERSATILITY AND DURABILITY

Engineered to provide enhanced traction in a variety of surface applications without sacrificing ride quality. Excellent overall durability and puncture resistance ensure maximum service life.

[camsco.co](http://camsco.co)

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO MPT 753



**FLAT NON-DIRECTIONAL TREAD PATTERN WITH HIGH LUG-TO-VOID RATIO**

- Enhances stability, ride quality and durability

**VOID GUARD IMPACT PROTECTION**

- Protects from tread punctures to minimize flat tires



**IMPACT GUARD SIDEWALL DESIGN**

- Deflects debris to better protect sidewalls and reduce stress cracking

**STEPPED AND OPEN SHOULDER LUGS**

- Enhances traction on softer surfaces for better versatility

TIRE SIZE	RECOMMENDED RIM SIZE (PERMITTED)	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	APPLICATION	INFLATION PRESSURE [PSI]	MAXIMUM TIRE LOAD [lb]					
		O.D. [in]	O.W. [in]	O.T.D. [in]	S.L.R. [in]	R.C. [in]					STATIC	3 mph	6 mph	9 mph	18 mph	31 mph
340/80-18 IND (12.5-18; 335/80-18)	11 (12; 11 SDC; 12 SDC; W10; W11)	39.6	13.8	26	18.4	119.3	143	A8	CYCLIC	58	13825	10030*	9015**	8045	6425	5465
		39.6	13.8	26	18.4	119.3			CONSTANT		13825	8710	7505	6790	6250	5465
340/80-20 IND (12.5-20; 335/80-20)	11 (12; 11 SDC; 12 SDC; W10; W11)	42	14	31	19.5	126.7	144	A8	CYCLIC	58	14200	10305*	9260**	8265	6605	5620
		42	14	31	19.5	126.7			CONSTANT		14200	8950	7715	6980	6415	5620
400/70-20 IND (405/70-20; 16.0/70-20)	13 (12 SDC; 13 SDC; 14)	43.3	15.9	34	19.9	129.5	155	A8	CYCLIC	73	19655	14265*	12820**	11455	9140	7770
		43.3	15.9	34	19.9	129.5			CONSTANT		19655	12390	10680	9655	8885	7770
400/70-24 IND (405/70-24; 16.0/70-24)	13 (DW12; 13SDC; DW13; DW13L; DW14L; TW13; TW14L)	46.7	15.8	37	21.7	140	158	A8	CYCLIC	73	21550	15655*	14055**	12555	10030	8530
		46.7	15.8	37	21.7	140			CONSTANT		21550	13590	11720	10595	9745	8530
400/80-24 IND (15.5/80-24)	DW13 (W12; W13; W14L; DW12; DW14L; TW14L)	49	16.2	42	22.8	147.8	162	A8	CYCLIC	73	24085	17495*	15710**	14030	11210	9535
		49	16.2	42	22.8	147.8			CONSTANT		24085	15190	13095	11840	10890	9535
460/70-24 IND (17.5L-24)	DW15L (DW14L; DW16L; TW14L; TW15L; TW16L)	49.3	17.9	43	22.9	140	159	A8	CYCLIC	58	22190	16105*	14475**	12930	10320	8775
		49.3	17.9	43	22.9	140			CONSTANT		22190	13990	12060	10900	10030	8775
440/80-28 IND (16.9-28)	DW14L (DW13; DW13L; DW15L; TW13; TW14L; TW15L)	56.2	17.1	45	26.2	169.7	156	A8	CYCLIC	46	20285	14725*	13230**	11815	9435	8025
		56.2	17.1	45	26.2	169.7			CONSTANT		20285	12785	11025	9965	9170	8025

\* Cyclic: One way distance up to 500 feet

\*\* Cyclic: One way distance up to 2000 feet

All tires listed are tubeless

