CAMSO SKS 7865 FORMERLY SOLIDEAL SAFETYMASTER SM





SOLID HARD SURFACE DURABILITY

The ideal solid tire solution for flat-free, hard-surface operation on skid steer loaders. Built to maximize tire life while providing excellent stability for primarily indoor, hard-surface operations.

PERFORMANCE





CAMSO SKS 786S



FULL SOLID CONSTRUCTION

 Provides excellent durability and flat-free operation


FULL-WIDTH FOOTPRINT

■ Provides excellent stability and tread life

REUSABLE WHEEL

 Provides lower cost per hour and quicker installation

	RIM SIZE	ACTUAL TIRE DIMENSIONS			HEEL		LOAD CAPACITY [kg] [lb]						
TIRE SIZE							Counterbalanced lift trucks			Other vehicles			Chatia
							Load wheel		Steering wheel			Static	
		O.D. [mm] <i>[in]</i>	O.W. [mm] <i>[in]</i>	0.T.D. [mm] [32nd]	Normal	Quick	15 km/h 9 mph	25 km/h 16 mph	25 km/h 16 mph	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph
31x10-20 (10-16.5)	7.50	781	237	33			-	4030	3100	4030	3660	3100	4680
		30.7	9.3	42			-	8885	6835	8900	8100	6850	10350
33x12-20 (12-16.5)	7.50	831	287	40		•	-	5200	4000	5200	4720	4000	6040
		32.7	11.3	50			-	11465	8820	11500	10400	8850	13350
36x14-20 (14-17.5)	7.50	909	326	43		•	-	6175	4750	6175	5605	4750	7175
		35.8	12.8	54			-	13650	10500	13650	12350	10500	15850



The Camso SKS 786S is a full-sized solid skid steer tire solution that maintains original equipment dimensions with a full, flat-tread profile for **improved stability and longevity** on hard surface applications. Embedded steel bead cables prevent tire spinning on the reusable wheel.

AUTHORIZED DISTRIBUTOR:

camso.co



