

CAMSO MPT 753



TELEHANDLERS



COMPACT WHEEL
LOADERS



BACKHOE
LOADER



THE NEXT GENERATION IN VERSATILITY AND DURABILITY

Engineered to provide enhanced traction in a variety of surface applications without sacrificing ride quality. Excellent overall durability and puncture resistance ensure maximum service life.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO MPT 753



FLAT NON-DIRECTIONAL TREAD PATTERN WITH HIGH LUG-TO-VOID RATIO

- Enhances stability, ride quality and durability

VOID GUARD IMPACT PROTECTION

- Protects from tread punctures to minimize flat tires

IMPACT GUARD SIDEWALL DESIGN

- Deflects debris to better protect sidewalls and reduce stress cracking

STEPPED AND OPEN SHOULDER LUGS

- Enhances traction on softer surfaces for better versatility

TIRE SIZE	RECOMMENDED RIM SIZE (PERMITTED)	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	APPLICATION	INFLATION PRESSURE [bar]	MAXIMUM TIRE LOAD [kg]					
		O.D. [mm]	O.W. [mm]	O.T.D. [mm]	S.L.R. [mm]	R.C. [mm]					STATIC	5 km/h	10 km/h	15 km/h	30 km/h	50 km/h
340/80-18 IND (12.5-18; 335/80-18)	11 (12; 11 SDC; 12 SDC; W10; W11)	1005	350	21	467	3029	143	A8	CYCLIC	4.00	6270	4550*	4090**	3650	2915	2480
		1005	350	21	467	3029			CONSTANT		6270	6270	3950	3405	3080	2835
340/80-20 IND (12.5-20; 335/80-20)	11 (12; 11 SDC; 12 SDC; W10; W11)	1067	355	25	495	3217	144	A8	CYCLIC	4.00	6440	4675*	4200**	3750	2995	2550
		1067	355	25	495	3217			CONSTANT		6440	6440	4060	3500	3165	2910
400/70-20 IND (405/70-20; 16.0/70-20)	13 (12 SDC; 13 SDC; 14)	1096	404	27	504	3290	155	A8	CYCLIC	5.00	8915	6470*	5815**	5195	4145	3525
		1096	404	27	504	3290			CONSTANT		8915	8915	5620	4845	4380	4030
400/70-24 IND (405/70-24; 16.0/70-24)	13 (DW12; 13SDC; DW13; DW13L; DW14L; TW13; TW14L)	1185	402	29	552	3555	158	A8	CYCLIC	5.00	9775	7100*	6375**	5695	4550	3870
		1185	402	29	552	3555			CONSTANT		9775	9775	6165	5315	4805	4420
400/80-24 IND (15.5/80-24)	DW13 (W12; W13; W14L; DW12; DW14L; TW14L)	1244	411	33	580	3753	162	A8	CYCLIC	5.00	10925	7935*	7125**	6365	5085	4325
		1244	411	33	580	3753			CONSTANT		10925	10925	6890	5940	5370	4940
460/70-24 IND (17.5L-24)	DW15L (DW14L; DW16L; TW14L; TW15L; TW16L)	1251	454	34	581	3557	159	A8	CYCLIC	4.00	10065	7305*	6565**	5865	4680	3980
		1251	454	34	581	3557			CONSTANT		10065	10065	6345	5470	4945	4550
440/80-28 IND (16.9-28)	DW14L (DW13; DW13L; DW15L; TW13; TW14L; TW15L)	1428	435	36	666	4310	156	A8	CYCLIC	3.20	9200	6680*	6000**	5360	4280	3640
		1428	435	36	666	4310			CONSTANT		9200	9200	5800	5000	4520	4160

* Cyclic: One way distance up to 150 m

** Cyclic: One way distance up to 600 m

All tires listed are tubeless