

CAMSO TLH 732+



TELEHANDLERS



MOTOR
GRADERS



ULTIMATE OFF-ROAD TRACTION AND STABILITY

Excellent solution for tough off-road applications delivering superior traction, durability, and impact resistance in pneumatic telehandler and grader tires

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO TLH 732+



**EXTRA THICK VOID GUARD
IMPACT PROTECTION**

- Maximizes tread impact protection to reduce risk of punctures

WRAPAROUND STEPPED TREAD DESIGN

- Maximizes tread cleanout for best off-road traction



**MASSIVE TREAD DEPTH
WITH CURVED TREAD LUGS**

- Ensures excellent traction on soft surfaces and long wearing durability when operating at higher speeds

IMPACT GUARD WITH ENHANCED RIM PROTECTION

- Provides maximum sidewall and rim flange protection, reducing risks of impact damages and flat tires

| TIRE SIZE | PR | RIM SIZE Recommended (Permitted) | ACTUAL TIRE DIMENSIONS | | | | | LOAD INDEX | SPEED SYMBOL | TRA CODE | SERVICE | INFLATION PRESSURE [bar] [PSI] | LOAD CAPACITY [kg] [lb] | | | | | |
|-----------|------|--|---------------------------|----------------------|---|------------------------|----------------------|------------|--------------|----------|------------|---|-------------------------|-----------------|------------------|-------------------|-------------------|-------------------|
| | | | O.D. [mm] [in] | O.W. [mm] [in] | O.T.D. [mm] [32 nd] [in] | S.L.R. [mm] [in] | R.C. [mm] [in] | | | | | | Static | 5 km/h 3 mph | 10 km/h 6 mph | 25 km/h 16 mph | 40 km/h 25 mph | 50 km/h 31 mph |
| 13.00-24 | 12 | 8.00TG | 1307 | 376 | 31 | 588 | 3942 | 143 | A8 | G-2 | Grader | 3.00 | - | - | - | - | 2725 | 2475 |
| | | | 51.5 | 14.8 | 39 | 23.1 | 155.2 | | | | | 44 | - | - | - | - | 6010 | 5455 |
| | | 10.00VA (SDC) | 1307 | 376 | 31 | 588 | 3942 | 146 | B | E-2 | Earthmover | 3.00 | - | - | 3350 | 3175 | 3100 | 3000 |
| | | | 51.5 | 14.8 | 39 | 23.1 | 155.2 | | | | | 44 | - | - | 7385 | 7000 | 6835 | 6615 |
| 13.00-24 | 16 | 10.00 | 1301 | 374 | 29 | 593 | 3924 | 152 | A8 | E-2 | Earthmover | 4.00 | - | - | 4000 | 3800 | 3675 | 3575 |
| | | | | | | | | | | | | 58 | - | - | 8820 | 8380 | 8100 | 7880 |
| | | | | | | | | | | | | 6.00 | 10400 | 7400 | 5650 | 5000 | 4550 | 4100 |
| | | 8.00TG | 1367 | 392 | 34 | 607 | 4123 | 153 | A8 | G-2 | Grader | 4.00 | - | - | - | - | 3650 | 3325 |
| | | | | | | | | | | | | 58 | - | - | - | - | 8045 | 7330 |
| | | | | | | | | | | | | 6.00 | 10400 | 7400 | 5650 | 5000 | 4550 | 4100 |
| 14.00-24 | 12 | 8.00TG | 1367 | 392 | 34 | 607 | 4123 | 147 | A8 | G-2 | Grader | 3 | - | - | - | - | 3075 | 2800 |
| | | | | | | | | | | | | 40 | - | - | - | - | 6780 | 6175 |
| | | 10.00VA (SDC) | 1367 | 392 | 34 | 607 | 4123 | 150 | B | E-2 | Earthmover | 3 | - | - | - | 3625 | 3450 | 3350 |
| | | | | | | | | | | | | 40 | - | - | - | 7990 | 7605 | 7385 |
| 14.00-24 | 16 | 8.00TG | 1364 | 397 | 34 | 608 | 4114 | 153 | A8 | G-2 | Grader | 3.75 | - | - | - | - | 3650 | 3325 |
| | | | | | | | | | | | | 54 | - | - | - | - | 8045 | 7330 |
| | | 10.00W | 1364 | 397 | 34 | 608 | 4114 | 156 | B | E-2 | Earthmover | 3.75 | - | - | 4475 | 4250 | 4125 | 4000 |
| | | | | | | | | | | | | 54 | - | - | 9865 | 9370 | 9095 | 8820 |
| 8.00TG | 1364 | 397 | 34 | 608 | 4114 | 177 | A2 | L-2 | Loader-Dozer | 5.50 | 11700 | 8300 | 6350 | 5600 | 5100 | 4600 | | |
| | | | | | | | | | | 80.00 | 25795 | 18300 | 14000 | 12345 | 11245 | 10140 | | |

All tires listed are tubeless.

AUTHORIZED DISTRIBUTOR:

camso.co

