

CAMSO WEX 752



WHEEL
EXCAVATORS



ULTIMATE OFF-ROAD PERFORMANCE AND DURABILITY

Engineered for today's heavier machines to provide maximum performance and durability on mixed-hard surfaces. Provides excellent traction and stability with superior impact protection.

camso.co

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO WEX 752



MASSIVE DIRECTIONAL TREAD LUGS WITH EXTENDED CENTRE

- Maximizes off-road traction and durability

EXTRA THICK VOID GUARD

- Maximizes tread impact protection to reduce risk of punctures

WRAPAROUND STEPPED TREAD DESIGN

- Enhances tread cleanout for best off-road traction



INTEGRATED STONE GUARD*

- Eliminates the need for a spacer while protecting inner sidewalls against impacts

HEAVY-DUTY SIDEWALL

- Provides enhanced sidewall protection, maximizes stability and operator comfort

TIRE SIZE	PR	RECOMMENDED RIM SIZE (PERMITTED)	ACTUAL TIRE DIMENSIONS						LOAD INDEX	SPEED SYMBOL	MAXIMUM INFLATION PRESSURE	MAXIMUM TIRE LOAD [kg] [lb]				
			O.D.	O.W.	O.T.D.	M.D.S.	S.L.R.	R.C.				Static	10 km/h 6 mph	25 km/h 16 mph	40 km/h 25 mph	50 km/h 31 mph
			[mm] [in]	[mm] [in]	[mm] [32 nd in]	[mm] [in]	[mm] [in]	[mm] [in]								
8.25-20	14	6.50 (7.00)	981	245	17	292	464	2959	140	A8	8.00	5700	3550	2850	2475	2225
			38.6	9.6	21	11.5	18.3	116.5			116	12565	7825	6285	5455	4905
9.00-20	14	7.00 (6.50; 7.50)	1023	263	20	324	470	3125	160 (144)	A2 (B)	7.00	7200	4500	3600	3150	2800
			40.3	10.4	25	12.8	18.5	123.0			102	15875	9920	7935	6945	6175
	18		1025	263	20	322	471	3091	164 (148)	A2 (B)	8.50	8000	5000	4000	3500	3150
			40.4	10.4	25	12.7	18.5	121.7			123	17635	11025	8820	7715	6945
10.00-20	16	7.50 (7.00; 8.00)	1065	279	21	339	495	3212	149	A8	7.50	8250	5150	4125	3600	3250
			41.9	11.0	26	13.3	19.5	126.5			109	18190	11355	9095	7940	7165
290/90-20	18	8.00	1065	293	26	**	501	3211	168	A2	9.00	8960	5600	4480	3920	3530
			41.9	11.5	33	**	19.7	126.4			130	19755	12345	9875	8640	7780

All tires listed are tube type.

*Only available on tire size 290/90-20.

**Consult your sales representative for appropriate wheel spacing. Tire not suitable for use on machines with a gross vehicle weight exceeding 20 tons.

