CAMSO EMT 538R

WHEEL LOADERS

MOTOR GRADERS

ARTICULATED DUMP TRUCKS

OPTIMIZED PERFORMANCE IN WINTER CONDITIONS

Built to provide enhanced traction all-year long in mud, snow and ice. Its radial construction provides great service life and ride quality for optimized snow removal performance.

camso.co

PERFORMANCE

TIRE LIFE

PUNCTURE RESISTANCE

TRACTION

CAMSO

CAMSO EMT 538R



HEAVY-DUTY DUAL STAR RATED CARCASS

- Enhances stability and versatility for loader, earthmover and grader applications

OPEN SHOULDER TREAD PATTERN DESIGN

- Enhances tread cleanout for improved traction in mud and snow

REINFORCED SIDEWALL RIB

- Enhances protection against sidewall damage and punctures

WINTER-RESISTANT RUBBER COMPOUND WITH DEEP LUG SIPING

- Provides many biting edges for excellent traction on snow and ice

TIRE SIZE	RIM SIZE RECOM-MENDED	ACTUAL TIRE DIMENSIONS					MACHINE	Tread Code	SI	LI	SPEED		MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]								
		O.D. [mm] [in]	O.W [mm] [in]	O.T.D [mm] [32nd]	S.L.R [mm] [in]	R.C. [mm] [in]					km/h	mph	bar	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50
													PSI	43	50	57	64	71	79	86	93
17.5R25	14.00/1.5	1346	448	27	606	4059	Loader-Dozer	L-2	A2	176	10	5	kg	4850	5600	6000	6500	7100	7500	8000	8500
													lb	10700	12300	13200	14300	15700	16500	17600	18700
							Earthmover	E-2	B	167	50	30	kg	3550	4000	4375	4750	5150	-	-	-
													lb	7850	8800	9650	10500	11400	-	-	-
		53	17.6	34	23.9	159.8	Grader	G-2	A8	153	40	25	kg	3650	-	-	-	-	-	-	-
													lb	8050	-	-	-	-	-	-	-
20.5R25	17.00/2.0	1502	538	30	656	4530	Loader-Dozer	L-2	A2	186	10	5	kg	-	-	8000	8750	9500	10000	10900	11500
													lb	-	-	17600	19300	20900	22000	24000	25400
							Earthmover	E-2	B	177	50	30	kg	-	-	5800	6500	6900	-	-	-
													lb	-	-	12800	14300	15200	-	-	-
		59.1	21.2	38	25.8	178.3	Grader	G-2	A8	161	40	25	kg	-	-	-	-	-	-	-	-
													lb	-	-	-	-	-	-	-	-
23.5R25	19.50/2.5	1604	614	33	703	4838	Loader-Dozer	L-2	A2	195	10	5	kg	-	-	-	11200	12150	12850	13600	14500
													lb	-	-	-	24700	26800	28300	30000	32000
							Earthmover	E-2	B	185	50	30	kg	-	-	-	8250	9000	-	-	-
													lb	-	-	-	18200	19800	-	-	-
		63.1	24.2	42	27.7	190.5	Grader	G-2	A8	170	40	25	kg	-	-	-	-	-	-	-	-
													lb	-	-	-	-	-	-	-	-

All tires listed are tubeless.