

# CAMSO MPT 732



BACKHOE  
LOADERS



TELEHANDLERS



COMPACT WHEEL  
LOADERS



## BEST OFF-ROAD TRACTION AND DURABILITY

The ultimate mixed soft surface backhoe tire solution. Deepest traction tread with enhanced protective features to maximize durability in softer conditions.

[camso.co](http://camso.co)

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO MPT 732



## MASSIVE DIRECTIONAL TREAD LUGS WITH EXTENDED CENTRE BLOCKS

- Maximizes off-road traction and durability

## WRAPAROUND STEPPED TREAD DESIGN

- Maximizes tread cleanout for best off-road traction



## EXTRA THICK VOID GUARD

- Maximizes tread impact protection to reduce risk of punctures

## HEAVY-DUTY SIDEWALL WITH ENHANCED RIM PROTECTION

- Provides enhanced sidewall and rim flange protection, reducing impact damage and flat tires

TIRE SIZE	RECOMMENDED RIM SIZE (PERMITTED)	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	APPLICATION	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]					
		O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	S.L.R. [mm] [in]	R.C. [mm] [in]					Static	5 km/h [3 mph]	10 km/h [6 mph]	25 km/h [16 mph]	40 km/h [25 mph]	50 km/h [31 mph]
280/80-18 IND (10.5/80-18)	W9 (W8; W10)	900	278	18	409	2698	132	A8	CYCLIC	4.00	4600	3340*	3000**	2220	2000	1820
		35.4	10.9	23	16.1	106.2				58	10140	7365*	6615**	4895	4410	4010
		900	278	18	409	2698	132	A8	CONSTANT	4.00	4600	2900	2500	2120	2000	1820
		35.4	10.9	23	16.1	106.2				58	10140	6395	5510	4675	4410	4010
320/80-18 IND (12.5/80-18)	11 (W11; 9; 10)	973	317	26	444	2945	139	A8	CYCLIC	4.00	5590	4060*	3645**	2695	2430	2210
		38.3	12.5	33	17.5	115.9				58	13325	8950*	8035**	5940	5355	4870
		973	317	26	444	2945	139	A8	CONSTANT	4.00	5590	3525	3040	2575	2430	2210
		38.3	12.5	33	17.5	115.9				58	13325	7770	6700	5675	5355	4870
340/80-18 IND (12.5-18; 335/80-18)	11 (12; 11SDC; 12SDC; W10; W11)	1000	351	22	458	3014	143	A8	CYCLIC	4.00	6270	4550*	4090**	3025	2725	2480
		39.4	13.8	28	18.0	118.7				58	13825	10030*	9015**	6670	6010	5465
		1000	351	22	458	3014	143	A8	CONSTANT	4.00	6270	3950	3405	2890	2725	2480
		39.4	13.8	28	18.0	118.7				58	13825	8710	7505	6370	6010	5465
400/70-20 IND (405/70-20; 16.0/70-20)	13 (12 SDC; 13 SDC; 14)	1064	409	31	487	3177	149	A8	CYCLIC	4.00	7475	5430*	4875**	3610	3250	2960
		41.9	16.1	39	19.2	125.1				58	16480	11970*	10750**	7960	7165	6525
		1064	409	31	487	3177	149	A8	CONSTANT	4.00	7475	4715	4065	3445	3250	2960
		41.9	16.1	39	19.2	125.1				58	16480	10395	8960	7595	7165	6525
440/80-24 IND (16.9-24; 16.5/85-24)	DW14L (DW13; DW13L; DW15L; TW13; TW14L; TW15L)	1315	445	26	592	3937	154	A8	CYCLIC	3.20	8625	6265*	5625**	4165	3750	3415
		51.8	17.5	33	23.3	155.0				46	19015	13810*	12400**	9180	8265	7530
		1315	445	26	592	3937	154	A8	CONSTANT	3.20	8625	5440	4690	3975	3750	3415
		51.8	17.5	33	23.3	155.0				46	10915	11995	10340	8765	8265	7530
500/70-24 IND (19.5L-24)	DW16L (DW15L; DW18L; TW15L; TW16L; TW18L)	1328	501	25	603	4023	157	A8	CYCLIC	3.20	9490	6890*	6190**	4580	4125	3755
		52.3	19.7	31	23.7	158.4				46	20920	15190*	13645**	10095	9095	8280
		1328	501	25	603	4023	157	A8	CONSTANT	3.20	9490	5980	5155	4375	4125	3755
		52.3	19.7	31	23.7	158.4				46	20920	13185	11365	9645	9095	8280
480/80-26 IND (18.4-26)	DW15L (DW16L; TW15L; TW16L)	1439	488	29	657	4544	160	A8	CYCLIC	3.20	10350	7515*	6750**	4995	4500	4095
		56.7	19.2	37	25.9	178.9				46	22820	16570*	14880**	11010	9920	9030
		1439	488	29	657	4544	160	A8	CONSTANT	3.20	10350	6525	5625	4770	4500	4095
		56.7	19.2	37	25.9	178.9				46	22820	14385	12400	10515	9920	9030
440/80-28 IND (16.9-28)	DW14L (DW13; DW13L; DW15L; TW13; TW14L; TW15L)	1430	440	35	654	4338	156	A8	CYCLIC	3.20	9200	6680*	6000**	4440	4000	3640
		56.3	17.3	44	25.7	170.8				46	20285	14725*	13230**	9790	8820	8025
		1430	440	35	654	4338	156	A8	CONSTANT	3.20	9200	5800	5000	4240	4000	3640
		56.3	17.3	44	25.7	170.8				46	20285	12785	11025	9350	8820	8025

\* Cyclic: One way distance up to 150 m (500 feet)

\*\* Cyclic: One way distance up to 600 m (2000 feet)

All tires listed are tubeless

