# **SOLIDEAL ECOMATIC TRACTION**

**BY CAMSO** 





## PERFORMANCE WHEN YOU NEED IT.

Best-in-class and ideal for low-intensity material handling applications. With its natural rubber compounds it delivers maximum life where premium technology is not required.

### camso.co

### **PERFORMANCE**

ENERGY SAVINGS

TIRE LIFE





FORMERLY CAMOPLAST SOLIDEAL

# **SOLIDEAL ECOMATIC TRACTION**

BY CAMSO

TIRE SIZE (1)	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY <sup>(2)</sup> Counterbalanced lift trucks (kg)					
	OVERALL DIAMETER	OVERALL WIDTH	REPLACEMENT OVERALL DIAMETER(3) (mm)	10 km/h		16 km/h		25 km/h	
	(mm)	(mm)		LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
14 x 4 1/2 x 8	354	114	308	1165	955	1040	875	845	695
16 x 5 x 10 1/2	404	127	363	1505	1240	1345	1130	1095	895
16 x 6 x 10 1/2	403	152	362	1905	1565	1700	1430	1385	1135
16 1/4 x 5 x 11 1/4	410	127	373	1525	1250	1360	1145	1105	905
16 1/4 x 6 x 11 1/4	410	152	373	1915	1570	1710	1435	1390	1140
18 x 6 x 12 1/8	454	152	410	2090	1715	1865	1565	1515	1245
18 x 7 x 12 1/8	454	178	410	2555	2100	2280	1915	1855	1520
18 x 8 x 12 1/8	454	203	410	3000	2465	2680	2250	2180	1785
21 x 7 x 15	531	178	485	2870	2360	2565	2155	2085	1710
21 x 8 x 15	530	203	485	3375	2775	3015	2530	2450	2010
22 x 9 x 16	554	229	510	4045	3325	3615	3035	2940	2140

#### **HUGE LUG DEPTH**

Increases life and traction

#### **NATURAL RUBBER COMPOUND**

 Provides good overall wear and performance

### AVAILABLE IN NON-MARKING COMPOUND



#### Remarks

- (1) Tolerances on wheel diameter Code designated sizes (in): nominal rim diameter +0.005"/-0" Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3  $\mu m$  Chamfer 5 mm wide @ 30°
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.
- (3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter. All specifications for non-marking tires are the same as the equivalent standard black tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

### AUTHORIZED DISTRIBUTOR:



To keep moving forward while staying true to our history, we're now the Road Free company.



