SOLIDEAL PORTMASTER by camso





NO STRONGER BIAS TYRE IN ITS SIZE

Its massive deep tread increases service life while providing the strongest carcass and optimal sidewall protection. This extremelly durable bias tyre is the ideal on hard surfaces and in highly abrasive environments.

PERFORMANCE





FORMERLY CAMOPLAST SOLIDEAL

PORT APPLICATIONS

SOLIDEAL PORTMASTER

T YRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾		ACTUAL TYRE DIMENSIONS				z₩	LOAD		LOAD CAPACITY (2)			
				Recom- mended	Alternative	Overall diameter		Original tread depth (mm)	Static loaded radius (mm)	INFLATION PRESSURE	INDEX & SPEED SYMBOL		Counterbalance Up to 25 km/h		d lift trucks (kg) Up to 35 km/h	
						(mm)	(mm)			(bar)			Load wheel	Steering wheel	Load wheel	Steering wheel
12.00-20	20	V3-02-14	200-20	8.50	8.00/10.00	1144	320	57	515	10.00	175	A5	9230	7100	8875	6570
12.00-20	28	V3-02-14	200-20	8.50	8.00/10.00	1130	320	57	514	10.00	175	A5	9230	7100	8875	6570



Remarks

- (1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyres are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size.

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tyre availability in your region.

AUTHORIZED DISTRIBUTOR:



FORMERLY CAMOPLAST SOLIDEAL