



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camso.co



SOLIDEAL RES 330

BY CAMSO



RESILIENT



**LONGEST LASTING TIRE
IN THE INDUSTRY FOR
LOW INTENSITY APPLICATIONS**

Best-in-class tire for low intensity applications*. A high performing tread rubber compound makes this tire a unique long lasting tire. Wide, aggressive tread with natural rubber compounds extends its life while resisting cutting and chunking. A steel-bead reinforced heel means the tire won't slip on the rim.

camso.co

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



SOLIDEAL RES 330
BY CAMSO



| TIRE SIZE | RIM SIZE ⁽¹⁾ | HEEL | | ACTUAL TIRE DIMENSIONS | | WEARABLE HEIGHT | LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (lbs) | |
|-------------------------------|-------------------------|--------|-------|---------------------------|------------------|--------------------|---|-----------------------|
| | | | | OVERALL DIAMETER | OVERALL WIDTH | | Load wheel | Steering wheel |
| | | NORMAL | QUICK | (in) | (in) | | Up to 16 mph (lbs) | Up to 16 mph (lbs) |
| 5.00-8 | 3.00D-8 | ■ | ■ | 17.72 | 4.53 | 1.61 | 3120 | 2405 |
| 15x4 1/2-8 (125/75-8) | 3.00D-8 | ■ | ■ | 14.57 | 4.57 | 1.08 | 2295 | 1765 |
| 16x6-8 (150/75-8) | 4.33R-8 | ■ | ■ | 16.10 | 5.75 | 1.34 | 3295 | 2535 |
| 18x7-8 (180/70-8) | 4.33R-8 | ■ | ■ | 17.52 | 5.83 | 1.57 | 4730 | 3640 |
| 6.00-9 | 4.00E-9 | ■ | ■ | 20.43 | 5.35 | 1.89 | 4155 | 3195 |
| 21x8-9 (200/75-9) | 6.00E-9 | ■ | ■ | 20.28 | 7.13 | 1.87 | 6075 | 4675 |
| 200/50-10 | 6.50F-10 | ■ | ■ | 17.72 | 7.60 | 1.28 | 5445 | 4190 |
| 6.50-10 | 5.00F-10 | ■ | ■ | 22.28 | 6.02 | 2.05 | 5160 | 3970 |
| 23x9-10 (225/75-10) | 6.50F-10 | ■ | ■ | 22.56 | 7.87 | 2.09 | 7595 | 5840 |
| 23x10-12 (250/60-12) | 8.00G-12 | ■ | ■ | 22.72 | 9.21 | 1.77 | 8310 | 6395 |
| 27x10-12 (250/75-12) | 8.00G-12 | ■ | ■ | 26.14 | 9.76 | 2.34 | 8600 | 6615 |
| 7.00-12 | 5.00S-12 | ■ | ■ | 25.39 | 6.50 | 2.19 | 6435 | 4940 |
| 28x9-15 (8.15-15 & 225/75-15) | 7.00-15 | ■ | ■ | 26.81 | 8.31 | 1.91 | 7595 | 5840 |
| 355/45-15 (28x12.5-15) | 9.75-15 | ■ | ■ | 26.57 | 11.50 | 1.87 | 12545 | 9645 |
| 355/65-15 (32x12.1-15) | 9.75-15 | ■ | ■ | 31.93 | 12.20 | 2.76 | 17195 | 13230 |
| 250-15 (250/70-15) | 7.00-15 | ■ | ■ | 27.83 | 8.35 | 2.07 | 10470 | 8045 |
| 250-15 (250/70-15) | 7.50-15 | ■ | ■ | 27.83 | 8.35 | 2.07 | 10470 | 8045 |
| 300-15 (315/70-15) | 8.00-15 | ■ | ■ | 31.81 | 9.84 | 2.74 | 12895 | 9920 |
| 7.00-15 | 5.50-15 | ■ | ■ | 28.39 | 7.28 | 2.17 | 7815 | 6010 |
| 7.50-15 | 6.50-15 | ■ | ■ | 29.25 | 7.99 | 2.30 | 8600 | 6615 |
| 8.25-15 | 6.50-15 | ■ | ■ | 31.65 | 7.99 | 2.70 | 10470 | 8045 |
| 10.00-20 | 7.50-20 | ■ | ■ | 39.76 | 10.00 | 3.21 | 13230 | 11025 |
| 10.00-20 | 8.00-20 | ■ | ■ | 39.76 | 10.00 | 3.21 | 13230 | 11025 |

WELL BALANCED RUBBER COMPOUND

- Operate in low intensity applications and offer the lowest operating cost

EXCEPTIONAL TREAD
RUBBER COMPOUND PROPERTIES

- Make this tire the longest lasting tire in the industry for low intensity applications*

STEEL BEAD REINFORCED HEEL

- Prevents rim slip

AGGRESSIVE DEEP TREAD DESIGN

- Provide great traction and stability

WEAR INDICATOR

- Ensures maximum tire utilization



* Based on internal testing

Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where there is a variation in load and/or speed.

For further details, please consult the technical department.

Loads are valid for intermittent service only. Intermittent service means a minimum load variation of 2.5. Does not include the additional weight of the solid tire when converting from pneumatics.

This document contains technical data of all products globally.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

AUTHORIZED DISTRIBUTOR: