

SOLIDEAL XTREME NM

BY CAMSO



RESILIENT



OPTIMAL NON-MARKING RESILIENT SOLUTION FOR HIGH INTENSITY APPLICATIONS

The preferred solution for high intensity applications requiring non-marking resilient tires. Its design increases stability, reduces vibration and improves operator comfort for lower heat build-up and enhanced tire life. Its clean running and versatility makes this tire the ideal solution for indoor operations and rental fleets.

camso.co

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



RESILIENT TIRES

SOLIDEAL XTREME NM
BY CAMSO

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
5.00-8	3.00D-8	■	■
15x4 1/2-8 (125/75-8)	3.00D-8	■	■
16x6-8 (150/75-8)	4.33R-8	■	■
18x7-8 (180/70-8)	4.33R-8	■	■
140/55-9	4.00E-9		■
6.00-9	4.00E-9	■	■
21x8-9 (200/75-9)	6.00E-9	■	■
180/60-10	5.00F-10		■
200/50-10	6.50F-10	■	■
6.50-10	5.00F-10	■	■
23x9-10 (225/75-10)	6.50F-10	■	■
23x10-12 (250/60-12)	8.00G-12	■	■
23x12-12 (315/45-12)	10.00G-12		■
27x10-12 (250/75-12)	8.00G-12		■
7.00-12	5.00S-12	■	■
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■
355/45-15 (28x12.5-15)	9.75-15	■	■
355/50-15	9.75-15		■
355/65-15 (32x12.1-15)	9.75-15		■
250-15 (250/70-15)	7.00-15	■	■
250-15 (250/70-15)	7.50-15	■	■
300-15 (315/70-15)	8.00-15	■	■
7.00-15	5.50-15	■	■
7.00-15	6.00-15	■	
7.50-15	6.50-15	■	■
8.25-15	6.50-15	■	■
355/50-20	10.00-20	■	■



CONTINUOUS CENTER LUG

- Reduces vibration which lowers heat build-up and increases life
- Increases operator comfort and slows wear on driveline components

NON-MARKING NATURAL RUBBER COMPOUND

- Prevents visible marks on the floor, ensuring a clean working environment
- Reduces chunking and cutting



WIDE TREAD PROFILE

- Increases lateral load stability
- Safer in high-lift and cornering situations

WEAR INDICATOR

- Ensures maximum tire utilization



**ALSO AVAILABLE
IN NON-MARKING ANTI-STATIC**

Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

camso.co

