

SOLIDEAL MAGNUM NM

BY CAMSO



RESILIENT



OPTIMAL NON-MARKING RESILIENT SOLUTION FOR MEDIUM INTENSITY APPLICATIONS

The preferred solution for medium intensity applications requiring non-marking resilient tires. Its wide profile, flat footprint and proven tread design provide maximum reliability, stability and traction. Its clean running makes this tire the ideal solution for indoor operations and rental fleets.

camso.co

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



RESILIENT TIRES

SOLIDEAL MAGNUM NM

BY CAMSO

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
3.00-4	2.10-4	■	
3.00-4	2.50C-4	■	
4.00-4	2.50C-4	■	
4.00-8	3.00D-8	■	■
5.00-8	3.00D-8	■	■
5.00-8	3.50-8	■	
15x4 1/2-8 (125/75-8)	3.00D-8	■	■
15x4 1/2-8 (125/75-8)	3.25I-8	■	
16x6-8 (150/75-8)	4.33R-8	■	■
18x7-8 (180/70-8)	4.33R-8	■	■
140/55-9	4.00E-9		■
6.00-9	4.00E-9	■	■
21x8-9 (200/75-9)	6.00E-9	■	■
200/50-10	6.50F-10	■	■
6.50-10	5.00F-10	■	■
23x9-10 (225/75-10)	6.50F-10	■	■
23x10-12 (250/60-12)	8.00G-12	■	■
27x10-12 (250/75-12)	8.00G-12		■
7.00-12	5.00S-12	■	■
150/100-13 (23x5)	3.75P-13	■	
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■
355/50-15	9.75-15	■	■
355/65-15 (32x12.1-15)	9.75-15	■	■
250-15 (250/70-15)	7.00-15	■	■
250-15 (250/70-15)	7.50-15	■	■
300-15 (315/70-15)	8.00-15	■	■
310-15 EW	8.00V-15	■	
7.00-15	5.50-15	■	■
8.25-15	6.50-15	■	■
9.00-20	7.00-20	■	
10.00-20	7.50-20	■	
10.00-20	8.00-20	■	
11.00-20	8.00-20	■	
12.00-20	8.00-20	■	
12.00-20	8.50-20	■	
14.00-24	10.00-24IRA	■	



WIDE PROFILE AND FLAT FOOTPRINT

- Increases stability and grip

LARGE TREAD BLOCKS AND DEEP LUGS

- Improves tire life and provides better traction

ESTABLISHED TREAD PATTERN DESIGN

- Delivers proven reliability for over 25 years



NON-MARKING NATURAL RUBBER COMPOUND

- Prevents visible marks on the floor, ensuring a clean working environment
- Reduces chunking and cutting

60J LINE

- Ensures maximum tire utilization

Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

camso.co

1910_MH_Magnum NM_ProdSheet_Letter_EN_V8

