

# SOLIDEAL RES 550 MAGNUM SERIES

BY CAMSO



RESILIENT



## MAXIMUM LIFESPAN FOR MEDIUM INTENSITY APPLICATIONS

The standard in reliability and the longest lasting tire in the industry for medium intensity applications\*. Its wide profile and flat footprint designed to maximize life. Its large tread blocks and deep lugs increase traction, while delivering maximum stability.

[camso.co](http://camso.co)

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



# RESILIENT TIRES

# SOLIDEAL RES 550 MAGNUM SERIES

BY CAMSO

TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
		NORMAL	QUICK
3.00 - 4	2.10-4	■	
3.00 - 4	2.50C-4	■	
4.00 - 4	2.10-4	■	
4.00 - 4	2.50C-4	■	
4.00 - 8	3.00D-8	■	■
5.00 - 8	3.00D-8	■	■
5.00 - 8	3.50-8	■	
15 x 4 1/2 - 8 (125/75-8)	3.00D-8	■	■
15 x 4 1/2 - 8 (125/75-8)	3.25I-8	■	
16 x 6 - 8 (150/75-8)	4.33R-8	■	■
18 x 7 - 8 (180/70-8)	4.33R-8	■	■
18 x 9 - 8	7.00E-8	■	
140 / 55 - 9	4.00E-9		■
6.00 - 9	4.00E-9	■	■
21 x 8 - 9 (200/75-9)	6.00E-9	■	■
200 / 50 - 10	6.50F-10	■	■
6.50 - 10	5.00F-10	■	■
6.50 - 10	5.50F-10	■	
23 x 9 - 10 (225/75-10)	6.50F-10	■	■
7.50 - 10	5.00F-10	■	
7.50 - 10	5.50F-10	■	■
23 x 10 - 12 (250/60-12)	8.00G-12	■	■
27 x 10 - 12 (250/75-12)	8.00G-12	■	■
7.00 - 12	5.00S-12	■	■
8.25 - 12	5.00S-12	■	
150 / 100 - 13 (23x5)	3.75P-13	■	■
28 x 9 - 15 (8.15-15 & 225/75-15)	6.50-15	■	
28 x 9 - 15 (8.15-15 & 225/75-15)	7.00-15	■	■

TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL	
		NORMAL	QUICK
355 / 50 - 15	9.75-15	■	■
355 / 65 - 15 (32x12.1-15)	9.75-15	■	■
250 - 15 (250/70-15)	7.00-15	■	■
250 - 15 (250/70-15)	7.50-15	■	■
300 - 15 (315/70-15)	8.00-15	■	■
310 - 15 EW	8.00V-15	■	
5.50 - 15	4.50E-15SDC	■	
6.00 - 15	4.50E-15SDC	■	
7.00 - 15	5.50-15	■	■
7.00 - 15	6.00-15	■	
7.50 - 15	5.50-15	■	■
7.50 - 15	6.00-15	■	
7.50 - 15	6.50-15	■	■
8.25 - 15	5.50-15	■	■
8.25 - 15	6.50-15	■	■
7.50 - 16	6.00-16	■	
9.00 - 20	7.00-20	■	
10.00 - 20	6.50-20	■	
10.00 - 20	7.00-20	■	
10.00 - 20	7.50-20	■	
10.00 - 20	8.00-20	■	
11.00 - 20	7.50-20	■	
11.00 - 20	8.00-20	■	
12.00 - 20	8.00-20	■	
12.00 - 20	8.50-20	■	
14.00 - 24	10.00-24IRA	■	
14.00 - 25	11.25-25	■	
16.00 - 25	11.25-25	■	



**WIDE PROFILE AND FLAT FOOTPRINT**

- Increases stability and grip

**LARGE TREAD BLOCKS AND DEEP LUGS**

- Maximizes life and traction

**ESTABLISHED TREAD PATTERN DESIGN**

- Proven reliability for over 25 years



**EXCEPTIONAL TREAD RUBBER COMPOUND PROPERTIES**

- Make this tire the longest lasting tire in the industry for medium intensity applications\*

**60J LINE**

- Ensures maximum tire utilization

\*Based on internal tests

**AVAILABLE IN NON-MARKING**



Remarks

(1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286.  
Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

**camso.co**

1910\_MH\_RES\_ProdSheet\_RES550\_LETTER\_EN\_V3 - PRINTED IN CANADA

