SOLIDEAL RES XTREME NMAS



RESILIENT

BY CAMSO





USAGE INTENSITY

COMFORT

ENGINEERED TO PREVENT STATIC ELECTRICITY BUILD-UP IN HIGH INTENSITY APPLICATIONS

The ultimate resilient tire to resolve the important safety issue of static electricity generated by non-marking tires. Its design reduces vibration which increases operator comfort and lowers heat build-up for enhanced tire life.

camso.co

| | | ' | <u> </u> | | | <u> </u> | | |
|----------|----------|----------|----------|---|--|----------|----------|--|
| PERFO | RM | ANC | E | | | | | |
| ENER | GY S | SAVI | NGS | 3 | | | | |
| TIRE L | / IFF | | | | | | | |
|) |) |) |) | | |) |) | |



SOLIDEAL RES XTREME NMAS



BY CAMSO

| | RIM SIZE (1) | HEEL | | |
|----------------|-----------------------|-----------|--------|-------|
| | TIRE SIZE | RIWI SIZE | NORMAL | QUICK |
| 5.00 - 8 | | 3.00D-8 | | • |
| 15 x 4 1/2 - 8 | (125/75-8) | 3.00D-8 | | • |
| 16 x 6 - 8 | (150/75-8) | 4.33R-8 | | • |
| 18 x 7 - 8 | (180/70-8) | 4.33R-8 | | • |
| 140 / 55 - 9 | | 4.00E-9 | | • |
| 6.00 - 9 | | 4.00E-9 | | • |
| 21 x 8 - 9 | (200/75-9) | 6.00E-9 | | • |
| 180 / 60 - 10 | | 5.00F-10 | | - |
| 200 / 50 - 10 | | 6.50F-10 | | • |
| 6.50 - 10 | | 5.00F-10 | | • |
| 23 x 9 - 10 | (225/75-10) | 6.50F-10 | | • |
| 23 x 10 - 12 | (250/60-12) | 8.00G-12 | | - |
| 23 x 12 - 12 | (315/45-12) | 10.00G-12 | | • |
| 27 x 10 - 12 | (250/75-12) | 8.00G-12 | | • |
| 7.00 - 12 | | 5.00S-12 | | - |
| 28 x 9 - 15 | (8.15-15 & 225/75-15) | 7.00-15 | | • |
| 355 / 45 - 15 | (28x12.5-15) | 9.75-15 | | • |
| 355 / 50 - 15 | | 9.75-15 | | • |
| 355 / 65 - 15 | (32x12.1-15) | 9.75-15 | | • |
| 250 - 15 | (250/70-15) | 7.00-15 | | • |
| 250 - 15 | (250/70-15) | 7.50-15 | - | - |
| 300 - 15 | (315/70-15) | 8.00-15 | - | • |
| 7.00 - 15 | | 5.50-15 | - | • |
| 7.00 - 15 | | 6.00-15 | - | |
| 7.50 - 15 | | 6.50-15 | - | - |
| 8.25 - 15 | | 6.50-15 | - | - |
| 355 / 50 - 20 | | 10.00-20 | | - |

WIDE TREAD PROFILE

Increases lateral load stability

• Safer in high-lift and cornering situation

CONTINUOUS CENTER LUG

- Reduces vibrations which lowers heat build-up and increases life
- Increases operator comfort and slows wear on driveline components





WEAR INDICATOR

• Ensures maximum utilization

PATENTED ANTI-STATIC TECHNOLOGY

 Prevents static electricity build-up to eliminate the risk of safety issues, fires and facility damages

Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.



