SOLIDEAL AIR 570 BY CAMSO






LOW ROLLING RESISTANCE SOLUTION FOR ELECTRIC TRUCKS

Best all-around pneumatic tire for electric forklifts. Engineered to deliver low rolling resistance and reduced vibrations for optimal performance.

PERFORMANCE





INDUSTRIAL PNEUMATIC TIRES

SOLIDEAL AIR 570 BY CAMSO

TIRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
5.00-8	8	JS2	90 - 8	3.00 D	3.251/3.751
15 x 4 1/2-8	12	JS2	90 - 8	3.00 D	3.25l
16 x 6-8	10	V3-02-5	130 - 8	4.33 R	-
18 x 7-8	14	V3-02-07	130 - 8	4.33 R	5.00F
18 x 7-8	16	V3-02-07	130 - 8	4.33 R	5.00F
6.00-9	10	JS2	125 - 9	4.00 E	-
21 x 8-9	16	JS2	180 - 9	6.00 E	7.00E
23 x 9-10	16	JS2	180 - 10	6.50 F	-
23 x 9-10	18	V3-02-07	180 - 10	6.50 F	-
28 x 9-15	14	TR75A	180 - 15 HD	7.00	-
28 x 9-15	18	V3-02-08	180 - 15 HD	7.00	-





Remarks

- (1) Consult tire and wheel manufacturer for confirmation of the suitability of the tire/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tire are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use. but rather that there is a variation in load and/or speed.

* Tube size is identical to tire size

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tires primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tires come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

