

SOLIDEAL RIB

BY CAMSO



GROUND SUPPORT
EQUIPMENT



PERFECT SOLUTION TO PREVENT SNAKING

Mainly designed for ground support equipment applications, this tire offers high cornering capability, low vibration and long lifespan.

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



STABILITY



GROUND SUPPORT EQUIPMENT

SOLIDEAL RIB
BY CAMSO

Industrial pneumatic. Also available in solid resilient version

TIRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
4.00-8 (4.80-8)	8	JS2	90-8	3.25I	3.00D

CIRCUMFERENTIAL RIBS

- Provide high cornering capability and prevents snaking

EXCELLENT TREAD RUBBER COMPOUND

- Increases tire life

LOW ROLLING RESISTANCE
RUBBER COMPOUND

- Optimizes battery life and fuel consumption



Remarks

(1) Consult tire and wheel manufacturer for confirmation of the suitability of the tire/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tires are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tire size.

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tires primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tires come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

