

SOLIDEAL PON 550 NM

BY CAMSO



PRESS-ON
TIRES



NON-MARKING WITH MAXIMUM LIFE FOR MEDIUM INTENSITY APPLICATIONS

Enhanced non-marking natural rubber compound ensures clean working environment, low rolling resistance and improved thermal performance. Its wide profile, flat footprint and proven tread pattern design provide maximum stability and traction. Especially designed to provide maximum lifespan for medium intensity applications requiring non-marking press-on tires.

camsso.co

PERFORMANCE

INTENSITY



ENERGY SAVINGS



TIRE LIFE



PRESS-ON TIRES

SOLIDEAL PON 550 NM

BY CAMSO



TIRE SIZES ⁽¹⁾					
10 x 5 x 6 1/2	16 x 6 x 10 1/2	16 1/4 x 7 x 11 1/4	18 x 9 x 12 1/8	22 x 7 x 16	28 x 10 x 22
13 1/2 x 5 1/2 x 8	16 x 7 x 10 1/2	18 x 5 x 12 1/8	21 x 7 x 15	22 x 8 x 16	28 x 12 x 22
14 x 4 1/2 x 8	15 x 5 x 11 1/4	18 x 6 x 12 1/8	21 x 8 x 15	22 x 9 x 16	
14 x 5 x 10	16 1/4 x 5 x 11 1/4	18 x 7 x 12 1/8	21 x 9 x 15	22 x 10 x 16	
16 x 5 x 10 1/2	16 1/4 x 6 x 11 1/4	18 x 8 x 12 1/8	22 x 6 x 16	22 x 12 x 16	

WIDE PROFILE AND FLAT FOOTPRINT

- Increases stability and grip

LOW ROLLING RESISTANCE COMPOUND

- Increases energy efficiency and thermal performance

NON-MARKING NATURAL RUBBER COMPOUND

- Prevents visible marks on the floor ensuring a clean working environment
- Reduces chunking and cutting

UNIQUE TWO-STAGE CONSTRUCTION

- Inner thermal-layer reduces heat build-up for enhanced tire life

Remarks

(1) Tolerances on wheeldiameter • Code designated sizes (inch sizes): nominal rim diameter +0.005"/-0" • Metric sizes (mm sizes): h11 according to ISO/R286 • Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°

For the Magnum Smooth and Magnum Traction Non-Marking tires, please check with your Camso representative or your nearest Camso dealer.

camso.co

