

SOLIDEAL SM

BY CAMSO



RESILIENT



PUNCTURE-FREE TIRE DESIGNED SPECIFICALLY FOR TRAILER AND FORKLIFT APPLICATIONS

All around solid resilient tire for both trailer and forklift applications with an outstanding tire lifetime. The smooth tread offers great cornering capabilities and a comfortable ride with no vibrations. The low rolling resistance reduces the energy use of the machine.

camso.co

PERFORMANCE

COMFORT



ENERGY SAVING



PUNCTURE RESISTANCE



TIRE LIFE



RESILIENT TIRES

SOLIDEAL SM

BY CAMSO

TIRE SIZE	TREAD PATTERN	RIM SIZE ⁽¹⁾	HEEL	
			NORMAL	QUICK
100 / 50 - 8	SM	3.00D-8	■	
100 / 80 - 8	SM	2.50C-8	■	
5.00 - 8	SM	3.00D-8	■	
15 x 4 1/2 - 8	SM	3.00D-8		
16 x 6 - 8	SM	4.33R-8		
18 x 7 - 8	SM	4.33R-8	■	■
6.00 - 9	SM	4.00E-9	■	
21 x 7 - 10	SM	5.00F-10		■
6.50 - 10	SM	5.00F-10	■	
7.00 - 12	SM	5.00S-12	■	
300 - 15	SM	8.00-15		■
8.25 - 15	SM	6.50-15	■	■
6.50 - 16	SM	5.50-16	■	
10.00 - 20	SM	7.50-20	■	
10.00 - 20	SM	8.00-20	■	
12.00 - 20	SM	8.00-20	■	
12.00 - 20	SM	10.00-20	■	
12.00 - 24	SM	10.00-24IRA	■	

SMOOTH SLICK TIRE TREAD

- Great cornering capabilities
- No vibration for increased driver comfort and low wear on the machine components

LOW ROLLING RESISTANCE

- Increases battery life and reduces fuel consumption



EXCELLENT TREAD RUBBER COMPOUND

- Enhances tire performance and life

Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.