

SOLIDEAL RIB

BY CAMSO



GROUND SUPPORT
EQUIPMENT



PERFECT SOLUTION TO PREVENT SNAKING

Mainly designed for ground support equipment applications, this tyre offers high cornering capability, low vibration and long lifespan.

PERFORMANCE

TYRE LIFE



PUNCTURE RESISTANCE



STABILITY



GROUND SUPPORT EQUIPMENT

SOLIDEAL RIB BY CAMSO

These data refer to the industrial pneumatic version.
A solid resilient version is also available.

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE (1)	
				Recommended	Alternative
4.00-8 (4.80-8)	8	JS2	90-8	3.25I	3.00D

CIRCUMFERENTIAL RIBS

- Provide high cornering capability and prevents snaking

LOW ROLLING RESISTANCE RUBBER COMPOUND

- Optimizes battery life and fuel consumption



EXCELLENT TREAD RUBBER COMPOUND

- Increases tyre life

Remarks

(1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyres are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size.

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tyre availability in your region.

camso.co

2405_MH_ProductSheet_RIB_BIAS_A4_EN_V1 - PRINTED IN CANADA

