

CAMSO

# UTV 4S1

## Tough and ready for the long haul

This track system reaches the next level of performance in any conditions. You simply won't find another track kit offering this level of ride quality, performance, durability and ease of use. It's the best choice for any applications including deep snow, swamps, marshes, mud and muskeg.



MACHINE  
**400<sup>CC</sup> TO  
1000<sup>CC</sup>**



SIDE-BY-SIDE



SPECIFICATIONS

RUBBER TRACK	
Width	Front: 12.5 in. (318 mm) Rear: 14 in. (356 mm)
Length	Front: 98.5 in. (2507 mm) Rear: 116.7 in. (2964 mm)
Lug height	Front: 1.125 in. (29 mm) Rear: 1.125 in. (29 mm)
Rubber track	Front: flex Rear: flat
PERFORMANCE	
Ground surface	2520 sq. in. (1.62 m²)
Maintained speed (average)	2/3

Please find more specifications on page 20

INDUSTRY'S FIRST

Flex-Track design

**Front-mounted tracks with flexible sides and slight curve toward the inside**

Stable handling  
More comfortable ride than traditional flat tracks  
Precise steering for pleasant long-distance riding and long working hours

Bearing housing

**Triple bearing design with oil bath lubrication**

Enduring bearing durability  
Stainless sleeves for greater reliability

Solid steel frame


**Open light-weight design**

Proven durability and performance  
Easily sheds snow, mud, and debris

Puncture-proof tires

**High-density tire with adjusted shape**

Reduced friction and wear  
Maximizes shock absorption to improve ride quality  
Delivers trouble-free performance



**Tandem stabilizer and wheel shaft**

**Rubber-mounted shafts**  
Eliminates need for greasing  
Absorbs shocks for a smoother and more stable ride

Wheel and seal

**ENHANCED Wheel seal design**  
Sturdy sealing and guiding reduce wear  
Eliminates water absorption due to temperature variations