

Sno X



High-performance designs, custom-tailored for snocross competition, tested and proven by select OE factory race teams. Fitments are available for all types of competition vehicles. Lug geometry and specialty rubber compounds provide firm lugs for the best holeshots, keeping you out in front of the pack.

- **1.75" lugs, the choice of professional racers**
- **Extra hard outside lug for the best holeshots**
- **ISR approved for use in mod class**

Model 9293R /9294R

MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CONFIG.
9067R ¹	15" x 121" (38 cm x 307 cm)	1.75" (44 mm)	41 lb. (18.5 kg)	2.52" (64 mm)	Full
9068R ¹	15" x 128" (38 cm x 325 cm)	1.75" (44 mm)	43 lb. (19.5 kg)	2.52" (64 mm)	Full
9205R ¹	15" x 136" (38 cm x 345 cm)	1.75" (44 mm)	46 lb. (20.75 kg)	2.52" (64 mm)	Full
9206R ¹	15" x 144" (38 cm x 366 cm)	1.75" (44 mm)	48 lb. (21.75 kg)	2.52" (64 mm)	Full
9207R ²	15" x 137" (38 cm x 348 cm)	1.75" (44 mm)	48 lb. (21.75 kg)	2.86" (73 mm)	Full
9208R ²	15" x 146" (38 cm x 371 cm)	1.75" (44 mm)	49 lb. (22.25 kg)	2.86" (73 mm)	Full
9293R	15" x 120" (38 cm x 305 cm)	1.75" (44 mm)	37 lb. (16.75 kg)	2.86" (73 mm)	Full
9294R	15" x 129" (38 cm x 326 cm)	1.75" (44 mm)	40 lb. (18.25 kg)	2.86" (73 mm)	Full

▲ Embedded sharp tip lug studs

■ Single-ply construction

● Enhanced stud easy tracks

¹ BackCountry design see p. 27

² BackCountry X design see p. 27