

CAMSO

Ice and Grass Drag

Ahead of the pack

Designed specifically for the intense acceleration of drag racing, where the first seconds of the race make the difference between winning and losing.

- Low-resistance 0.525" lugs require less fuel for optimal straight-line acceleration
- 13.5" width available for lightweight and maximum top speed
- Multiple lengths for a wide variety of race chassis

MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CONFIG.
9084R	13.5" x 144" (34 cm x 366 cm)	0.525" (13 mm)	35 lb. (15.75 kg)	2.52" (64 mm)	Full
9359R	14" x 144" (36 cm x 366 cm)	1" (25 mm)	38 lb. (17.25 kg)	2.52" (64 mm)	Full
9811R	15" x 121" (38 cm x 307 cm)	0.525" (13 mm)	33 lb. (15 kg)	2.52" (64 mm)	Full
9929R	13.5" x 136" (34 cm x 345 cm)	0.525" (13 mm)	31 lb. (14 kg)	2.52" (64 mm)	No windows / clips
9976R	13.5" x 144" (34 cm x 366 cm)	0.525" (13 mm)	33 lb. (15 kg)	2.52" (64 mm)	No windows / clips