

WE START

WHERE

THE ROAD

ENDS



**CONSTRUCTION
TIRES & TRACKS
DATABOOK 2018**

GENERAL REFERENCE DATA

LOAD INDEX EQUIVALENCES in kg and lb

LI	kg	lb	LI	kg	lb	LI	kg	lb	LI	kg	lb	LI	kg	lb	LI	kg	lb
100	800	1,764	121	1,450	3,200	142	2,650	5,840	160	4,500	9,920	181	8,250	18,190	202	15,000	33,070
101	825	1,819	122	1,500	3,310	143	2,725	6,010	161	4,625	10,200	182	8,500	18,740	203	15,500	34,180
102	850	1,874	123	1,550	3,420	144	2,800	6,170	162	4,750	10,470	183	8,750	19,290	204	16,000	35,280
103	875	1,929	124	1,600	3,530	145	2,900	6,390	163	4,875	10,750	184	9,000	19,840	205	16,500	36,380
104	900	1,985	125	1,650	3,640	146	3,000	6,610	164	5,000	11,020	185	9,250	20,390	206	17,000	37,480
105	925	2,040	126	1,700	3,750	147	3,075	6,780	165	5,150	11,350	186	9,500	20,940	207	17,500	38,590
106	950	2,095	127	1,750	3,860	148	3,150	6,950	166	5,300	11,690	187	9,750	21,500	208	18,000	39,690
110	1,060	2,337	128	1,800	3,970	149	3,250	7,170	170	6,000	13,230	188	10,000	22,050	209	18,500	40,790
111	1,090	2,403	129	1,850	4,080	150	3,350	7,390	171	6,150	13,560	189	10,300	22,710	210	19,000	41,890
112	1,120	2,470	130	1,900	4,190	151	3,450	7,610	172	6,300	13,890	190	10,600	23,370	211	19,500	43,000
113	1,150	2,536	131	1,950	4,300	152	3,550	7,830	173	6,500	14,330	191	10,900	24,030	212	20,000	44,100
114	1,180	2,602	132	2,000	4,410	153	3,650	8,050	174	6,700	14,770	192	11,200	24,690	213	20,600	45,420
115	1,215	2,679	133	2,060	4,540	154	3,750	8,270	175	6,900	15,210	193	11,500	25,360	214	21,200	46,750
116	1,250	2,756	134	2,120	4,670	155	3,875	8,540	176	7,100	15,650	194	11,800	26,020	215	21,800	48,070
117	1,285	2,833	135	2,180	4,810	156	4,000	8,820	177	7,300	16,090	195	12,150	26,790	216	22,400	49,390
118	1,320	2,911	136	2,240	4,940	157	4,125	9,090	178	7,500	16,530	196	12,500	27,560	217	23,000	50,700
119	1,360	2,999	140	2,500	5,510	158	4,250	9,370	179	7,750	17,090	200	14,000	30,870	218	23,600	52,040
120	1,400	3,090	141	2,575	5,680	159	4,375	9,650	180	8,000	17,640	201	14,500	31,970	219	24,300	53,580

INFLATION UNITS

Kpa	Bar	Psi	kg/cm²
100	1	14.5	1.0
150	1.5	22	1.5
200	2	29	2
250	2.5	36	2.6
300	3	44	3.1
350	3.5	51	3.6
400	4	58	4.1
450	4.5	65	4.6
500	5	73	5.1
550	5.5	80	5.6
600	6	87	6.1
650	6.5	94	6.6
700	7	102	7.1
750	7.5	109	7.7
800	8	116	8.2
850	8.5	123	8.7
900	9	131	9.2
950	9.5	138	9.7
1000	10	145	10.2
1050	10.5	152	10.7

SPEED INDEX

Speed km/h	Speed index
5	A1
10	A2
15	A3
20	A4
25	A5
40	A8
50	B

DEFINITIONS

O.D.	Overall Diameter
O.W.	Overall Width
TL	Tubeless
TT	Tubetype
PR	Plyrating
O.T.D.	Original Tread Depth
S.L.R.	Static Loaded Radius
R.C.	Rolling Circumference
M.D.S.	Minimum Dual Spacing

TABLE OF CONTENTS

CONSTRUCTION TIRES

TIRES FOR SKID STEER LOADERS

CAMSO SKS 732 _____ 4

CAMSO SKS 532 _____ 5

CAMSO SKS 332 Formerly Solideal Gripper _____ 6

CAMSO SKS 753 _____ 7

CAMSO SKS 775 _____ 8

CAMSO HAULER SKS _____ 10

CAMSO XTRA WALL _____ 12

CAMSO HAULER SKZ _____ 14

CAMSO SKS 774 Formerly Solideal Hauler XD44 _____ 16

CAMSO SKS 511 Formerly Solideal SKS R1 _____ 17

CAMSO SKS 792S Formerly Solideal SolidAir SKS _____ 18

CAMSO SKS 782S Formerly Solideal Safetymaster SKS _____ 19

CAMSO SKS 793S _____ 20

CAMSO SKS 796S Formerly Solideal SolidAir SM _____ 21

CAMSO SKS 786S Formerly Solideal Safetymaster SM _____ 22

TIRES FOR BACKHOE LOADERS

CAMSO SL R4 _____ 24

CAMSO BHL 532 Formerly Solideal SLA R4 _____ 28

CAMSO BHL 753 Formerly Solideal BHZ _____ 30

CAMSO BHL 530 Formerly Solideal MR F3 _____ 32

TIRES FOR TELESCOPIC HANDLERS AND MOTOR GRADERS

CAMSO TLH 732 _____ 34

CAMSO TLH 532 Formerly Solideal TH2 _____ 36

CAMSO TLH 753 _____ 38

CAMSO SL G2 _____ 40

CAMSO SL G3 _____ 42

TIRES FOR TELESCOPIC HANDLERS

CAMSO TLH 792S Formerly Solideal SolidAir TLH _____ 44

TIRES FOR TELESCOPIC HANDLERS, COMPACT WHEEL LOADERS AND MINI-DUMPERS

CAMSO MPT 552 _____ 46

CAMSO MPT 753 _____ 48

CAMSO TM R4 _____ 50

CAMSO 4L I3 _____ 52

CAMSO 4L R1 _____ 54

CAMSO TM R1 _____ 56

CAMSO MPT 793S _____ 57

CAMSO MPT 532R _____ 58

CAMSO MPT 553R _____ 59

TIRES FOR WHEEL EXCAVATORS

CAMSO WL _____ 60

CAMSO WEX 552 Formerly Solideal WEX _____ 62

CAMSO WEX 583S Formerly Solideal Bagger HT _____ 64

TIRES FOR COMPACTION EQUIPMENT

CAMSO CMP 533 _____ 65

CAMSO CMP 576 Formerly Solideal SM C1 _____ 66

TIRES FOR MINE SERVICE

CAMSO MST 776 _____ 67

TIRES FOR WHEEL LOADERS, ARTICULATED DUMP TRUCKS AND MOTOR GRADERS

CAMSO WHL 753R Formerly Solideal SRGP _____ 68

CAMSO ADT 753R Formerly Solideal SRAT _____ 70

CAMSO WHL 775R Formerly Solideal SRLD L5 _____ 72

CAMSO WHL 776R Formerly Solideal SRLS L5S _____ 74

CAMSO GRD 533R _____ 76

CAMSO EMT 553R _____ 77

CAMSO LM L2 _____ 78

CAMSO LM L3 _____ 80

CAMSO WHL 773 _____ 84

CAMSO WHL 775 _____ 86

CONSTRUCTION TRACKS

TRACKS FOR MINI-EXCAVATORS

CAMSO MEX HXD _____ 88

CAMSO MEX SD _____ 90

TRACKS FOR COMPACT TRACK LOADERS

CAMSO CTL HXD _____ 92

CAMSO CTL SD _____ 93

SPROCKETS FOR COMPACT TRACK LOADERS

CAMSO CTL SPROCKET _____ 94

TRACKS FOR MULTI-TERRAIN LOADERS

CAMSO MTL HXD _____ 95

OTT TRACKS FOR SKID STEER LOADERS

CAMSO OTT HXD _____ 96

TRACKS FOR PAVERS

CAMSO HXD SMOOTH _____ 97

CAMSO HXD CHEVRON _____ 98

TRACKS FOR CARRIERS

CAMSO CARRIER HXD _____ 99

COMPLETE LINE OVERVIEW _____ 101



CAMSO SKS 732

THE ULTIMATE OFF-ROAD SKID STEER TIRE SOLUTION

FEATURES

- Massive tread depth with optimized lug-to-void ratio
- New impact guard sidewall design
- Self-cleaning stepped tread
- Void guard tread impact protection

BENEFITS

- Maximizes off-road durability and traction
- Deflects debris to better protect sidewalls and reduce stress cracking
- Maximizes cleanout for improved off-road traction
- Protects from tread punctures to minimize flat tires

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.		
A	10-16.5 NHS	10	TL	8.25	-	780	276	23	359	2361	-	-
						30.6	10.4	29	14.1	93.0		
B	12-16.5 NHS	10	TL	9.75	-	836	330	25	585	2520	-	-
						32.9	13.0	31	23.0	99.2		
C	12-16.5 NHS	12	TL	9.75	-	833	330	26	383	2512	-	-
						32.5	13.0	33	15.1	98.9		
D	14-17.5 NHS	14	TL	10.5	-	935	360	32	425	2845	-	-
						36.8	14.2	40	16.7	112.0		

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]						
		STATIC	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	30 km/h 20 mph	40 km/h 25 mph	50 km/h 30 mph
A	5.20	3375	2135	1685	1625	1450	1410	1345
	75	7440	4710	3720	3580	3205	3110	2965
B	4.50	4015	2540	2005	1930	1725	1675	1600
	65	8850	5600	4425	4255	3810	3695	3530
C	5.50	4525	2865	2265	2175	1950	1890	1805
	80	9985	6320	4995	4805	4300	4170	3980
D	5.50	6125	3875	3060	2945	2635	2560	2440
	80	13495	8540	6745	6490	5805	5635	5380



CAMSO SKS 532

BEST GENERAL DUTY SOLUTION

FEATURES

- Extra-deep tread depth with curved tread lugs
- Self-cleaning stepped tread
- New impact guard sidewall design
- Void guard impact protection

BENEFITS

- Ensures great durability and extra traction
- Maximizes cleanout for improved off-road traction
- Deflects debris to better protect sidewalls and reduce stress cracking
- Protects from tread punctures to minimize flat tires

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.		
A	10-16.5 NHS	10	TL	8.25	-	768	278	18	356	2316	-	-
						30.2	10.9	23	14.0	91.2		
B	12-16.5 NHS	12	TL	9.75	-	831	330	19	383	2513	-	-
						32.7	13.0	24	15.1	98.9		
C	14-17.5 NHS	14	TL	10.5	-	925	351	24	423	2789	-	-
						36.4	13.8	30	16.7	109.8		

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]						
		STATIC	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	30 km/h 20 mph	40 km/h 25 mph	50 km/h 30 mph
A	5.20	3375	2135	1685	1625	1450	1410	1345
	75	7440	4710	3720	3580	3205	3110	2965
B	5.50	4525	2865	2265	2175	1950	1890	1805
	80	9985	6320	4995	4805	4300	4170	3980
C	5.50	6125	3875	3060	2945	2635	2560	2440
	80	13495	8540	6745	6490	5805	5635	5380



CAMSO SKS 332

Formerly Solideal Gripper

RELIABLE PERFORMANCE AND QUALITY

FEATURES

- Deep lug design
- Lower lug-to-void ratio
- Premium rubber compounds

BENEFITS

- Provides good durability and traction in light-duty conditions
- Provides good traction in off-road conditions
- Provides good chunk and tear resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.		
A	10-16.5 NHS	8	TL	8.25	-	762	271	14	345	2313	-	-
						30.0	10.7	18	13.6	91.1		
B	12-16.5 NHS	10	TL	9.75	-	819	318	18	370	2521	-	-
						32.2	12.5	23	14.6	99.3		

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]						
		STATIC	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	30 km/h 20 mph	40 km/h 25 mph	50 km/h 30 mph
A	4.10	2970	1880	1485	1430	1280	1240	1185
	60	6540	4140	3270	3145	2815	2730	2610
B	4.50	4015	2540	2005	1930	1725	1675	1600
	65	8850	5600	4425	4255	3810	3695	3530



CAMSO SKS 753

VERSATILITY AND DURABILITY

FEATURES

- Innovative non-directional tread pattern
- High lug-to-void ratio
- New impact guard sidewall design
- Stepped shoulder lugs

BENEFITS

- Optimizes durability and versatility on mixed and hard surfaces
- Provides excellent wear and puncture resistance
- Deflects debris to better protect sidewalls and reduce stress cracking
- Enhances traction in softer surfaces

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.		
A	10-16.5 NHS	10	TL	8.25	-	791	268	29	367	2386	-	-
						31.1	10.6	37	14.4	93.9		
B	12-16.5 NHS	12	TL	9.75	-	837	326	29	388	2496	-	-
						33.0	12.8	37	15.3	98.3		
C	14-17.5 NHS	14	TL	10.5	-	950	357	40	436	2861	-	-
						37.4	14.1	50	17.2	112.6		

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]						
		STATIC	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	30 km/h 20 mph	40 km/h 25 mph	50 km/h 30 mph
A	5.20	3375	2135	1685	1625	1450	1410	1345
	75	7440	4710	3720	3580	3205	3110	2965
B	5.50	4525	2865	2265	2175	1950	1890	1805
	80	9985	6320	4995	4805	4300	4170	3980
C	5.50	6125	3875	3060	2945	2635	2560	2440
	80	13495	8540	6745	6490	5805	5635	5380



CAMSO SKS 775

THE VERSATILE HEAVY-DUTY CHOICE

FEATURES	BENEFITS	PERFORMANCE
<ul style="list-style-type: none"> Massive 50/32 tread depth with high lug-to-void ratio Innovative tread pattern New impact guard sidewall design Stepped tread design shoulder lugs 	<ul style="list-style-type: none"> Maximizes tire life and tread impact resistance Optimizes traction and versatility for mixed and hard surface applications Deflects debris to better protect sidewalls and reduce stress cracking Provides lower cost per hour and quicker installation 	<p>TIRE LIFE</p> <p>PUNCTURE RESISTANCE</p> <p>TRACTION</p>

#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.		
A	10-16.5 NHS	10	TL	8.25	-	780	270	38	364	2365	-	-
						30.7	10.6	48	14.3	93.1		
B	12-16.5 NHS	12	TL	9.75	-	850	328	40	394	2575	-	-
						33.5	12.9	50	15.5	101.4		

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]						
		STATIC	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	30 km/h 20 mph	40 km/h 25 mph	50 km/h 30 mph
A	5.20	3375	2135	1685	1625	1450	1410	1345
	75	7440	4710	3720	3580	3205	3110	2965
B	5.50	4525	2865	2265	2175	1950	1890	1805
	80	9985	6320	4995	4805	4300	4170	3980





CAMSO XTRA WALL

BUILT FOR TOUGH OFF-ROAD APPLICATIONS

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE [bar] [psi]
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.			
5.70-12 NHS	4	TL	-	4.50-1-70 4.50-1-90 5JA	566	158	13	267	1707	-	-	4.10
					22.3	6.2	16	10.5	67.2			60
23 x 8.50-12 SS	6	TL	-	7.00-1-70 7.00-1-90 7JA	572	213	15	256	1723	-	-	3.40
					22.5	8.4	18	10.1	67.8			50
26 x 12.00-12 SS	10	TL	-	-	655	297	22	297	1955	-	-	4.50
					25.8	11.7	27	11.7	77.0			65
27 x 10-12	14	TT	8.00G	-	689	261	19	301	2054	143	A5	7.00
					27.1	10.3	24	11.9	80.9			102
7.00-15 SS	6	TL	-	5.50F 6LB	780	221	19	363	2359	-	-	4.10
					30.7	8.7	24	14.3	92.9			60
27 x 8.50-15 NHS	6	TL	7JA	-	681	225	15	309	2026	96	B	3.10
					26.8	8.9	19	12.2	79.8			45
31 x 15.50-15 NHS	8	TL	13LB	-	788	384	24	365	2352	116	B	3.10
					31.0	15.1	30	14.4	92.6			45
10-16.5 NHS	8	TL	8.25	-	766	277	17	349	2277	-	-	4.10
					30.1	10.9	21	13.7	89.6			60
10-16.5 NHS	10	TL	8.25	-	765	276	18	348	2306	-	-	5.20
					30.1	10.9	23	13.7	90.8			75
10-16.5 NHS	12	TL	8.25	-	-	-	-	-	-	-	-	6.20
					-	-	-	-	-			90
12-16.5 NHS	10	TL	9.75	-	818	320	18	371	2497	-	-	4.50
					32.2	12.6	23	14.6	98.3			65
12-16.5 NHS	12	TL	9.75	-	811	320	18	372	2459	-	-	5.50
					31.9	12.6	23	14.6	96.8			80
26 x 12-16.5 (300/40-16.5)	10	TL	9.75	-	663	283	24	303	1986	-	-	4.00
					26.1	11.1	30	11.9	78.2			57
14-17.5 NHS	12	TL	10.5	-	914	347	31	417	2746	-	-	4.50
					36.0	13.7	39	16.4	108.1			65

FEATURES

- Wide, deep lug design
- Stepped tread design
- Reinforced sidewall
- Rim protector

BENEFITS

- Provides enhanced durability and traction in off-road conditions
- Provides enhanced cleanout for improved traction
- Provides improved side impact resistance
- Protects wheel from impact damage

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



STATIC	CREEP	MAXIMUM TIRE LOAD [kg] [lb]									
		5 km/h 3 mph	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	25 km/h 15 mph	30 km/h 20 mph	35 km/h 22 mph	40 km/h 25 mph	45 km/h 28 mph	50 km/h 30 mph
1045	-	-	660	520	500	-	450	-	435	-	415
2290	-	-	1450	1145	1100	-	985	-	955	-	915
1295	-	-	820	650	625	-	560	-	540	-	515
2860	-	-	1810	1430	1375	-	1230	-	1195	-	1140
2450	-	-	1550	1225	1180	-	1055	-	1025	-	975
5575	-	-	3530	2790	2685	-	2400	-	2330	-	2225
-	-	-	3540	-	-	2725	-	-	2425	-	2290
-	-	-	7805	-	-	6010	-	-	5345	-	5050
2275	-	-	1440	1140	1095	-	980	-	950	-	905
5025	-	-	3180	2510	2415	-	2160	-	2100	-	2005
1880	1420	-	1120	935	895	845	795	780	755	725	710
4160	3140	-	2480	2070	1980	1870	1760	1725	1665	1600	1570
3315	2500	-	1975	1650	1575	1490	1400	1375	1325	1275	1250
7315	5520	-	4360	3645	3480	3285	3090	3035	2925	2815	2760
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-
2970	-	-	1880	1485	1430	-	1280	-	1240	-	1185
6540	-	-	4140	3270	3145	-	2815	-	2730	-	2610
3375	-	-	2135	1685	1625	-	1450	-	1410	-	1345
7440	-	-	4710	3720	3580	-	3205	-	3110	-	2965
3755	-	-	2375	1875	1805	-	1615	-	1570	-	1495
8280	-	-	5240	4140	3980	-	3565	-	3460	-	3300
4015	-	-	2540	2005	1930	-	1725	-	1675	-	1600
8850	-	-	5600	4425	4255	-	3810	-	3695	-	3530
4525	-	-	2865	2265	2175	-	1950	-	1890	-	1805
9985	-	-	6320	4995	4805	-	4300	-	4170	-	3980
5420	-	-	3430	2710	2605	-	2330	-	2265	-	2160
11945	-	-	7560	5970	5745	-	5140	-	4990	-	4765



CAMSO HAULER SKZ

VERSATILITE DURABILITY ON MIXED SURFACES

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE [bar] [psi]
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.			
31 x 15.50-15 NHS	8	TL	13LB	-	782	384	24	-	-	116	B	3.10
					30.8	15.1	30	-	-			45
10-16.5 NHS	10	TL	8.25	-	785	273	31	364	2335	-	-	5.20
					30.9	10.7	39	14.3	91.9			75
12-16.5 NHS	10	TL	9.75	-	834	320	34	381	2515	-	-	4.50
					32.8	12.6	43	15.0	99.0			65
12-16.5 NHS	12	TL	9.75	-	834	324	34	384	2483	-	-	5.50
					32.8	12.8	43	15.1	97.8			80
33 x 15.50-16.5 NHS	14	TL	12	-	836	380	35	384	2446	-	-	4.85
					32.9	15.0	44	15.1	96.3			70
14-17.5 NHS	14	TL	10.5	-	930	351	44	426	2733	-	-	5.50
					36.6	13.8	55	16.8	107.6			80

FEATURES

- Non-directional extra deep tread
- Large footprint with massive lug-to-void ratio
- Versatile tread pattern
- Wide sidewall

BENEFITS

- Improves tread life and resistance to punctures
- Provides excellent durability and even tread wearing
- Optimizes traction and handling on mixed and hard surfaces
- Provides superior side impact resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



STATIC	CREEP	MAXIMUM TIRE LOAD [kg] [lb]								
		10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	25 km/h 15 mph	30 km/h 20 mph	35 km/h 22 mph	40 km/h 25 mph	45 km/h 28 mph	50 km/h 30 mph
3315	2500	1975	1650	1575	1490	1400	1375	1325	1275	1250
7315	5520	4360	3645	3480	3285	3090	3035	2925	2815	2760
3375	-	2135	1685	1625	-	1450	-	1410	-	1345
7440	-	4710	3720	3580	-	3205	-	3110	-	2965
4015	-	2540	2005	1930	-	1725	-	1675	-	1600
8850	-	5600	4425	4255	-	3810	-	3695	-	3530
4525	-	2865	2265	2175	-	1950	-	1890	-	1805
9985	-	6320	4995	4805	-	4300	-	4170	-	3980
5370	-	3400	2685	2585	-	2310	-	2245	-	2140
11840	-	7495	5920	5700	-	5095	-	4950	-	4720
6125	-	3875	3060	2945	-	2635	-	2560	-	2440
13495	-	8540	6745	6490	-	5805	-	5635	-	5380



CAMSO SKS 792S

Formerly Solideal SolidAir SKS

FLAT-PROOF DURABILITY MEETS OFF-ROAD TRACTION

FEATURES

- FEA-validated aperture design
- Stepped tread design
- Reusable wheel

BENEFITS

- Improves ride quality and reduces cracking
- Provides excellent cleanout for improved off-road traction
- Provides lower cost per hour and quicker installation

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO SKS 782S

Formerly Solideal Safetymaster SKS

SOLID OFF-ROAD TRACTION

FEATURES

- Full solid construction
- Stepped tread design
- Reusable wheel

BENEFITS

- Provides excellent durability and flat-free operation
- Provides excellent cleanout for improved off-road traction
- Provides lower cost per hour and quicker installation

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]					
										OTHER VEHICLES			STATIC	COUNTERBALANCED LIFT TRUCKS	
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	25 km/h 16 mph	25 km/h 16 mph
31 x 10-20 (10-16.5 NHS)	7.50	7.50	781	237	33	372	2522	-	■	4030	3660	3100	4680	4030	3100
			30.7	9.3	42	14.6	99.3	-	■	8900	8100	6850	10350	8885	6835
33 x 12-20 (12-16.5 NHS)	7.50	7.50	831	287	40	388	2669	-	■	5200	4720	4000	6040	5200	4000
			32.7	11.3	50	15.3	105.1	-	■	11500	10400	8850	13350	11465	8820
36 x 14-20 (14-17.5 NHS)	7.50	7.50	910	320	43	426	2860	-	■	6175	5605	4750	7175	6175	4750
			35.8	12.6	54	16.8	112.6	-	■	13650	12350	10500	15850	13650	10500

TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]					
										OTHER VEHICLES			STATIC	COUNTERBALANCED LIFT TRUCKS	
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	25 km/h 16 mph	25 km/h 16 mph
6.50-16	5.50	5.50	743	166	15	341	2344	■	■	2600	2360	2000	3020	2600	2000
			29.3	6.5	18.9	13.4	92.3	■	■	5750	5200	4400	6650	5750	4400
7.50-16	5.50	5.50	793	207	19	371	2392	■	■	3965	3600	3050	4605	3965	3050
			31.2	8.1	23.9	14.6	94.2	■	■	8750	7950	6750	10150	8750	6750
8.00-16	5.50	5.50	818	208	14	379	2570	■	■	4160	3775	3200	4830	4160	3200
			32.2	8.2	17.6	14.9	101.2	■	■	9200	8350	7050	10650	9200	7050
8.00-16	6.00	6.00	818	208	14	379	2570	■	-	4160	3775	3200	4830	4160	3200
			32.2	8.2	17.6	14.9	101.2	■	-	9200	8350	7050	10650	9200	7050
31 x 10-20 (10-16.5 NHS)	7.50	7.50	781	237	33	372	2522	-	■	4030	3660	3100	4680	4030	3100
			30.7	9.3	42	14.6	99.3	-	■	8900	8100	6850	10350	8885	6835
33 x 12-20 (12-16.5 NHS)	7.50	7.50	831	287	40	396	2677	-	■	5200	4720	4000	6040	5200	4000
			32.7	11.3	50	15.6	105.4	-	■	11500	10400	8850	13350	11465	8820
36 x 14-20 (14-17.5 NHS)	7.50	7.50	910	320	43	426	2860	-	■	6175	5605	4750	7175	6175	4750
			35.8	12.6	54	16.8	112.6	-	■	13650	12350	10500	15850	13650	10500



CAMSO SKS 793S

SEVERE-DUTY AND FLAT-FREE

FEATURES

- Innovative non-directional tread pattern
- New elongated aperture design
- Massive tread depth
- Reusable wheel

BENEFITS

- Provides greater durability and versatility for mixed and hard surface applications
- Provides excellent ride quality and reduces cracking
- Improves durability for longer service life
- Provides lower cost per hour and quicker installation

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]					
										OTHER VEHICLES			STATIC	COUNTERBALANCED LIFT TRUCKS	
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	25 km/h 16 mph	25 km/h 16 mph
31 x 10-20 (10-16.5 NHS)	7.50	7.50	780	233	39	372	2451	-	■	4030	3660	3100	4680	4030	3100
			30.7	9.2	49	14.6	96.5			8900	8100	6850	10350	8885	6835
33 x 12-20 (12-16.5 NHS)	7.50	7.50	830	285	39	391	2503	-	■	5200	4720	4000	6040	5200	4000
			32.7	11.2	50	15.4	98.5			11500	10400	8850	13350	11465	8820
36 x 14-20 (14-17.5 NHS)	7.50	7.50	910	322	52	424	2858	-	■	6175	5605	4750	7175	6175	4750
			35.8	12.7	66	16.7	112.5			13650	12350	10500	15850	13650	10500



CAMSO SKS 796S

Formerly Solideal SolidAir SM

HARD SURFACE SOLID TIRE SOLUTION

FEATURES

- FEA-validated aperture design
- Full-width footprint
- Reusable wheel

BENEFITS

- Improves ride quality and reduces cracking
- Provides excellent stability and tread life
- Provides lower cost per hour and quicker installation

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]					
										OTHER VEHICLES			STATIC	COUNTERBALANCED LIFT TRUCKS	
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	25 km/h 16 mph	25 km/h 16 mph
31 x 10-20 (10-16.5 NHS)	7.50	7.50	781	237	-	372	2522	-	■	4030	3660	3100	4680	4030	3100
			30.7	9.3	-	14.6	99.3			8900	8100	6850	10350	8885	6835
33 x 12-20 (12-16.5 NHS)	7.50	7.50	831	287	-	388	2669	-	■	5200	4720	4000	6040	5200	4000
			32.7	11.3	-	15.3	105.1			11500	10400	8850	13350	11465	8820
36 x 14-20 (14-17.5 NHS)	7.50	7.50	909	326	-	425	2873	-	■	6175	5605	4750	7175	6175	4750
			35.8	12.8	-	16.7	113.1			13650	12350	10500	15850	13650	10500

CAMSO SKS 786S

Formerly Solideal Safetymaster SM

SOLID HARD SURFACE DURABILITY

FEATURES

- Full solid construction
- Full-width footprint
- Reusable wheel

BENEFITS

- Provides excellent durability and flat-free operation
- Provides excellent stability and tread life
- Provides lower cost per hour and quicker installation

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]					
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	OTHER VEHICLES			STATIC	COUNTERBALANCED LIFT TRUCKS	
										6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph	LOAD WHEEL 25 km/h 16 mph	STEERING WHEEL 25 km/h 16 mph
6.50-16	7.50	7.50	743	169	-	350	2334	■	-	2600	2360	2000	3020	2600	2000
			29.3	6.7	-	13.8	91.9			5750	5200	4400	6650	5750	4400
31 x 10-20 (10-16.5 NHS)	7.50	7.50	781	237	-	372	2522	-	■	4030	3660	3100	4680	4030	3100
			30.7	9.3	-	14.6	99.3			8900	8100	6850	10350	8885	6835
33 x 12-20 (12-16.5 NHS)	7.50	7.50	831	287	-	396	2677	-	■	5200	4720	4000	6040	5200	4000
			32.7	11.3	-	15.6	105.4			11500	10400	8850	13350	11465	8820
36 x 14-20 (14-17.5 NHS)	7.50	7.50	909	326	-	429	2905	-	■	6175	5605	4750	7175	6175	4750
			35.8	12.8	-	16.9	114.4			13650	12350	10500	15850	13650	10500





CAMSO SL R4

HEAVY-DUTY DURABILITY AND TRACTION

TIRE SIZE	ALT. SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
10.5/80-18 IMP	-	10	TL	W9	W8 9	877	270	22	406	2605	131	A8	WITHOUT HLV	FREE ROLLING
						34.5	10.6	28	16.0	102.6				
10.5/80-18 IMP	-	10	TL	W9	W8 9	877	270	22	406	2605	119	A8	WITHOUT HLV	DRIVE
						34.5	10.6	28	16.0	102.6				
12.5/80-18 IMP	-	12	TL	W9	11	960	303	29	434	2853	142	A8	WITHOUT HLV	FREE ROLLING
						37.8	11.9	37	17.1	112.3				
12.5/80-18 IMP	-	12	TL	W9	11	961	303	29	434	2853	129	A8	WITHOUT HLV	DRIVE
						37.8	11.9	37	17.1	112.3				
12.5/80-18 IMP	-	14	TL	W9	11	956	303	29	-	-	146	A8	WITHOUT HLV	FREE ROLLING
						37.7	11.9	37	-	-				
12.5/80-18 IMP	-	14	TL	W9	11	956	303	29	-	-	134	A8	WITHOUT HLV	DRIVE
						37.7	11.9	37	-	-				
14.9-24 IND	-	12	TL	DW13	DW11 DW12 DW13L TW13	1233	400	29	555	3694	145	A8	IND. TRACTOR	CYCLIC
						48.5	15.7	37	21.9	145.4				
						1233	400	29	555	3694				CONSTANT
						48.5	15.7	37	21.9	145.4				
16.9-24 IND	440/80-24; 16.5/85-24	12	TL	DW15L	DW14L TW14L TW15L	1303	454	23	591	3899	149	A8	IND. TRACTOR	CYCLIC
						51.3	17.9	29	23.3	153.5				
						1303	454	23	591	3899				CONSTANT
						51.3	17.9	29	23.3	153.5				
17.5L-24 IND	460/70-24	10	TL	DW15L	DW14L TW14L TW15L	1269	458	25	567	3716	144	A8	IND. TRACTOR	CYCLIC
						50.0	18.0	31	22.3	146.3				
						1269	458	25	567	3716				CONSTANT
						50.0	18.0	31	22.3	146.3				
17.5L-24 IND	460/70-24	12	TL	DW15L	DW14L TW14L TW15L	1249	450	32	575	3728	149	A8	IND. TRACTOR	CYCLIC
						49.2	17.7	40	22.6	146.8				
						1249	450	32	575	3728				CONSTANT
						49.2	17.7	40	22.6	146.8				
19.5L-24 IND	500/70-24	12	TL	DW16L	TW16L	1312	485	28	568	3895	151	A8	IND. TRACTOR	CYCLIC
						51.7	19.1	35	22.4	153.3				
						1312	485	28	568	3895				CONSTANT
						51.7	19.1	35	22.4	153.3				
21L-24 IND	540/70-24	12	TL	DW18L	TW18L	1382	538	36	628	4072	155	A8	IND. TRACTOR	CYCLIC
						54.4	21.2	45	24.7	160.3				
						1382	538	36	628	4072				CONSTANT
						54.4	21.2	45	24.7	160.3				

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.

FEATURES

- Heavy-duty carcass
- Optimized lug-to-void ratio with extra-deep tread
- Stepped tread design

BENEFITS

- Improves stability and side impact resistance
- Increases tread life and off-road traction
- Improves self-cleaning and stone ejection for excellent traction

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
3.70	3220	-	2730	2595	2455	2320	2185	2050	1950	1855	1755
54	7095	-	6020	5720	5420	5115	4815	4515	4300	4085	3870
3.70	3195	-	1905	1810	1715	1620	1525	1430	1360	1290	1225
54	7050	-	4200	3990	3780	3570	3360	3150	3000	2850	2700
3.70	4375	-	3710	3525	3340	3155	2970	2785	2650	2520	2385
54	9635	-	8175	7765	7360	6950	6540	6130	5840	5550	5255
3.70	4350	-	2590	2460	2330	2200	2070	1945	1850	1760	1665
54	9590	-	5710	5425	5140	4855	4570	4285	4080	3875	3670
4.30	4950	-	4200	3990	3780	3570	3360	3150	3000	2850	2700
62	10915	-	9260	8800	8335	7870	7410	6945	6615	6285	5955
4.30	4980	-	2970	2820	2670	2525	2375	2225	2120	2015	1910
62	10985	-	6545	6220	5890	5565	5235	4910	4675	4440	4210
2.90	6670	4845	4350	3885	3565	3220	3105	2985	2900	2785	2640
42	14705	10680	9590	8565	7860	7100	6845	6580	6395	6140	5820
2.90	6670	4205	3625	3275	3160	3075	3015	2960	2900	2785	2640
42	14705	9270	7990	7220	6965	6780	6645	6525	6395	6140	5820
2.60	7475	5430	4875	4355	4000	3610	3480	3350	3250	3120	2960
38	16480	11970	10745	9600	8820	7960	7670	7385	7165	6880	6525
2.60	7475	4715	4065	3675	3545	3445	3380	3315	3250	3120	2960
38	16480	10395	8960	8100	7815	7595	7450	7310	7165	6880	6525
2.20	6440	4675	4200	3750	3445	3110	2995	2885	2800	2690	2550
32	14200	10305	9260	8265	7595	6855	6605	6360	6175	5930	5620
2.20	6440	4060	3500	3165	3050	2970	2910	2855	2800	2690	2550
32	14200	8950	7715	6980	6725	6550	6415	6295	6175	5930	5620
2.60	7475	5430	4875	4355	4000	3610	3480	3350	3250	3120	2960
38	16480	11970	10745	9600	8820	7960	7670	7385	7165	6880	6525
2.60	7475	4715	4065	3675	3545	3445	3380	3315	3250	3120	2960
38	16480	10395	8960	8100	7815	7595	7450	7310	7165	6880	6525
2.30	7935	5760	5175	4625	4245	3830	3690	3555	3450	3310	3140
33	17495	12700	11410	10195	9360	8445	8135	7835	7605	7295	6920
2.30	7935	5005	4315	3900	3760	3655	3590	3520	3450	3310	3140
33	17495	11035	9515	8600	8290	8060	7915	7760	7605	7295	6920
2.20	8915	6470	5815	5195	4765	4300	4145	3990	3875	3720	3525
32	19655	14265	12820	11455	10505	9480	9140	8795	8545	8200	7770
2.20	8915	5620	4845	4380	4225	4110	4030	3955	3875	3720	3525
32	19655	12390	10680	9655	9315	9060	8885	8720	8545	8200	7770

* Cyclic: One way distance up to 150 m (500 feet) ** Cyclic: One way distance up to 600 m (2000 feet)



CAMSO SL R4 (cont.)

HEAVY-DUTY DURABILITY AND TRACTION

TIRE SIZE	ALT. SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
18.4-26 IND	480/80-26	12	TL	DW16L	DW15L TW15L TW16L	1430	495	28	635	4270	156	A8	IND. TRACTOR	CYCLIC
						56.3	19.5	35	25.0	168.1				CONSTANT
						1430	495	28	635	4270				
						56.3	19.5	35	25.0	168.1				
16.9-28 IND	440/80-28	12	TL	DW15L	DW14L TW14L TW15L	1415	441	33	-	-	152	A8	IND. TRACTOR	CYCLIC
						55.7	17.4	42	-	-				CONSTANT
						1415	441	33	-	-				
						55.7	17.4	42	-	-				
18.4-28 IND	-	12	TL	DW16L	DW15L TW15L TW16L	1489	494	39	681	4414	157	A8	IND. TRACTOR	CYCLIC
						58.6	19.4	49	26.8	173.8				CONSTANT
						1489	494	39	681	4414				
						58.6	19.4	49	26.8	173.8				
420/80-30 IND	16.9-30	-	TL	DW15L	DW14L TW14L TW15L	1452	446	30	674	4354	155	A8	IND. TRACTOR	CYCLIC
						57.2	17.6	38	26.5	171.4				CONSTANT
						1452	446	30	674	4354				
						57.2	17.6	38	26.5	171.4				

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.

FEATURES

- Heavy-duty carcass
- Optimized lug-to-void ratio with extra-deep tread
- Stepped tread design

BENEFITS

- Improves stability and side impact resistance
- Increases tread life and off-road traction
- Improves self-cleaning and stone ejection for excellent traction

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
2.50	9200	6680	6000	5360	4920	4440	4280	4120	4000	3840	3640
36	20280	14725	13230	11815	10845	9790	9435	9085	8820	8465	8025
2.50	9200	5800	5000	4520	4360	4240	4160	4080	4000	3840	3640
36	20280	12785	11025	9965	9610	9345	9170	8995	8820	8465	8025
2.60	8165	5930	5325	4755	4365	3940	3800	3655	3550	3410	3230
38	18000	13075	11740	10485	9625	8685	8375	8060	7825	7520	7120
2.60	8165	5150	4440	4010	3870	3765	3690	3620	3550	3410	3230
38	18000	11355	9790	8840	8530	8300	8135	7980	7825	7520	7120
2.50	9490	6890	6190	5530	5075	4580	4415	4250	4125	3960	3755
36	20920	15190	13645	12190	11190	10095	9735	9370	9095	8730	8280
2.50	9490	5980	5155	4660	4495	4375	4290	4210	4125	3960	3755
36	20920	13185	11365	10275	9910	9645	9460	9280	9095	8730	8280
3.2	8915	6470	5815	5195	4765	4300	4145	3990	3875	3720	3525
46	19655	14265	12820	11455	10505	9480	9140	8795	8545	8200	7770
3.20	8915	5620	4845	4380	4225	4110	4030	3955	3875	3720	3525
46	19655	12390	10680	9655	9315	9060	8885	8720	8545	8200	7770

*Cyclic: One way distance up to 150 m (500 feet) **Cyclic: One way distance up to 600 m (2000 feet)



CAMSO BHL 532

Formerly Solideal SLA R4

ROADING COMFORT AND OFF-ROAD TRACTION

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
14.9-24 IND	12	TL	DW13	DW11 DW12 DW13L TW13	1233	393	22	548	3644	145	A8	IND. TRACTOR	CYCLIC
					48.5	15.5	28	21.6	143.5				
					1233	393	22	548	3644	145	A8	IND. TRACTOR	CONSTANT
					48.5	15.5	28	21.6	143.5				
16.9-24 IND (440/80-24 16.5/85-24)	12	TL	DW15L	DW14L TW14L TW15L	1296	448	22	-	-	149	A8	IND. TRACTOR	CYCLIC
					51.0	17.6	28	-	-				
					1296	448	22	-	-	149	A8	IND. TRACTOR	CONSTANT
					51.0	17.6	28	-	-				
17.5L-24 IND (460/70-24)	10	TL	DW15L	DW14L TW14L TW15L	1246	452	24	564	3705	144	A8	IND. TRACTOR	CYCLIC
					49.1	17.8	30	22.2	145.9				
					1246	452	24	564	3705	144	A8	IND. TRACTOR	CONSTANT
					49.1	17.8	30	22.2	145.9				
19.5L-24 IND (500/70-24)	12	TL	DW16L	TW16L	1318	495	26	592	3883	151	A8	IND. TRACTOR	CYCLIC
					51.9	19.5	33	23.3	152.9				
					1318	495	26	592	3883	151	A8	IND. TRACTOR	CONSTANT
					51.9	19.5	33	23.3	152.9				
21L-24 IND (540/70-24)	12	TL	DW18L	TW18L	1375	532	26	618	4079	155	A8	IND. TRACTOR	CYCLIC
					54.1	20.9	33	24.3	160.6				
					1375	532	26	618	4079	155	A8	IND. TRACTOR	CONSTANT
					54.1	20.9	33	24.3	160.6				
18.4-26 IND (480/80-26)	12	TL	DW16L	DW15L TW15L TW16L	1450	490	25	648	4269	156	A8	IND. TRACTOR	CYCLIC
					57.1	19.3	31	25.5	168.1				
					1450	490	25	648	4269	156	A8	IND. TRACTOR	CONSTANT
					57.1	19.3	31	25.5	168.1				
16.9-28 IND (440/80-28)	12	TL	DW15L	DW14L TW14L TW15L	1417	455	28	621	4224	152	A8	IND. TRACTOR	CYCLIC
					55.8	17.9	35	24.4	166.3				
					1417	455	28	621	4224	152	A8	IND. TRACTOR	CONSTANT
					55.8	17.9	35	24.4	166.3				

FEATURES

- Engineered low-vibration tread design
- Continuous multi-angle tread lugs
- Stepped tread design

BENEFITS

- Minimizes vibrations for improved ride quality
- Minimizes vibrations for improved ride quality
- Improves self-cleaning and stone ejection for excellent traction

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
2.90	6670	4845	4350	3885	3565	3220	3105	2985	2900	2785	2640
42	14705	10680	9590	8565	7860	7100	6845	6580	6395	6140	5820
2.90	6670	4205	3625	3275	3160	3075	3015	2960	2900	2785	2640
42	14705	9270	7990	7220	6965	6780	6645	6525	6395	6140	5820
2.60	7475	5430	4875	4355	4000	3610	3480	3350	3250	3120	2960
38	16480	11970	10745	9600	8820	7960	7670	7385	7165	6880	6525
2.60	7475	4715	4065	3675	3545	3445	3380	3315	3250	3120	2960
38	16480	10395	8960	8100	7815	7595	7450	7310	7165	6880	6525
2.20	6440	4675	4200	3750	3445	3110	2995	2885	2800	2690	2550
32	14200	10305	9260	8265	7595	6855	6605	6360	6175	5930	5620
2.20	6440	4060	3500	3165	3050	2970	2910	2855	2800	2690	2550
32	14200	8950	7715	6980	6725	6550	6415	6295	6175	5930	5620
2.30	7935	5760	5175	4625	4245	3830	3690	3555	3450	3310	3140
33	17495	12700	11410	10195	9360	8445	8135	7835	7605	7295	6920
2.30	7935	5005	4315	3900	3760	3655	3590	3520	3450	3310	3140
33	17495	11035	9515	8600	8290	8060	7915	7760	7605	7295	6920
2.20	8915	6470	5815	5195	4765	4300	4145	3990	3875	3720	3525
32	19655	14265	12820	11455	10505	9480	9140	8795	8545	8200	7770
2.20	8915	5620	4845	4380	4225	4110	4030	3955	3875	3720	3525
32	19655	12390	10680	9655	9315	9060	8885	8720	8545	8200	7770
2.50	9200	6680	6000	5360	4920	4440	4280	4120	4000	3840	3640
36	20280	14725	13230	11815	10845	9790	9435	9085	8820	8465	8025
2.50	9200	5800	5000	4520	4360	4240	4160	4080	4000	3840	3640
36	20280	12785	11025	9965	9610	9345	9170	8995	8820	8465	8025
2.60	8165	5930	5325	4755	4365	3940	3800	3655	3550	3410	3230
38	18000	13075	11740	10485	9625	8685	8375	8060	7825	7520	7120
2.60	8165	5150	4440	4010	3870	3765	3690	3620	3550	3410	3230
38	18000	11355	9790	8840	8530	8300	8135	7980	7825	7520	7120

*Cyclic: One way distance up to 150 m (500 feet) **Cyclic: One way distance up to 600 m (2000 feet)



CAMSO BHL 753

Formerly Solideal BHZ

DURABILITY MEETS RIDE QUALITY

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
12-16.5 NHS	12	TL	9.75	-	828	324	18	379	2506	-	-	CON. EQUIP	-
					32.6	12.8	23	14.9	98.7				
12.5/80-18 IMP	12	TL	W9	11	996	319	23	465	2926	142	A8	WITHOUT HLV	FREE ROLLING
					39.2	12.6	29	18.3	1115.2				
					996	319	23	465	2926	129	A8	WITHOUT HLV	DRIVE
					39.2	12.6	29	18.3	1115.2				
19.5L-24 IND (500/70-24)	12	TL	DW16L	TW16L	1308	502	25	594	3896	151	A8	IND. TRACTOR	CYCLIC
					51.5	19.8	31	23.4	153.4				
					1308	502	25	594	3896	151	A8	IND. TRACTOR	CONSTANT
					51.5	19.8	31	23.4	153.4				
18.4-26 IND (480/80-26)	12	TL	DW16L	DW15L TW15L TW16L	1427	499	25	-	-	156	A8	IND. TRACTOR	CYCLIC
					56.2	19.6	31	-	-				
					1427	499	25	-	-	156	A8	IND. TRACTOR	CONSTANT
					56.2	19.6	31	-	-				
16.9-28 IND (440/80-28)	12	TL	DW15L	DW14L TW14L TW15L	1399	456	28	-	-	152	A8	IND. TRACTOR	CYCLIC
					55.1	18.0	35	-	-				
					1399	456	28	-	-	152	A8	IND. TRACTOR	CONSTANT
					55.1	18.0	35	-	-				

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.

FEATURES

- Non-directional tread pattern with high lug-to-void ratio
- Optimized continuous-contact tread pattern
- Non-directional tread pattern with high lug-to-void ratio
- Tapered tread lugs

BENEFITS

- Ensures even tread wearing for greater durability
- Significantly reduces vibration for improved ride quality
- Protects against tread impacts and punctures
- Improves lug stability for even wearing

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h* 3 mph	10 km/h 5 mph	15 km/h 10 mph	20 km/h 12.5 mph	25 km/h 15 mph	30 km/h 20 mph	35 km/h 22 mph	40 km/h 25 mph	45 km/h 28 mph	50 km/h 30 mph
5.50	4525	-	2865	2265	2175	-	1950	-	1890	-	1805
80	9985	-	6320	4995	4805	-	4300	-	4170	-	3980
3.70	4375	-	3710	3525	3340	3155	2970	2785	2650	2520	2385
54	9635	-	8175	7765	7360	6950	6540	6130	5840	5550	5255
3.70	4350	-	2590	2460	2330	2200	2070	1945	1850	1760	1665
54	9590	-	5710	5425	5140	4855	4570	4285	4080	3875	3670
2.30	7935	5760	5175	4625	4245	3830	3690	3555	3450	3310	3140
33	17495	12700	11410	10195	9360	8445	8135	7835	7605	7295	6920
2.30	7935	5005	4315	3900	3760	3655	3590	3520	3450	3310	3140
33	17495	11035	9515	8600	8290	8060	7915	7760	7605	7295	6920
2.50	9200	6680	6000	5360	4920	4440	4280	4120	4000	3840	3640
36	20280	14725	13230	11815	10845	9790	9435	9085	8820	8465	8025
2.50	9200	5800	5000	4520	4360	4240	4160	4080	4000	3840	3640
36	20280	12785	11025	9965	9610	9345	9170	8995	8820	8465	8025
2.60	8165	5930	5325	4755	4365	3940	3800	3655	3550	3410	3230
38	18000	13075	11740	10485	9625	8685	8375	8060	7825	7520	7120
2.60	8165	5150	4440	4010	3870	3765	3690	3620	3550	3410	3230
38	18000	11355	9790	8840	8530	8300	8135	7980	7825	7520	7120

*Cyclic: One way distance up to 150 m (500 feet)



CAMSO BHL 530

Formerly Solideal MR F3

PERFORMANCE AND QUALITY YOU CAN RELY ON

FEATURES

- Engineered F-3 rib tread design
- Robust carcass
- Deep tread depth

BENEFITS

- Provides smooth ride and effective steering
- Reduces tread crowning for even wearing and excellent stability
- Enhances longevity

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [Inches]					LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]		
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				STATIC	15 km/h 9 mph	50 km/h 31 mph
A	11L-15SLIMP	12	TL	8LB	10LB	*	*	*	*	*	121	B	3.60	2900	1670	1450
						*	*	*	*	*			52	6395	3680	3195
B	11L-16SLIMP	12	TL	-	-	*	*	*	*	*	123	B	3.60	3100	1785	1550
						*	*	*	*	*			52	6835	3935	3415
C	14L-16.1SLIMP	14	TL	W11Cx16.1	-	*	*	*	*	*	138	B	3.60	4720	2715	2360
						*	*	*	*	*			52	10405	5985	5205





CAMSO TLH 732

ULTIMATE OFF-ROAD TRACTION AND STABILITY

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
13.00-24	12	TL / TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC)	1294	372	23	576	3890	168	A2	L-2	LOADER-DOZER
					50.9	14.6	29	22.7	153.1				
					1294	372	23	576	3890	146	B	E-2	EARTHMOVER
					50.9	14.6	29	22.7	153.1				
13.00-24	12	TL / TT	8.00TG	9.00/1.5 (DC) 10.00VA (SDC)	1276	343	23	590	3848	143	A8	G-2	GRADER
					50.2	13.5	29	23.2	151.5				
13.00-24	16	TL / TT	10.00	9.0 9.00/1.5 (DC)	1290	375	24	589	3912	173	A2	L-2	LOADER-DOZER
					50.8	14.8	30	23.2	154.0				
					1290	375	24	589	3912	152	A8	G-2	EARTHMOVER
					50.8	14.8	30	23.2	154.0				
					1290	375	24	589	3912	153	A8	G-2	GRADER
					50.8	14.8	30	23.2	154.0				
14.00-24	12	TL / TT	8.00TG	10.00VA (SDC) 10.00WA (SDC)	1347	363	25	615	4062	147	A8	G-2	GRADER
					53.0	14.3	31	24.2	159.9				
14.00-24	12	TL / TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC) 10.00WA (SDC)	1364	393	25	598	4104	172	A2	L-2	LOADER-DOZER
					53.7	15.5	31	23.5	161.6				
					1364	393	25	598	4104	150	B	E-2	EARTHMOVER
					53.7	15.5	31	23.5	161.6				
14.00-24	16	TL / TT	8.00TG	10.00VA (SDC) 9.00/1.5 (DC)	1355	398	25	616	4077	153	A8	G-2	GRADER
					53.3	15.7	31	24.3	160.5				
14.00-24	16	TL / TT	10.00W	10.0 9.0 9.00/1.5 (DC)	1355	398	25	616	4077	177	A2	L-2	LOADER-DOZER
					53.3	15.7	31	24.3	160.5				
					1355	398	25	616	4077	156	B	E-2	EARTHMOVER
					53.3	15.7	31	24.3	160.5				

FEATURES

- Massive tread depth with curved tread lugs
- New wraparound stepped tread design
- Void guard impact protection
- New impact guard sidewall design

BENEFITS

- Ensures great durability and extra traction
- Maximizes tread cleanout for best off-road traction
- Protects from punctures to minimize flat tires
- Deflects debris to better protect sidewalls and reduce stress cracking

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
4.50	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3525	-	-	-	
65	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7770	-	-	-	
3.00	-	-	-	-	3350	3300	3250	3175	3125	3100	3050	3000	2900	2750	2500	
44	-	-	-	-	7385	7275	7165	7000	6890	6835	6725	6615	6395	6065	5510	
3.00	-	-	-	-	-	-	-	-	-	2725	-	2475	-	2225	2000	
44	-	-	-	-	-	-	-	-	-	6010	-	5455	-	4905	4410	
6.00	10400	8450	7400	6500	5650	5450	5200	5000	4800	4550	4350	4100	-	-	-	
87	22930	18630	16315	14330	12455	12015	11465	11025	10580	10030	9590	9040	-	-	-	
4.00	-	-	-	-	4000	3925	3850	3800	3725	3675	3650	3575	3475	3300	2975	
58	-	-	-	-	8820	8655	8490	8380	8210	8100	8045	7880	7660	7275	6560	
4.00	-	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
58	-	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
2.75	10080	-	-	-	-	-	-	-	-	3075	-	2800	-	2525	2250	
40	22225	-	-	-	-	-	-	-	-	6780	-	6175	-	5565	4960	
4.25	10100	8200	7200	6300	5500	5300	5050	4850	4650	4400	4225	3975	-	-	-	
62	22265	18080	15875	13890	12125	11685	11135	10690	10250	9700	9315	8765	-	-	-	
2.75	-	-	-	-	3750	3675	3625	3550	3475	3450	3425	3350	3250	3075	2775	
40	-	-	-	-	8265	8100	7990	7825	7660	7605	7550	7385	7165	6780	6120	
3.75	11680	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
54	25750	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
5.50	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4900	4600	-	-	-	
80	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10805	10140	-	-	-	
3.75	-	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
54	-	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	



CAMSO TLH 532

Formerly Solideal TH2

HIGH QUALITY FOR STANDARD DUTY

FEATURES

- Deep tread pattern
- Optimized tread pattern
- Flatter tread profile

BENEFITS

- Enhances durability and traction
- Provides good traction in off-road conditions
- Resists tread crowning for even wearing

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
A	13.00-24 TG	12	TL/TT	8.00TG	9.00/1.5 (DC) 10.00VA (SDC)	1249	349	21	-	-	143	A8	G-2	GRADER
						49.2	13.7	26	-	-				
B	13.00-24 TG	12	TL/TT	10.00VA (SDC)	8.00TG, 9.00/1.5 (DC)	1263	354	21	559	3797	168	A2	L-2	LOADER-DOZER
						49.7	13.9	26	22.0	149.5				
C	14.00-24 TG	12	TL/TT	8.00TG	10.00VA 9.00DC	1324	384	22	569	3982	172	A2	L-2	LOADER-DOZER
						52.1	15.1	28	22.4	156.8				
						1324	384	22	569	3982	147	A8	G-2	GRADER
						52.1	15.1	28	22.4	156.8				

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]														
		STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph
A	3.00	-	-	-	-	-	-	-	-	-	2725	-	2475	-	2225	2000
	44	-	-	-	-	-	-	-	-	-	6010	-	5455	-	4905	4410
B	4.50	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3525	-	-	-
	65	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7770	-	-	-
C	4.25	10100	8200	7200	6300	5500	5300	5050	4850	4650	4400	4225	3975	-	-	-
	62	22265	18080	15875	13890	12125	11685	11135	10690	10250	9700	9315	8765	-	-	-
C	2.75	10080	-	-	6300	-	-	-	-	-	3075	-	2800	-	2525	2250
	40	22225	-	-	13890	-	-	-	-	-	6780	-	6175	-	5565	4960





CAMSO TLH 753

NEXT-LEVEL DURABILITY AND VERSATILITY

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
13.00-24	12	TL / TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC)	1296	372	23	581	3880	168	A2	L-3	LOADER-DOZER
					51.0	14.6	29	22.9	152.8				
					1296	372	23	581	3880	146	B	E-3	EARTHMOVER
					51.0	14.6	29	22.9	152.8				
13.00-24	12	TL / TT	8.00TG	9.00/1.5 (DC) 10.00VA (SDC)	1282	347	23	595	3866	143	A8	G-3	GRADER
					50.5	13.7	29	23.4	152.2				
13.00-24	16	TL / TT	10.00	9.0 9.00/1.5 (DC)	1283	372	25	583	3878	173	A2	L-3	LOADER-DOZER
					50.5	14.6	31	23.0	152.7				
					1283	372	25	583	3878	152	A8	E-3	EARTHMOVER
					50.5	14.6	31	23.0	152.7				
					1283	372	25	583	3878	153	A8	G-3	GRADER
					50.5	14.6	31	23.0	152.7				
14.00-24	12	TL / TT	8.00TG	10.00VA (SDC) 10.00WA (SDC)	1344	366	25	621	4053	147	A8	G-3	GRADER
					52.9	14.4	31	24.4	159.6				
14.00-24	12	TL / TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC) 10.00WA (SDC)	1355	391	25	603	4046	172	A2	L-3	LOADER-DOZER
					53.3	15.4	31	23.7	159.3				
					1355	391	25	603	4046	150	B	E-3	EARTHMOVER
					53.3	15.4	31	23.7	159.3				
14.00-24	16	TL / TT	8.00TG	10.00VA (SDC) 9.00/1.5 (DC)	1355	398	26	616	4077	153	A8	G-3	GRADER
					53.3	15.7	33	24.3	160.5				
14.00-24	16	TL / TT	10.00W	10.0 9.0 9.00/1.5 (DC)	1355	398	26	616	4077	177	A2	L-3	LOADER-DOZER
					53.3	15.7	33	24.3	160.5				
					1355	398	26	616	4077	156	B	E-3	EARTHMOVER
					53.3	15.7	33	24.3	160.5				
370/75-28	14	TL	11.00 GR	-	1275	365	33	589	3858	167	A2	L-3	LOADER-DOZER
					50.2	14.4	42	23.2	151.9				
					1275	365	33	589	3858	149	B	E-3	EARTHMOVER
					50.2	14.4	42	23.2	151.9				
400/75-28	16	TL	12.00 GR	-	1301	391	37	606	3935	173	A2	L-3	LOADER-DOZER
					51.2	15.4	47	23.9	154.9				
					1301	391	37	606	3935	155	B	E-3	EARTHMOVER
					51.2	15.4	47	23.9	154.9				

FEATURES

- Extra-deep non-directional tread pattern
- Stepped tread design
- Optimized lug-to-void ratio
- New impact guard sidewall design

BENEFITS

- Optimizes durability and traction on mixed and hard surfaces
- Maximizes tread cleanout on soft surfaces for improved traction
- Provides excellent traction for mixed and hard surface applications
- Deflects debris to better protect sidewalls and reduce stress cracking

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
4.50	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3525	-	-	-	
65	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7770	-	-	-	
3.00	-	-	-	-	3350	3300	3250	3175	3125	3100	3050	3000	2900	2750	2500	
44	-	-	-	-	7385	7275	7165	7000	6890	6835	6725	6615	6395	6065	5510	
3.00	-	-	-	-	-	-	-	-	-	2725	-	2475	-	2225	2000	
44	-	-	-	-	-	-	-	-	-	6010	-	5455	-	4905	4410	
6.00	10400	8450	7400	6500	5650	5450	5200	5000	4800	4550	4350	4100	-	-	-	
87	22930	18630	16315	14330	12455	12015	11465	11025	10580	10030	9590	9040	-	-	-	
4.00	-	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
58	-	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
4.00	-	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
58	-	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
2.75	10080	-	-	6300	-	-	-	-	-	3075	-	2800	-	2525	2250	
40	22225	-	-	13890	-	-	-	-	-	6780	-	6175	-	5565	4960	
4.25	10100	8200	7200	6300	5500	5300	5050	4850	4650	4400	4225	3975	-	-	-	
62	22265	18080	15875	13890	12125	11685	11135	10690	10250	9700	9315	8765	-	-	-	
2.75	-	-	-	-	3750	3675	3625	3550	3475	3450	3425	3350	3250	3075	2775	
40	-	-	-	-	8265	8100	7990	7825	7660	7605	7550	7385	7165	6780	6120	
3.75	11680	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
54	25750	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
5.50	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4900	4600	-	-	-	
80	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10805	10140	-	-	-	
3.75	-	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
54	-	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	
5.00	8700	7100	6200	5450	4750	-	4350	-	-	-	-	-	-	-	-	
73	19200	15600	13700	12000	10400	-	9600	-	-	-	-	-	-	-	-	
3.25	-	-	-	-	3650	-	-	-	-	-	-	3250	-	-	2700	
47	-	-	-	-	8000	-	-	-	-	-	-	7150	-	-	5950	
5.25	10400	8450	7400	6500	5650	-	5200	-	-	-	-	-	-	-	-	
76	22900	18600	16300	14300	12400	-	11400	-	-	-	-	-	-	-	-	
3.50	-	-	-	-	4350	-	-	-	-	-	-	3875	-	-	3225	
51	-	-	-	-	9600	-	-	-	-	-	-	8550	-	-	7100	



CAMSO SL G2

HEAVY-DUTY OFF-ROAD DURABILITY AND TRACTION

TIRE SIZE	PR	TL / TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
13.00-24 TG	12	TL / TT	8.00TG	9.00/1.5 (DC) 10.00VA (SDC)	1281	360	29	595	3823	143	A8	G-2	GRADER
					50.4	14.2	37	23.4	150.5				
13.00-24 TG	12	TL / TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC)	1281	360	29	595	3823	168	A8	L-2	LOADER-DOZER
					50.4	14.2	37	23.4	150.5				
					1281	360	29	595	3823	146	B	E-2	EARTHMOVER
					50.4	14.2	37	23.4	150.5				
13.00-24 TG	16	TL / TT	10.00VA	-	1298	366	29	596	3823	173	A2	L-2	LOADER-DOZER
					51.1	14.4	37	23.5	153.1				
					1298	366	29	596	3823	152	A8	E-2	EARTHMOVER
					51.1	14.4	37	23.5	153.1				
					1298	366	29	596	3823	153	A8	G-2	GRADER
					51.1	14.4	37	23.5	153.1				
14.00-24 TG	12	TL / TT	8.00TG	10.00VA 9.00DC	1335	388	32	592	3984	172	A2	L-2	LOADER-DOZER
					52.6	15.3	40	23.3	156.9				
					1335	388	32	592	3984	150	B	E-2	EARTHMOVER
					52.6	15.3	40	23.3	156.9				
					1335	388	32	592	3984	147	A8	G-2	GRADER
					52.6	15.3	40	23.3	156.9				
14.00-24 TG	16	TL / TT	10.00VA	-	1326	368	32	618	3957	177	A2	L-2	LOADER-DOZER
					52.2	14.5	40	24.3	155.8				
					1326	368	32	618	3957	156	B	E-2	EARTHMOVER
					52.2	14.5	40	24.3	155.8				
					1326	368	32	618	3957	153	A8	G-2	GRADER
					52.2	14.5	40	24.3	155.8				

FEATURES

- Extra-deep tread pattern
- Stepped tread design
- Heavy-duty sidewall construction
- Flatter tread profile

BENEFITS

- Provides best durability and traction in off-road conditions
- Provides excellent cleanout for improved traction
- Provides superior side impact resistance and stability
- Resists tread crowning for even wearing

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
3.00	-	-	-	-	-	-	-	-	-	2725	-	2475	-	2225	2000	
44	-	-	-	-	-	-	-	-	-	6010	-	5455	-	4905	4410	
4.50	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3525	-	-	-	
65	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7770	-	-	-	
3.00	-	-	-	-	3350	3300	3250	3175	3125	3100	3050	3000	2900	2750	2500	
44	-	-	-	-	7385	7275	7165	7000	6890	6835	6725	6615	6395	6065	5510	
6.00	10400	8450	7400	6500	5650	5450	5200	5000	4800	4550	4350	4100	-	-	-	
87	22930	18630	16315	14330	12455	12015	11465	11025	10580	10030	9590	9040	-	-	-	
4.00	-	-	-	-	4000	3925	3850	3800	3725	3675	3650	3575	3475	3300	2975	
58	-	-	-	-	8820	8655	8490	8380	8210	8100	8045	7880	7660	7275	6560	
4.00	-	-	-	-	-	-	-	-	-	3650	-	3325	-	3000	2675	
58	-	-	-	-	-	-	-	-	-	8045	-	7330	-	6615	5895	
4.25	10100	8200	7200	6300	5500	5300	5050	4850	4650	4400	4225	3975	-	-	-	
62	22265	18080	15875	13890	12125	11685	11135	10690	10250	9700	9315	8765	-	-	-	
2.75	-	-	-	-	3750	3675	3625	3550	3475	3450	3425	3350	3250	3075	2775	
40	-	-	-	-	8265	8100	7990	7825	7660	7605	7550	7385	7165	6780	6120	
2.75	10080	-	-	6300	-	-	-	-	-	3075	-	2800	-	2525	2250	
40	22225	-	-	13890	-	-	-	-	-	6780	-	6175	-	5565	4960	
5.50	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4900	4600	-	-	-	
80	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10805	10140	-	-	-	
3.75	-	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
54	-	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	
3.75	11680	-	-	7300	-	-	-	-	-	3650	-	3325	-	3000	2675	
54	25750	-	-	16095	-	-	-	-	-	8045	-	7330	-	6615	5895	



CAMSO SL G3

MULTI-SURFACE STABILITY AND PERFORMANCE

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
13.00-24 TG	12	TL/TT	8.00TG	9.00/1.5 (DC) 10.00VA (SDC)	1303	367	28	576	3832	143	A8	G-3	GRADER
					51.3	14.4	35	22.7	150.9				
13.00-24 TG	12	TL/TT	10.00VA (SDC)	8.00TG 9.00/1.5 (DC)	1303	367	28	576	3832	168	A2	L-3	LOADER-DOZER
					51.3	14.4	35	22.7	150.9				
					1303	367	28	576	3832	146	B	E-3	EARTHMOVER
					51.3	14.4	35	22.7	150.9				
14.00-24 TG	12	TL/TT	8.00TG	10.00VA 9.00DC	1354	385	27	592	3998	172	A2	L-3	LOADER-DOZER
					53.3	15.2	34	23.3	157.4				
					1354	385	27	592	3998	150	B	E-3	EARTHMOVER
					53.3	15.2	34	23.3	157.4				
					1354	385	27	592	3998	147	A8	G-3	GRADER
					53.3	15.2	34	23.3	157.4				
14.00-24 TG	16	TL/TT	10.00VA	-	1338	393	27	622	3993	177	A2	L-3	LOADER-DOZER
					52.7	15.5	34	24.5	157.2				
					1338	393	27	622	3993	156	B	E-3	EARTHMOVER
					52.7	15.5	34	24.5	157.2				
					1338	393	27	622	3993	153	A8	G-3	GRADER
					52.7	15.5	34	24.5	157.2				

FEATURES

- Extra-deep non-directional tread pattern
- Optimized lug-to-void ratio
- Heavy-duty sidewall construction
- Flatter tread profile

BENEFITS

- Optimizes durability and traction on mixed and hard surfaces
- Provides excellent traction for mixed and hard surface applications
- Provides superior side impact resistance and stability
- Resists tread crowning for even wearing

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]														
	STATIC	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
3.00	-	-	-	-	-	-	-	-	2725	-	2475	-	2225	2000	
44	-	-	-	-	-	-	-	-	6010	-	5455	-	4905	4410	
4.50	8950	6400	5600	4875	4700	4475	4300	4150	3925	3750	3525	-	-	-	
65	19730	14110	12345	10750	10360	9865	9480	9150	8655	8265	7770	-	-	-	
3.00	-	-	-	3350	3300	3250	3175	3125	3100	3050	3000	2900	2750	2500	
44	-	-	-	7385	7275	7165	7000	6890	6835	6725	6615	6395	6065	5510	
4.25	10100	7200	6300	5500	5300	5050	4850	4650	4400	4225	3975	-	-	-	
62	22265	15875	13890	12125	11685	11135	10690	10250	9700	9315	8765	-	-	-	
2.75	-	-	-	3750	3675	3625	3550	3475	3450	3425	3350	3250	3075	2775	
40	-	-	-	8265	8100	7990	7825	7660	7605	7550	7385	7165	6780	6120	
2.75	10080	-	6300	-	-	-	-	-	3075	-	2800	-	2525	2250	
40	22225	-	13890	-	-	-	-	-	6780	-	6175	-	5565	4960	
5.50	11700	8300	7300	6350	6150	5850	5600	5400	5100	4900	4600	-	-	-	
80	25795	18300	16095	14000	13560	12895	12345	11905	11245	10805	10140	-	-	-	
3.75	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
54	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	
3.75	11680	-	7300	-	-	-	-	-	3650	-	3325	-	3000	2675	
54	25750	-	16095	-	-	-	-	-	8045	-	7330	-	6615	5895	



CAMSO TLH 792S

Formerly Solideal SolidAir TLH

EXTREME-DUTY FLAT-FREE TIRE SOLUTION

FEATURES

- Engineered solid tire solution
- Patented triangular aperture design
- Massive tread depth
- Stepped tread design

BENEFITS

- Provides flat-free operation and ultimate durability
- Optimizes stability, strength and comfort
- Improves durability and traction
- Provides excellent cleanout for improved traction

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]			
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	OTHER VEHICLES			STATIC
										6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	
13.00-24	8.50	8.50V	1290	330	70	595	4027	-	■	7650	6950	6375	9625
			50.8	13.0	88	23.4	158.5			16900	15350	14050	21250
14.00-24	8.50	8.50V	1330	350	88	617	4164	-	■	8460	7685	7050	10645
			52.4	13.8	111	24.3	163.9			18700	16950	15550	23500





CAMSO MPT 552

A SMOOTH RIDE WITH ENHANCED TRACTION

FEATURES

- Versatile directional tread pattern with centre block
- Self-cleaning stepped tread
- Open shoulder tread design
- Improved heel engineering

BENEFITS

- Reduces vibrations and enhances driving comfort
- Maximizes cleanout for improved off-road traction
- Provides excellent traction in off-road conditions
- Reduces mounting and inflation time

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	PR	RIM SIZE		ACTUAL TIRE DIMENSIONS			LOAD INDEX	SPEED SYMBOL	SERVICE	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]			
		RECOMMENDED	ALTERNATIVE	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]					Static	10 km/h 6 mph	40 km/h 25 mph	50 km/h 31 mph
10.0/75-15.3 IMP (255/75-15.3)	12	9.00	-	772.0	261.0	21	126	A8	FREE	4.70	2805	2380	1700	1530
				30.4	10.3	26				68	6185	5245	3750	3375
10.0/75-15.3 IMP (255/75-15.3)	12	9.00	-	772.0	261.0	21	114	A8	DRIVE	4.70	2775	1650	1180	1060
				30.4	10.3	26				68	6120	3640	2600	2335
10.0/75-15.3 IMP (255/75-15.3)	18	9.00	-	763.0	264.0	20	137	A8	FREE	7.10	3795	3220	2300	2070
				30.0	10.4	25				103	8365	7100	5070	4565
10.0/75-15.3 IMP (255/75-15.3)	18	9.00	-	763.0	264.0	20	124	A8	DRIVE	7.10	3760	2240	1600	1440
				30.0	10.4	25				103	8290	4940	3525	3175
11.5/80-15.3 IMP (295/80-15.3)	14	9.00	-	856.0	293.0	19	139	A8	FREE	4.75	4010	3400	2430	2185
				33.7	11.5	24				69	8840	7495	5355	4815
11.5/80-15.3 IMP 295/80-15.3	14	9.00	-	856.0	293.0	19	126	A8	DRIVE	4.75	3995	2380	1700	1530
				33.7	11.5	24				69	8805	5250	3750	3375
12.0/75-18 IMP (300/75-18)	12	W9	9; 11	915*	296*	20*	139	A8	FREE	4.00	4010	3400	2430	2185
				36.0*	11.7*	25*				58	8835	7495	5355	4820
12.0/75-18 IMP (300/75-18)	12	W9	9; 11	915*	296*	20*	126	A8	DRIVE	4.00	3995	2380	1700	1530
				36.0*	11.7*	25*				58	8805	5250	3750	3375

All tires listed are tubeless.

Higher load capacities may be allowed for cyclic loaded (HLV) applications with an one way distance of maximum 1 km. Contact our technical department for more information.





CAMSO MPT 753

THE NEXT GENERATION IN VERSATILITY AND DURABILITY

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
340/80-18 IND	-	TL	11	12 11 SDC, 12 SDC W10, W11	1005	350	21	467	3029	143	A8	IND. TRACTOR	CYCLIC
					39.6	13.8	26	18.4	119.3				
340/80-18 IND	-	TL	11	12 11 SDC, 12 SDC W10, W11	1005	350	21	467	3029	143	A8	IND. TRACTOR	CONSTANT
					39.6	13.8	26	18.4	119.3				
340/80-20 IND	-	TL	11	12 11 SDC, 12 SDC W10, W11	1067	355	25	495	3217	144	A8	IND. TRACTOR	CYCLIC
					42.0	14.0	31	19.5	126.7				
340/80-20 IND	-	TL	11	12 11 SDC, 12 SDC W10, W11	1067	355	25	495	3217	144	A8	IND. TRACTOR	CONSTANT
					42.0	14.0	31	19.5	126.7				
400/70-20 IND	-	TL	13	DW12 13 SDC DW13, DW13L DW14L	1100	405	27	504	3290	155	A8	IND. TRACTOR	CYCLIC
					43.3	15.9	34	19.9	129.5				
400/70-20 IND	-	TL	13	DW12 13 SDC DW13, DW13L DW14L	1100	405	27	504	3290	155	A8	IND. TRACTOR	CONSTANT
					43.3	15.9	34	19.9	129.5				
400/70-24 IND	-	TL	13	DW12 13SDC DW13, DW13L DW14L TW13, TW14L	1187	402	29	552	3555	158	A8	IND. TRACTOR	CYCLIC
					46.7	15.8	37	21.7	140.0				
400/70-24 IND	-	TL	13	DW12 13SDC DW13, DW13L DW14L TW13, TW14L	1187	402	29	552	3555	158	A8	IND. TRACTOR	CONSTANT
					46.7	15.8	37	21.7	140.0				
400/80-24 IND	-	TL	DW13	DW12 DW13L, DW14L TW13, TW14L	1244	412	33	580	3753	162	A8	IND. TRACTOR	CYCLIC
					49.0	16.2	42	22.8	147.8				
400/80-24 IND	-	TL	DW13	DW12 DW13L, DW14L TW13, TW14L	1244	412	33	580	3753	162	A8	IND. TRACTOR	CONSTANT
					49.0	16.2	42	22.8	147.8				
460/70-24 IND	-	TL	DW15L	DW14L, DW16L TW14L, TW15L TW16L	1251	453	33	581	3557	159	A8	IND. TRACTOR	CYCLIC
					49.3	17.8	42	22.9	140.0				
460/70-24 IND	-	TL	DW15L	DW14L, DW16L TW14L, TW15L TW16L	1251	453	33	581	3557	159	A8	IND. TRACTOR	CONSTANT
					49.3	17.8	42	22.9	140.0				

FEATURES	BENEFITS	PERFORMANCE
<ul style="list-style-type: none"> Flat non-directional tread pattern with high lug-to-void Void guard impact protection Impact guard sidewall design Stepped and open shoulder lugs 	<ul style="list-style-type: none"> Enhances stability, ride quality and durability Protects from tread punctures to minimize flat tires Deflects debris to better protect sidewalls and reduce stress cracking Maximizes tread cleanout on softer surfaces for improved traction 	<p>TIRE LIFE</p> <p>PUNCTURE RESISTANCE</p> <p>TRACTION</p>

INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
4.00	6270	4550	4090	3650	3350	3025	2915	2805	2725	2615	2480
58	13825	10030	9015	8045	7385	6670	6425	6185	6010	5765	5465
4.00	6270	3950	3405	3080	2970	2890	2835	2780	2725	2615	2480
58	13825	8710	7505	6790	6550	6370	6250	6130	6010	5765	5465
4.00	6440	4675	4200	3750	3445	3110	2995	2885	2800	2690	2550
58	14200	10305	9260	8265	7595	6855	6605	6360	6175	5930	5620
4.00	6440	4060	3500	3165	3050	2970	2910	2855	2800	2690	2550
58	14200	8950	7715	6980	6725	6550	6415	6295	6175	5930	5620
5.00	8915	6470	5815	5195	4765	4300	4145	3990	3875	3720	3525
73	19655	14265	12820	11455	10505	9480	9140	8795	8545	8200	7770
5.00	8915	5620	4845	4380	4225	4110	4030	3955	3875	3720	3525
73	19655	12390	10680	9655	9315	9060	8885	8720	8545	8200	7770
5.00	9775	7100	6375	5695	5230	4720	4550	4380	4250	4080	3870
73	21550	15655	14055	12555	11530	10405	10030	9655	9370	8995	8530
5.00	9775	6165	5315	4805	4635	4505	4420	4335	4250	4080	3870
73	21550	13590	11720	10595	10220	9930	9745	9555	9370	8995	8530
5.00	10925	7935	7125	6365	5845	5275	5085	4895	4750	4560	4325
73	24085	17495	15710	14030	12885	11630	11210	10790	10470	10055	9535
5.00	10925	6890	5940	5370	5180	5035	4940	4845	4750	4560	4325
73	24085	15190	13095	11840	11420	11100	10890	10680	10470	10055	9535
4.00	10065	7305	6565	5865	5380	4855	4680	4505	4375	4200	3980
58	22190	16105	14475	12930	11860	10705	10320	9930	9645	9260	8775
4.00	10065	6345	5470	4945	4770	4640	4550	4465	4375	4200	3980
58	22190	13990	12060	10900	10515	10230	10030	9845	9645	9260	8775

* Cyclic: One way distance up to 150 m (500 feet) ** Cyclic: One way distance up to 600 m (2000 feet)



CAMSO TM R4

DURABLE OFF-ROAD PERFORMANCE

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION	
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.					
400/80-24 IND (15.5/80-24)	-	TL	DW13	-	DW12	1244	409	34	571	3771	162	A8	IND. TRACTOR	CYCLIC
					DW13L	49.0	16.1	43	22.5	148.5				
					DW14L	1244	409	34	571	3771	162	A8	IND. TRACTOR	CONSTANT
					TW13	49.0	16.1	43	22.5	148.5				
440/80-24 IND (16.9-24 16.5/85-24)	-	TL	DW14L	-	DW13	1328	453	33	601	4016	168	A8	IND. TRACTOR	CYCLIC
					DW13L	52.3	17.8	42	23.7	158.1				
					DW15L	1328	453	33	601	4016	168	A8	IND. TRACTOR	CONSTANT
					TW13	52.3	17.8	42	23.7	158.1				
460/70-24 IND (17.5L-24)	-	TL	DW15L	-	DW14L	1264	455	31	578	3789	159	A8	IND. TRACTOR	CYCLIC
					DW16L	49.8	17.9	39	22.8	149.2				
					TW14L	1264	455	31	578	3789	159	A8	IND. TRACTOR	CONSTANT
					TW15L	49.8	17.9	39	22.8	149.2				
18-19.5	16	TL/TT	14.00	-	1117	454	32	505	3352	160	A8	MPT	DRIVE	
				44.0	17.9	40	19.9	132.0						
405/70-20 (16/70-20)	14	TL/TT	13x20	13SDC	1085	403	27	490	3238	154	A8	MPT	FREE	
					42.7	15.9	34	19.3	127.5					
405/70-20 (16/70-20)	14	TL/TT	13x20	13SDC	1085	403	27	490	3238	142	A8	MPT	DRIVE	
					42.7	15.9	34	19.3	127.5					
18-22.5	16	TL/TT	14.00	-	1209	444	35	545	3638	163	A8	MPT	DRIVE	
					47.6	17.5	44	21.5	143.2					

FEATURES

- Stepped tread design
- Tapered tread lugs
- Optimized lug-to-void ratio
- Heavy-duty carcass

BENEFITS

- Enhances tread cleanout for improved traction
- Improves lug stability for even wearing
- Enhances longevity and tread puncture resistance
- Provides excellent stability and side impact resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]											
	STATIC	CREEP	5 km/h* 3 mph	10 km/h** 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
5.00	10925	-	7935	7125	6365	5845	5275	5085	4895	4750	4560	4325
73	24085	-	17495	15710	14030	12885	11630	11210	10790	10470	10055	9535
5.00	10925	-	6890	5940	5370	5180	5035	4940	4845	4750	4560	4325
73	24085	-	15190	13095	11840	11420	11100	10890	10680	10470	10055	9535
5.00	12880	-	9350	8400	7505	6890	6215	5990	5770	5600	5375	5095
73	28395	-	20615	18520	16545	15190	13700	13205	12720	12345	11850	11230
5.00	12880	-	8120	7000	6330	6105	5935	5825	5710	5600	5375	5095
73	28395	-	17900	15430	13955	13460	13085	12840	12590	12345	11850	11230
4.00	10065	-	7305	6565	5865	5380	4855	4680	4505	4375	4200	3980
58	22190	-	16105	14475	12930	11860	10705	10320	9930	9645	9260	8775
4.00	10065	-	6345	5470	4945	4770	4640	4550	4465	4375	4200	3980
58	22190	-	13990	12060	10900	10515	10230	10030	9845	9645	9260	8775
5.85	7755	6715	6305	5985	5170	-	-	4765	-	4625	-	4490
85	17100	14800	13900	13200	11400	-	-	10500	-	10200	-	9900
3.50	6190	-	-	-	-	-	5250	4990	-	3375	-	4490
50	13650	-	-	-	-	-	11600	11000	-	7450	-	9900
3.50	6230	-	-	-	-	-	3710	3525	-	2385	-	-
50	13750	-	-	-	-	-	8200	7800	-	5250	-	-
4.50	9850	-	-	-	-	-	6825	6485	-	4390	-	-
64	21750	-	-	-	-	-	15050	14300	-	9700	-	-

*Cyclic: One way distance up to 150 m (500 feet) **Cyclic: One way distance up to 600 m (2000 feet)



**CAMSO
4L13**

A SMOOTH RIDE WITH ENHANCED TRACTION

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	SERVICE	APPLICATION
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
10.0/75-15.3 IMP	8	TL/TT	9.00	-	784	266	19	-	-	119	A8	WITHOUT HLV	FREE ROLLING
					30.9	10.5	24	-	-				
					784	266	19	-	-	106	A8	WITHOUT HLV	DRIVE
					30.9	10.5	24	-	-				
11.5/80-15.3 IMP	10	TL/TT	9.00	-	847	294	25	-	-	131	A8	WITHOUT HLV	FREE ROLLING
					33.3	11.6	31	-	-				
					847	294	25	-	-	119	A8	WITHOUT HLV	DRIVE
					33.3	11.6	31	-	-				
11.5/80-15.3 IMP	14	TL/TT	9.00	-	840.0	301.0	21	-	-	139	A8	WITHOUT HLV	FREE ROLLING
					33.1	11.9	26	-	-				
					840.0	301.0	21	-	-	126	A8	WITHOUT HLV	DRIVE
					33.1	11.9	26	-	-				
10.5-18	10	TL/TT	-	9 9 (SDC)	907	271	22	-	-	130	B	MPT	-
					35.7	10.7	28	-	-				
12.5-18	12	TL/TT	-	11 11 (SDC) 12 12 (SDC)	995	327	22	469	2969	135	B	MPT	-
					39.2	12.9	28	18.5	116.9				
12.5-18	16	TL/TT	-	-	1000	351	25	467	3016	141	B	MPT	-
					39.5	13.8	31	18.4	118.7				
10.5-20	10	TL/TT	-	9 9 (SDC)	950	278	22	423	2825	132	B	MPT	-
					37.4	10.9	28	16.7	111.2				
12.5-20	12	TL/TT	-	11 11 (SDC) 12 12 (SDC)	1054	348	23	471	3138	136	B	MPT	-
					41.5	13.7	29	18.5	123.5				
14.5-20	14	TL/TT	-	11 11 (SDC)	1107	359	27	490	3277	143	B	MPT	-
					43.6	14.1	34	19.3	129.0				
405/70-20 (16/70-20)	14	TL/TT	13x20	13SDC	1081	442	26	503	3183	154	A8	MPT	FREE
					42.6	17.4	33	19.8	125.3				
					1081	442	26	503	3183	142	A8	MPT	DRIVE
					42.6	17.4	33	19.8	125.3				
405/70-24 (16/70-24)	14	TL/TT	13x24	13SDC	1188	421	27	553	3516	156	A8	MPT	FREE
					46.8	16.6	34	21.8	138.4				
					1188	421	27	553	3516	144	A8	MPT	DRIVE
					46.8	16.6	34	21.8	138.4				

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.

FEATURES

- Versatile directional tread pattern with center block
- Stepped tread design
- Open shoulder tread design
- Heavy-duty carcass

BENEFITS

- Reduces vibrations and enhances driving comfort
- Maximizes tread cleanout in off-road conditions for improved traction
- Provides excellent traction in off-road conditions
- Provides excellent stability and side impact resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]										
	STATIC	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
3.10	2245	-	1905	1810	1715	1620	1525	1430	1360	1290	1225
45	4950	-	4200	3990	3780	3570	3360	3150	3000	2850	2700
3.10	2235	-	1330	1265	1195	1130	1065	1000	950	905	855
45	4925	-	2935	2785	2640	2495	2345	2200	2095	1990	1885
3.40	3220	-	2730	2595	2455	2320	2185	2050	1950	1855	1755
49	7095	-	6020	5720	5420	5115	4815	4515	4300	4085	3870
3.40	3195	-	1905	1810	1715	1620	1525	1430	1360	1290	1225
49	7050	-	4200	3990	3780	3570	3360	3150	3000	2850	2700
4.75	4010	-	3400	3230	3060	2890	2720	2550	2430	2310	2185
69	8835	-	7495	7120	6745	6370	6000	5625	5355	5085	4820
4.75	3995	-	2380	2260	2140	2025	1905	1785	1700	1615	1530
69	8815	-	5250	4990	4725	4465	4200	3940	3750	3565	3375
4.50	4250	3570	3060	2805	2550	2295	2125	2025	1955	1920	1905
65	9350	7850	6750	6200	5600	5050	4700	4450	4300	4250	4200
4.20	4875	4095	3510	3220	2925	2635	2440	2320	2245	2205	2185
61	10750	9050	7750	7100	6450	5800	5400	5100	4950	4850	4800
5.40	5750	4830	4140	3795	3450	3105	2875	2735	2645	2600	2575
78	12700	10650	9150	8350	7600	6850	6350	6050	5850	5750	5700
4.50	4500	3780	3240	2970	2700	2430	2250	2140	2070	2035	2015
65	9900	8350	7150	6550	5950	5350	4950	4700	4550	4500	4450
4.20	5000	4200	3600	3300	3000	2700	2500	2380	2300	2260	2240
61	11000	9250	7950	7300	6600	5950	5500	5250	5050	5000	4950
4.20	6075	5105	4375	4010	3645	3280	3040	2890	2795	2745	2720
61	13400	11250	9650	8850	8050	7250	6700	6350	6150	6050	6000
3.50	6190	-	-	-	-	5250	4990	-	3375	-	-
50	13650	-	-	-	-	11600	11000	-	7450	-	-
3.50	6230	-	-	-	-	3710	3525	-	2385	-	-
50	13750	-	-	-	-	8200	7800	-	5250	-	-
3.50	6600	-	-	-	-	5600	5320	-	3600	-	-
50	14550	-	-	-	-	12350	11750	-	7950	-	-
3.50	6580	-	-	-	-	3920	3725	-	2520	-	-
50	14550	-	-	-	-	8650	8200	-	5550	-	-



**CAMSO
4L R1**

ROADING COMFORT AND OFF-ROAD TRACTION

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]						LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.					
11.5/80-15.3 IMP	8	TL/TT	9.00	-	849	291	23	-	-	-	126	A8	-	WITHOUT HLV	FREE ROLLING
					33.4	11.5	29	-	-	-					DRIVE
					849	291	23	-	-	-	114				DRIVE
					11.5	29	-	-	-	-					
15.5/80-24 IMP (400/80-24)	14	TL	W12	W13 W14L	1282	405	40	-	-	-	160	A8	I-3	WITHOUT HLV	FREE ROLLING
					50.5	15.9	50	-	-	-					DRIVE
					1282	405	40	-	-	-	148				DRIVE
					50.5	15.9	50	-	-	-					
15.5/80-24 IMP (400/80-24)	16	TL	W12	W13 W14L	1282	400	40	-	-	-	163	A8	I-3	WITHOUT HLV	FREE ROLLING
					50.5	15.7	50	-	-	-					DRIVE
					1282	400	40	-	-	-	151				DRIVE
					50.5	15.7	50	-	-	-					
16.5/85-24 IMP (16.9-24 440/80-24)	8	TL	W13	W14L W15L	1330	418	25	522	576	4026	154	A8	-	WITHOUT HLV	FREE ROLLING
					52.4	16.5	31	20.6	22.7	158.5					DRIVE
					1330	418	25	522	576	4026	142				DRIVE
					52.4	16.5	31	20.6	22.7	158.5					
16.5/85-24 IMP (16.9-24 440/80-24)	14	TL	W13	W14L W15L	1327	428	26	517	586	3998	165	A8	-	WITHOUT HLV	FREE ROLLING
					52.2	16.9	32	20.4	23.1	157.4					DRIVE
					1327	428	26	517	586	3998	153				DRIVE
					52.2	16.9	32	20.4	23.1	157.4					
18-19.5	16	TL/TT	14.00	-	1105	448	32	493	495	3356	160	A8	-	MPT	DRIVE
					43.5	17.6	40	19.4	19.5	132.1					
405/70-20 (16/70-20)	14	TL/TT	11	11 SDC 12 12 SDC	1098	410	34	474	505	3332	154	A8	-	MPT	FREE
					43.2	16.1	43	18.7	19.9	131.2					
405/70-20 (16/70-20)	14	TL/TT	11	11 SDC 12 12 SDC	1098	410	34	474	505	3332	142	A8	-	MPT	DRIVE
					43.2	16.1	43	18.7	19.9	131.2					
18-22.5	16	TL/TT	14.00	-	1105	448	28	497	494	3667	163	A8	-	MPT	DRIVE
					43.5	17.6	35	19.6	19.4	144.4					
405/70-24 (16/70-24)	14	TL/TT	11	11 SDC 12 12 SDC	1202	406	27	434	543	3587	156	A8	-	MPT	FREE
					47.3	16.0	34	17.1	21.4	141.2					
405/70-24 (16/70-24)	14	TL/TT	11	11 SDC 12 12 SDC	1202	406	27	434	543	3587	144	A8	-	MPT	DRIVE
					47.3	16.0	34	17.1	21.4	141.2					
18.4-26 IND (480/80-26)	12	TL	DW16L	DW15L TW15L TW16L	1416	484	33	674	642	4241	156	A8	R-4	IND. TRACTOR	CYCLIC
					55.7	19.1	42	21.3	26.5	167.0					CONSTANT
					1416	484	33	674	642	4241					CONSTANT
					55.7	19.1	42	21.3	26.5	167.0					

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.

FEATURES

- Aggressive curved R1 tread pattern
- Stepped tread design
- Robust carcass design

BENEFITS

- Maximizes traction and improves ride quality
- Maximizes tread cleanout in off-road conditions for improved traction
- Improves stability and side impact resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]											
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
2.70	2805	-	-	2380	2260	2140	2025	1905	1785	1700	1615	1530
39	6190	-	-	5250	4990	4725	4465	4200	3940	3750	3565	3375
2.70	2775	-	-	1650	1570	1485	1405	1320	1240	1180	1120	1060
39	6110	-	-	3640	3460	3275	3095	2910	2730	2600	2470	2340
3.50	7425	-	-	6300	5985	5670	5355	5040	4725	4500	4275	4050
51	16370	-	-	13890	13195	12500	11805	11110	10415	9920	9425	8930
3.50	7405	-	-	4410	4190	3970	3750	3530	3310	3150	2995	2835
51	16320	-	-	9725	9235	8750	8265	7780	7290	6945	6600	6250
4.00	8045	-	-	6825	6485	6145	5800	5460	5120	4875	4630	4390
58	17735	-	-	15045	14295	13545	12785	12035	11290	10750	10205	9680
4.00	8110	-	-	4830	4590	4345	4105	3865	3625	3450	3280	3105
58	17880	-	-	10650	10120	9580	9050	8520	7990	7605	7230	6845
1.90	6190	-	-	5250	4990	4725	4465	4200	3940	3750	3565	3375
28	13635	-	-	11570	10990	10415	9835	9255	8680	8265	7850	7440
1.90	6230	-	-	3710	3525	3340	3155	2970	2785	2650	2520	2385
28	13725	-	-	8175	7765	7360	6950	6540	6130	5840	5550	5255
3.30	8500	-	-	7210	6850	6490	6130	5770	5410	5150	4895	4635
48	18735	-	-	15895	15100	14305	13510	12720	11925	11355	10785	10220
3.30	8580	-	-	5110	4855	4600	4345	4090	3835	3650	3470	3285
48	18905	-	-	11265	10700	10135	9575	9010	8445	8045	7645	7240
5.85	7755	6715	6305	5985	5170	-	-	4765	-	4625	-	4490
85	17100	14800	13900	13200	11400	-	-	10500	-	10200	-	9900
3.50	6190	-	-	-	-	-	5250	4990	-	3375	-	-
50	13650	-	-	-	-	-	11600	11000	-	7450	-	-
3.50	6230	-	-	-	-	-	3710	3525	-	2385	-	-
50	13750	-	-	-	-	-	8200	7800	-	5250	-	-
4.50	8045	-	-	-	-	-	6340	5850	-	4390	-	-
64	17750	-	-	-	-	-	14000	12900	-	9700	-	-
3.50	6600	-	-	-	-	-	5600	5320	-	3600	-	-
50	14550	-	-	-	-	-	12350	11750	-	7950	-	-
3.50	6580	-	-	-	-	-	3920	3725	-	2520	-	-
50	14550	-	-	-	-	-	8650	8200	-	5550	-	-
2.50	9200	-	6680	6000	5360	4920	4440	4280	4120	4000	3840	3640
36	20280	-	14725	13230	11815	10845	9790	9435	9085	8820	8465	8025
2.50	9200	-	5800	5000	4520	4360	4240	4160	4080	4000	3840	3640
36	20280	-	12785	11025	9965	9610	9345	9170	8995	8820	8465	8025



CAMSO TM R1

TRACTION THAT CAN'T BE BEAT

FEATURES

- Aggressive R1 tread pattern
- Robust carcass design
- Heavy-duty sidewall

BENEFITS

- Maximizes traction and improves ride quality
- Improves stability and side impact resistance
- Protects from side impact and flat tires

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]						LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.					
A	12.5/80-18 IMP	12	TL	W9	11	992	308	29	343	450	3005	142	A8	I-3	WITHOUT HLV	FREE ROLLING
						39.1	12.1	37	13.5	17.7	118.3					
						992	308	29	343	450	3005	129	A8	I-3	WITHOUT HLV	DRIVE
						39.1	12.1	37	13.5	17.7	118.3					

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]									
		STATIC	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
A	3.70	4375	3710	3525	3340	3155	2970	2785	2650	2520	2385
	54	9635	8175	7765	7360	6950	6540	6130	5840	5550	5255
	3.70	4350	2590	2460	2330	2200	2070	1945	1850	1760	1665
	54	9590	5710	5425	5140	4855	4570	4285	4080	3875	3670

HLV: vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty and on the other way the gross vehicle mass exceeds two times the mass of the empty vehicle, inclusive of the driver, if any: max 1km.



CAMSO MPT 793S

SEVERE-DUTY FLAT-FREE TIRE SOLUTION

FEATURES

- Engineered solid tire solution
- Massive non directional tread pattern
- Triangular aperture sidewall design
- Stepped shoulder lugs

BENEFITS

- Provides flat-free operation and ultimate durability
- Improves durability and traction
- Maximizes stability and ride quality
- Enhances tread cleanout for better traction in softer surfaces

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]						HEEL WIDTH	LOAD CAPACITY [kg] [lb]			
		O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.		OTHER VEHICLES			STATIC
									6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph ²	0 km/h 0 mph
385/70-20	10.00	1041	379	54	415	478	3140	10.00	9900	8995	8250	12460
		41,0	14,9	68	16,3	18,8	123,6		21825	19830	18190	27470
375/85-24	10.00	1245	370	66	*	*	*	10.00	10200	9265	8500	12835
		49,0	14,6	83	*	*	*		22485	20425	18740	28295



CAMSO MPT 532R

SUPERIOR OFF-ROAD TRACTION AND DURABILITY

FEATURES

- Aggressive tread design with deep lugs
- Wide and flat tread profile
- Strong radial carcass

BENEFITS

- Provides superior off-road traction
- Enhances stability and even wear
- Improves comfort, traction and durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO MPT 553R

OPTIMIZED PERFORMANCE ON MIXED SURFACES

FEATURES

- Non-directional tread pattern
- Large interlocked centre blocks
- Wide flat tread profile
- Strong radial carcass

BENEFITS

- Optimizes versatility and durability on mixed and hard surfaces
- Improves lateral stability and driving comfort
- Provides enhanced traction, stability and even wear
- Maximizes tread impact resistance, comfort and durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	RIM SIZE		ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	APPLICATION	INFLATION PRESSURE	MAXIMUM TIRE LOAD [kg] [lb]				
	RECOM-MENDED	ALTERNATIVE	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	S.L.R. [mm] [in]	R.C. [mm] [in]					Static	**10 km/h 6 mph	25 km/h 16 mph	30 km/h 19 mph	50 km/h 31 mph
400/70R24 IND (405/70R24; 16.0/70R24)	13	DW12; 13SDC; DW13; DW13L; DW14L; TW13; TW14L	1152	396	26	529	3487	152	A8 - B	CYCLIC	4.00	8165	5325	3940	3800	3230
			45.4	15.6	33	20.8	137.3				58	18000	11740	8685	8380	7120
			1152	396	26	529	3487				4.00	8165	4440	3765	3690	3230
			45.4	15.6	33	20.8	137.3				58	18000	9790	8300	8135	7120
440/80R24 IND (16.9R24; 16.5/85R24)	DW14L	DW13; DW13L; DW15L; TW13; TW14L; TW15L	1301	447	30	590	3924	161	A8 - B	CYCLIC	4.00	10640	6940	5135	4950	4210
			51.2	17.6	38	23.2	154.5				58	23455	15300	11320	10915	9280
			1301	447	30	590	3924				4.00	10640	5780	4905	4810	4210
			51.2	17.6	38	23.2	154.5				58	23455	12745	10815	10605	9280
460/70R24 IND (17.5LR24)	DW15L	DW14L; DW16L; TW14L; TW15L; TW16L	1237	456	30	560	3713	159	A8 - B	CYCLIC	4.00	10065	6565	4855	4680	3980
			48.7	18.0	38	22.0	146.2				58	22190	14475	10705	10320	8775
			1237	456	30	560	3713				4.00	10065	5470	4640	4550	3980
			48.7	18.0	38	22.0	146.2				58	22190	12060	10230	10030	8775
500/70R24 IND (19.5LR24)	DW15L	DW15L; DW18L; TW15L; TW16L; TW18L	1295	500	32	585	3890	164	A8 - B	CYCLIC	4.00	11500	7500	5550	5350	4550
			51.0	19.7	40	23.0	153.1				58	25355	16535	12235	11795	10030
			1295	500	32	585	3890				4.00	11500	6250	5300	5200	4550
			51.0	19.7	40	23.0	153.1				58	25355	13780	11685	11465	10030
480/80R26 IND (18.4R26)	DW15L	DW16L; TW15L; TW16L	1414	483	21	640	4262	160	A8 - B	CYCLIC	3.20	10350	6750	4995	4815	4095
			55.7	19.0	26	25.2	167.8				46	22820	14880	11010	10615	9030
			1414	483	21	640	4262				3.20	10350	5625	4770	4680	4095
			55.7	19.0	26	25.2	167.8				46	22820	12400	10515	10320	9030
440/80R28 IND (16.9R28)	DW14L	DW13; DW13L; DW15L; TW13; TW14L; TW15L	1402	443	33	644	4214	156	A8 - B	CYCLIC	3.20	9200	6000	4440	4280	3640
			55.2	17.4	42	25.4	165.9				46	20285	13230	9790	9435	8025
			1402	443	33	644	4214				3.20	9200	5000	4240	4160	3640
			55.2	17.4	42	25.4	165.9				46	20285	11025	9350	9170	8025

TIRE SIZE	RIM SIZE		ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]				
	RECOM-MENDED	ALTERNATIVE	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	S.L.R. [mm] [in]	R.C. [mm] [in]						Static	5 km/h 3 mph	15 km/h 9 mph	25 km/h 16 mph	50 km/h 31 mph
335/80R20 (12.5R20)	11.00	11.00 (SDC); 12.00; 12.00 (SDC)	1036	331	17	466	3110	147	A2	L-2	LOADER DOZER	3.75	4925	3500	2675	2450	1925
			40.8	13.0	21	18.3	122.4					54	10860	7715	5895	5400	4245
335/80R20 (12.5R20)	11.00	11.00 (SDC); 12.00; 12.00 (SDC)	1036	331	17	466	3110	136	B	E-2	EARTH-MOVER	3.75	-	-	2500	2425	2240
			40.8	13.0	21	18.3	122.4					54	-	-	5510	5345	4940
405/70R20 (16/70R20)	13.00	11.00; 11.00 (SDC); 12.00; 12.00 (SDC); 13.00 (SDC); 14.00	1069	400	18	471	3207	155	A2	L-2	LOADER DOZER	3.75	6200	4425	3375	3100	2450
			42.1	15.7	23	18.5	126.3					54	13670	9755	7440	6835	5400
405/70R20 (16/70R20)	13.00	11.00; 11.00 (SDC); 12.00; 12.00 (SDC); 13.00 (SDC); 14.00	1069	400	18	471	3207	143	B	E-2	EARTH-MOVER	3.75	-	-	3050	2950	2725
			42.1	15.7	23	18.5	126.3					54	-	-	6725	6505	6010



**CAMSO
WL**

HIGH PERFORMANCE. MAXIMUM PROTECTION

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [Inches]						LOAD INDEX	SPEED SYMBOL
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.		
8.25-20	14	TT	6.50	7.00	1000	252	26	272	486	2985	148	A2
					39.4	9.9	33	10.7	19.1	117.5		
					1000	252	26	272	486	2985	148	A2
					39.4	9.9	33	10.7	19.1	117.5		
9.00-20	14	TT	7.00	6.50/7.50	1040	267	27	301	485	3101	153	A2
					40.9	10.5	34	11.9	19.1	122.1		
					1039	267	27	301	485	3101	153	A2
					40.9	10.5	34	11.9	19.1	122.1		
10.00-20	16	TT	7.50	7.00/8.00	1070	283	26	316	496	3226	158	A2
					42.1	11.1	33	12.4	19.5	127.0		
					1070	283	26	316	496	3226	158	A2
					42.1	11.1	33	12.4	19.5	127.0		
11.00-20	16	TT	8.00	8.50	1100	301	22	334	512	3376	160	A2
					43.3	11.9	28	13.1	20.2	132.9		
					1100	301	22	334	512	3376	160	A2
					43.3	11.9	28	13.1	20.2	132.9		

FEATURES

- Heavy-duty carcass
- Large casing design
- Extra-deep lug depth
- Premium rubber compounds

BENEFITS

- Provides best stability and side impact resistance
- Improves ride quality and stability
- Provides best durability and traction
- Provides best durability and cut resistance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



MAXIMUM TIRE LOAD [kg] [lb]					
ALL SURFACES			IMPROVED SURFACES		
STATIC	CREEP	0-8 km/h 0-5 mph	10 km/h 6 mph	25 km/h 16 mph	45 km/h 28 mph
6105	5120	3645	3150	2600	2325
13500	11300	8050	6950	5750	5150
9.00 bar	9.00 bar	8.00 bar	8.00 bar	7.50 bar	7.50 bar
129 psi	129 psi	114 psi	114 psi	107 psi	107 psi
6990	5860	4170	3605	2975	2660
15450	12950	9200	7950	6550	5850
8.50 bar	8.50 bar	7.50 bar	7.50 bar	7.00 bar	7.00 bar
121 psi	121 psi	107 psi	107 psi	100 psi	100 psi
8215	6890	4900	4240	3500	3125
18150	15200	10800	9350	7750	6900
8.50 bar	8.50 bar	8.00 bar	8.00 bar	7.50 bar	7.50 bar
121 psi	121 psi	114 psi	114 psi	107 psi	107 psi
8700	7300	5200	4500	3700	3300
19200	16100	11500	9950	8150	7300
8.50 bar	8.50 bar	7.75 bar	7.75 bar	7.00 bar	7.00 bar
121 psi	121 psi	111 psi	111 psi	100 psi	100 psi



CAMSO WEX 552

Formerly Solideal WEX

PERFORMANCE AND QUALITY YOU CAN COUNT ON

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]						LOAD INDEX	SPEED SYMBOL
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.		
8.25-20	14	TT	6.50	7.00	-	-	-	-	-	-	148	A2
9.00-20	14	TT	7.00	6.50/7.50	1022	267	19.5	302	448	3090	153	A2
					40.2	10.5	25	11.9	17.6	121.7		
10.00-20	14	TT	7.50	7.00/8.00	1022	267	19.5	302	448	3090	153	A2
					40.2	10.5	25	11.9	17.6	121.7		
10.00-20	14	TT	7.50	7.00/8.00	1064	281	21	325	461	3208	155	A2
					41.9	11.1	26	12.8	18.1	126.3		
10.00-20	16	TT	7.50	7.00/8.00	1064	281	21	325	461	3208	158	A2
					41.9	11.1	26	12.8	18.1	126.3		

FEATURES

- Robust carcass
- Advanced rubber compounds
- Deep lug depth

BENEFITS

- Enhances stability and side impact resistance
- Improves durability and cut resistance
- Enhances durability and traction

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



MAXIMUM TIRE LOAD [kg] [lb]					
ALL SURFACES			IMPROVED SURFACES		
STATIC	CREEP	0-8 km/h 0-5 mph	10 km/h 6 mph	25 km/h 16 mph	45 km/h 28 mph
9.00 bar	9.00 bar	8.00 bar	8.00 bar	7.50 bar	7.50 bar
6990	5860	4170	3605	2975	2660
15450	12950	9200	7950	6550	5850
8.50 bar	8.50 bar	7.50 bar	7.50 bar	7.00 bar	7.00 bar
121 psi	121 psi	107 psi	107 psi	100 psi	100 psi
7455	6255	4450	3850	3175	2840
16450	13800	9800	8500	7000	6250
7.5 bar	7.5 bar	7.0 bar	7.0 bar	6.0 bar	6.0 bar
107 psi	107 psi	100 psi	100 psi	87 psi	87 psi
8215	6890	4900	4240	3500	3125
18150	15200	10800	9350	7750	6900
8.50 bar	8.50 bar	8.00 bar	8.00 bar	7.50 bar	7.50 bar
121 psi	121 psi	114 psi	114 psi	107 psi	107 psi



CAMSO WEX 583S

Formerly Solideal Bagger HT

SOLID PUNCTURE PROOF SOLUTION FOR SEVERE CONDITIONS

FEATURES

- Solid multi-stage construction
- Aggressive tread design
- Optimized lug-to-void ratio

BENEFITS

- Provides flat-free operation and good ride quality
- Provides enhanced traction in off-road conditions
- Enhances chunking resistance and stability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO CMP 533

COMPACTION PERFORMANCE AND DURABILITY SOLUTION

FEATURES

- Optimized tread pattern
- Robust carcass design
- Flatter tread profile
- Engineered tread profile with stepped tread design and shoulder lugs

BENEFITS

- Minimizes ground pressure and damage for better compaction performance
- Enhances side impact resistance for fewer flats
- Ensures even tread wearing for greater durability
- Enhances traction for improved performance

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	HEEL WIDTH	RIM SIZE	ACTUAL TIRE DIMENSIONS [mm] [inches]					HEEL		LOAD CAPACITY [kg] [lb]			
			O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.	NORMAL	QUICK	OTHER VEHICLES			STATIC
										6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	
9.00-20	7.00	7.00	974	224	40	391	2669	■	-	5400	4905	4500	6795
			38.3	8.8	50	15.4	105.1			11900	10800	9900	15000
10.00-20	7.00 7.50 8.00	7.00 7.50 8.00	1007	244	35	474	3184	■	-	6000	5450	5000	7550
			39.6	9.6	44	18.7	125.4			13250	12000	11000	16650
12.00-20	8.00 8.50	8.00 8.50	1088	259	38	507	3418	■	-	7560	6865	6300	9515
			42.8	10.2	48	20.0	134.6			16650	15150	13900	21000
12.00-24	8.50	8.50	1178	278	33	554	3716	■	-	8040	7305	6700	10115
			46.4	10.9	42	21.8	146.3			17750	16100	14750	22300
14.00-24	10.00	10.00	1330	333	29	620	4147	■	-	11000	10085	9250	13970
			52.4	13.1	37	24.4	163.3			24250	22250	20400	30800

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]						LOAD INDEX	SPEED SYMBOL	IP [bar] [psi]	LOAD CAPACITY [kg] [lb]	
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	M.D.S.	S.L.R.	R.C.				10 km/h 6 mph	15 km/h 9 mph
23.1-26 IND	12	TL	DW20B	DW20A TW20B	1593	590	27	726	669	4690	162	A8	1.9	5940	5370
					62.7	23.2	34	28.6	26.3	184.6				13100	11850



CAMSO CMP 576

Formerly Solideal SM C1

EXCELLENT COMPACTION PERFORMANCE

FEATURES

- Smooth, flat tread profile
- Heat-resistant rubber compound
- Robust tread shoulder

BENEFITS

- Promotes even wear and reduced ground pressure for better compaction performance
- Improves durability for lower cost per hour
- Provides optimum compaction and minimal grooving

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO MST 776

BEST HARD SURFACE DURABILITY

FEATURES

- Massive L5 smooth tread pattern
- Dual premium rubber compounds
- Impact guard sidewall design
- Rim guard protector

BENEFITS

- Ensures long service life and great puncture resistance
- Protects against tread cuts and reduces carcass heat build-up
- Deflects debris to better protect sidewalls
- Protects wheel for longer life and constant inflation and reduce stress cracking

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	IP [bar] [psi]	LOAD CAPACITY [kg] [lb]	
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	M.D.S.	S.L.R.	R.C.				10 km/h 6 mph	15 km/h 9 mph
7.50-15 NHS	14	TT	6.00	6.50	788	214	226	362	2352	136	A3	8.50	2835	2270
					31.0	8.4	8.9	14.3	92.6				121	5000
8.50/90-15K	6	TL	6.00	5.5F	761	217	246	342	-	120	A3	3.50	1770	1400
					30.0	8.5	9.7	13.5	-				50	3100
11.00-20 NHS	16	TT	8.00	8.50	1053	287	313	493	3307	167	A2	7.40	5500	4355
					41.5	11.3	12.3	19.4	130.2				107	9600
11.00-20 NHS	18	TT	8.00	8.50	1060	291	321	498	3284	169	A2	8.40	5900	-
					41.7	11.5	12.6	19.6	129.3				122	13005

#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
A	12.00-24	24	TT	8.50	8.00	1275	327	56	603	3981	178	A2	L-5S	LOADER-DOZER
						50.2	12.9	71	23.7	156.7				

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]											
		STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
A	9.75	12000	9750	8550	7500	6550	6300	6000	5800	5550	5250	5050	4725
	141	26455	21495	18850	16535	14440	13890	13230	12785	12235	11575	11135	10415



CAMSO WHL 753R

Formerly Solideal SRGP

RADIAL PERFORMANCE, VERSATILITY AND DURABILITY

TIRE SIZE	PR	TL/TT	RIM SIZE RECOMMENDED	ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
				O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.					
17.5R25	**	TL	14.00/1.5	1348	469	28	601	4023	182	A2	L-3	LOADER - DOZER	10 km/h
				53.1	18.5	35	23.7	158.4					5 mph
				1348	469	28	601	4023	167	B	E-3	EARTHMOVER	50 km/h
				53.1	18.5	35	23.7	158.4					30 mph
				1348	469	28	601	4023					40 km/h
53.1	18.5	35	23.7	158.4	153	A8	G-3	GRADER	25 mph				
20.5R25	**	TL	17.00/2.0	1483	528	31	665	4426	193	A2	L-3	LOADER - DOZER	10 km/h
				58.4	20.8	39	26.2	174.3					5 mph
				1483	528	31	665	4426	177	B	E-3	EARTHMOVER	50 km/h
				58.4	20.8	39	26.2	174.3					30 mph
				1483	528	31	665	4426					40 km/h
58.4	20.8	39	26.2	174.3	161	A8	G-3	GRADER	25 mph				
23.5R25	**	TL	19.50/2.5	1614	623	35	720	4817	201	A2	L-3	LOADER - DOZER	10 km/h
				63.5	24.5	44	28.3	189.8					5 mph
				1614	623	35	720	4817	185	B	E-3	EARTHMOVER	50 km/h
				63.5	24.5	44	28.3	189.8					30 mph
				1614	623	35	720	4817					40 km/h
63.5	24.5	44	28.3	189.8	170	A8	G-3	GRADER	25 mph				
26.5R25	**	TL	22.00/3.0	1746	704	40	779	5211	209	A2	L-3	LOADER - DOZER	10 km/h
				68.7	27.7	50	30.7	205.2					5 mph
				1746	704	40	779	5211	193	B	E-3	EARTHMOVER	50 km/h
				68.7	27.7	50	30.7	205.2					30 mph
29.5R25	**	TL	25.00/3.5	1870	782	40	834	5581	216	A2	L-3	LOADER - DOZER	10 km/h
				73.6	30.8	50	32.8	219.7					5 mph
				1870	782	40	834	5581	200	B	E-3	EARTHMOVER	50 km/h
				73.6	30.8	50	32.8	219.7					30 mph

LOADER - DOZER
Max speed % change to loads in above 10 km/h

STATIONARY	+60%	
CREEP	+30%	
4 km/h	2.5 mph	+15%
10 km/h	5 mph	No change
15 km/h	10 mph	-13%
25 km/h	15 mph	-20%

One way distance up to 76 m (250 feet)

GRADER
Max speed % change to loads in above 40 km/h

40 km/h	25 mph	No change
50 km/h	30 mph	-9%
60 km/h	35 mph	-18%
65 km/h	40 mph	-27%
	10 mph	-13%
	15 mph	-20%

EARTHMOVER
Max speed % change to loads in above 50 km/h

50 km/h	30 mph	No change
65 km/h	40 mph	-12%

One way distance up to 4 km (2.5 miles)

CREEP: Movement of equipment at very slow speed (not over 60 m (200 feet) in 30 minutes). During creep motion, loads on the tire are very high and consideration must be given to the type of surface over which the equipment is travelling.

For maintenance work on established highways, inflation pressures may be increased 50% if desired with no increase in loads. For slope and ditching service, inflation pressures should be increased 100 kpa (15 psi) with no increase in load rating.

FEATURES	BENEFITS	PERFORMANCE
<ul style="list-style-type: none"> Heavy-duty Dual-Star carcass Optimized tread pattern Offset tapered tread lugs Non-directional stepped design 	<ul style="list-style-type: none"> Enhances stability and suitability for both one-star and two-star applications Provides excellent durability and low wear rate Reduces vibration for improved ride quality Enhances cleanout for improved traction 	<p>TIRE LIFE</p> <p>PUNCTURE RESISTANCE</p> <p>TRACTION</p>

MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]																			
1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
25	29	32	36	39	43	46	50	54	57	61	64	68	71	75	79	82	86	89	93
-	3650	4000	4250	4625	4850	5300	5600	5800	6000	6150	6500	6700	7100	7300	7500	7750	8000	8250	8500
-	8050	8800	9350	10200	10700	11700	12300	12800	13200	13600	14300	14800	15700	16100	16500	17100	17600	18200	18700
-	-	-	-	3350	3550	3750	4000	4125	4375	4625	4750	5000	5150	5450	-	-	-	-	-
-	-	-	-	7400	7850	8250	8800	9100	9650	10200	10500	11000	11400	12000	-	-	-	-	-
2360	2650	2900	3075	3350	3650	-	-	-	-	-	-	-	-	-	-	-	-	-	-
5200	5840	6400	6800	7400	8050	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	4750	5150	5600	6000	6300	6700	7100	7500	8000	8250	8750	9000	9500	9750	10000	10300	10900	11200	11500
-	10500	11400	12300	13200	13900	14800	15700	16500	17600	18200	19300	19800	20900	21500	22000	22700	24000	24700	25400
-	-	-	-	4375	4750	5000	5300	5600	5800	6150	6500	6700	6900	7300	-	-	-	-	-
-	-	-	-	9650	10500	11000	11700	12300	12800	13600	14300	14800	15200	16100	-	-	-	-	-
3150	3450	3875	4125	4375	4625	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	6000	6500	7100	7750	8250	8750	9250	9750	10300	10600	11200	11500	12150	12500	12850	13200	13600	14000	14500
-	13200	14300	15700	17100	18200	19300	20400	21500	22700	23400	24700	25400	26800	27600	28300	29100	30000	30900	32000
-	-	-	-	5600	6000	6500	6700	7100	7500	7750	8250	8500	9000	9250	-	-	-	-	-
-	-	-	-	12300	13200	14300	14800	15700	16500	17100	18200	18700	19800	20400	-	-	-	-	-
4000	4500	4875	5300	5600	6000	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8800	9900	10700	11700	12300	13200	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	7500	8250	9000	9500	10300	10900	11500	12150	12850	13200	14000	14500	15000	15500	16000	16500	17000	18000	18500
-	16500	18200	19800	20900	22700	24000	25400	26800	28300	29100	30900	32000	33100	34200	35300	36400	37500	39700	40800
-	-	-	-	7100	7500	8000	8500	9000	9500	9750	10300	10600	11200	11500	-	-	-	-	-
-	-	-	-	15700	16500	17600	18700	19800	20900	21500	22700	23400	24700	25400	-	-	-	-	-
-	-	-	-	-	-	-	-	-	15500	16000	17000	17500	18000	19000	19500	20000	20600	21200	22400
-	-	-	-	-	-	-	-	-	34200	35300	37500	38600	39700	41900	43000	44100	45400	46700	49400
-	-	-	-	8500	9250	9750	10300	10900	11500	11800	12500	12850	13600	14000	-	-	-	-	-
-	-	-	-	18700	20400	21500	22700	24000	25400	26000	27600	28300	30000	30900	-	-	-	-	-



CAMSO ADT 753R

Formerly Solideal SRAT

RADIAL PERFORMANCE MEETS HIGH TRACTION

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
			RECOMMENDED	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.						
20.5R25	**	TL	17.00/2.0	1485	524	31	663	4460	193	A2	L-3	LOADER - DOZER	10 km/h	
				58.5	20.6	39	26.1	175.6					5 mph	
				1485	524	31	663	4460	177	B	E-3	EARTHMOVER	50 km/h	
				58.5	20.6	39	26.1	175.6					30 mph	
				1485	524	31	663	4460	161	A8	G-3	GRADER	40 km/h	
				58.5	20.6	39	26.1	175.6					25 mph	
23.5R25	**	TL	19.50/2.5	1615	614	29	716	4850	201	A2	L-3	LOADER - DOZER	10 km/h	
				63.6	24.2	37	28.2	190.9					5 mph	
				1615	614	29	716	4850	185	B	E-3	EARTHMOVER	50 km/h	
				63.6	24.2	37	28.2	190.9					30 mph	
26.5R25	**	TL	22.00/3.0	1736	688	33	767	5236	209	A2	L-3	LOADER - DOZER	10 km/h	
				68.3	27.1	42	30.2	206.1					5 mph	
				1736	688	33	767	5236	193	B	E-3	EARTHMOVER	50 km/h	
				68.3	27.1	42	30.2	206.1					30 mph	
29.5R25	**	TL	25.00/3.5	1871	777	38	817	5619	216	A2	L-3	LOADER - DOZER	10 km/h	
				73.7	30.6	48	32.2	221.2					5 mph	
				1871	777	38	817	5619	200	B	E-3	EARTHMOVER	50 km/h	
				73.7	30.6	48	32.2	221.2					30 mph	

LOADER – DOZER
Max speed % change to loads in above 10 km/h

STATIONARY	+60%	
CREEP	+30%	
4 km/h	2.5 mph	+15%
10 km/h	5 mph	No change
15 km/h	10 mph	-13%
25 km/h	15 mph	-20%

One way distance up to 76 m (250 feet)

GRADER
Max speed % change to loads in above 40 km/h

40 km/h	25 mph	No change
50 km/h	30 mph	-9%
60 km/h	35 mph	-18%
65 km/h	40 mph	-27%
	10 mph	-13%
	15 mph	-20%

EARTHMOVER
Max speed % change to loads in above 50 km/h

50 km/h	30 mph	No change
65 km/h	40 mph	-12%

One way distance up to 4 km (2.5 miles)

CREEP: Movement of equipment at very slow speed (not over 60 m (200 feet) in 30 minutes). During creep motion, loads on the tire are very high and consideration must be given to the type of surface over which the equipment is travelling.

For maintenance work on established highways, inflation pressures may be increased 50% if desired, with no increase in loads. For slope and ditching service, inflation pressures should be increased 100 kpa (15 psi) with no increase in load rating.

FEATURES

- Heavy-duty Dual-Star carcass
- Non-directional tread pattern with optimized lug-to-void ratio
- Deep tread depth
- Premium rubber compounds

BENEFITS

- Optimizes stability for articulated dump truck applications
- Increases traction and durability in off-road conditions
- Enhances traction in off-road conditions
- Reduces heat build-up

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]																			
1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
25	29	32	36	39	43	46	50	54	57	61	64	68	71	75	79	82	86	89	93
-	4750	5150	5600	6000	6300	6700	7100	7500	8000	8250	8750	9000	9500	9750	10000	10300	10900	11200	11500
-	10500	11400	12300	13200	13900	14800	15700	16500	17600	18200	19300	19800	20900	21500	22000	22700	24000	24700	25400
-	-	-	-	4375	4750	5000	5300	5600	5800	6150	6500	6700	6900	7300	-	-	-	-	-
-	-	-	-	9650	10500	11000	11700	12300	12800	13600	14300	14800	15200	16100	-	-	-	-	-
3150	3450	3875	4125	4375	4625	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	6000	6500	7100	7750	8250	8750	9250	9750	10300	10600	11200	11500	12150	12500	12850	13200	13600	14000	14500
-	13200	14300	15700	17100	18200	19300	20400	21500	22700	23400	24700	25400	26800	27600	28300	29100	30000	30900	32000
-	-	-	-	5600	6000	6500	6700	7100	7500	7750	8250	8500	9000	9250	-	-	-	-	-
-	-	-	-	12300	13200	14300	14800	15700	16500	17100	18200	18700	19800	20400	-	-	-	-	-
-	7500	8250	9000	9500	10300	10900	11500	12150	12850	13200	14000	14500	15000	15500	16000	16500	17000	18000	18500
-	16500	18200	19800	20900	22700	24000	25400	26800	28300	29100	30900	32000	33100	34200	35300	36400	37500	39700	40800
-	-	-	-	7100	7500	8000	8500	9000	9500	9750	10300	10600	11200	11500	-	-	-	-	-
-	-	-	-	15700	16500	17600	18700	19800	20900	21500	22700	23400	24700	25400	-	-	-	-	-
-	-	-	-	-	-	-	-	-	15500	16000	17000	17500	18000	19000	19500	20000	20600	21200	22400
-	-	-	-	-	-	-	-	-	34200	35300	37500	38600	39700	41900	43000	44100	45400	46700	49400
-	-	-	-	8500	9250	9750	10300	10900	11500	11800	12500	12850	13600	14000	-	-	-	-	-
-	-	-	-	18700	20400	21500	22700	24000	25400	26000	27600	28300	30000	30900	-	-	-	-	-



CAMSO WHL 775R

Formerly Solideal SRLD L5

MULTI-SURFACE DURABILITY AT ITS BEST

TIRE SIZE	PR	TL/TT	RIM SIZE RECOMMENDED	ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
				O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.					
20.5R25	**	TL	17.00/2.0	1544	517	74	704	4637	193	A2	L-5	LOADER – DOZER	10 km/h
				60.8	20.4	93	27.7	182.6					5 mph
				1544	517	74	704	4637	177	B	L-5	EARTHMOVER	50 km/h
				60.8	20.4	93	27.7	182.6					30 mph
				1544	517	74	704	4637					40 km/h
60.8	20.4	93	27.7	182.6	161	A8	L-5	GRADER	25 mph				
23.5R25	**	TL	19.50/2.5	1673	605	80	751	5025	201	A2	L-5	LOADER – DOZER	10 km/h
				65.9	23.8	101	29.6	197.8					5 mph
				1673	605	80	751	5025	185	B	E-5	EARTHMOVER	50 km/h
				65.9	23.8	101	29.6	197.8					30 mph
26.5R25	**	TL	22.00/3.0	1791	700	86	801	5379	209	A2	L-5	LOADER – DOZER	10 km/h
				70.5	27.6	108	31.5	211.8					5 mph
				1791	700	86	801	5379	193	B	E-5	EARTHMOVER	50 km/h
				70.5	27.6	108	31.5	211.8					30 mph
29.5R25	**	TL	25.00/3.5	1915	790	92	855	5751	216	A2	L-5	LOADER – DOZER	10 km/h
				75.4	31.1	116	33.7	226.4					5 mph
				1915	790	92	855	5751	200	B	L-5	EARTHMOVER	50 km/h
				75.4	31.1	116	33.7	226.4					30 mph

LOADER – DOZER
Max speed % change to loads in above 10 km/h

STATIONARY	+60%	
CREEP	+30%	
4 km/h	2.5 mph	+15%
10 km/h	5 mph	No change
15 km/h	10 mph	-13%
25 km/h	15 mph	-20%

One way distance up to 76 m (250 feet)

GRADER
Max speed % change to loads in above 40 km/h

40 km/h	25 mph	No change
50 km/h	30 mph	-9%
60 km/h	35 mph	-18%
65 km/h	40 mph	-27%
	10 mph	-13%
	15 mph	-20%

EARTHMOVER
Max speed % change to loads in above 50 km/h

50 km/h	30 mph	No change
65 km/h	40 mph	-12%

One way distance up to 4 km (2.5 miles)

CREEP: Movement of equipment at very slow speed (not over 60 m (200 feet) in 30 minutes). During creep motion, loads on the tire are very high and consideration must be given to the type of surface over which the equipment is travelling.

For maintenance work on established highways, inflation pressures may be increased 50% if desired, with no increase in loads. For slope and ditching service, inflation pressures should be increased 100 kpa (15 psi) with no increase in load rating.

FEATURES	BENEFITS	PERFORMANCE
<ul style="list-style-type: none"> Extra-deep lug tread 	<ul style="list-style-type: none"> Enhances durability and resistance to flat tires for extreme mixed and hard surface applications 	TIRE LIFE
<ul style="list-style-type: none"> Robust Dual-Star carcass 	<ul style="list-style-type: none"> Provides excellent stability and enhanced loading capacity 	PUNCTURE RESISTANCE
<ul style="list-style-type: none"> Contoured lug base 	<ul style="list-style-type: none"> Promotes stone ejection and resistance to cracking 	TRACTION
<ul style="list-style-type: none"> Heavy-duty sidewall construction 	<ul style="list-style-type: none"> Protects against side impacts and deformation under heavy load 	

MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]																			
1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
25	29	32	36	39	43	46	50	54	57	61	64	68	71	75	79	82	86	89	93
-	4750	5150	5600	6000	6300	6700	7100	7500	8000	8250	8750	9000	9500	9750	10000	10300	10900	11200	11500
-	10500	11400	12300	13200	13900	14800	15700	16500	17600	18200	19300	19800	20900	21500	22000	22700	24000	24700	25400
-	-	-	-	4375	4750	5000	5300	5600	5800	6150	6500	6700	6900	7300	-	-	-	-	-
-	-	-	-	9650	10500	11000	11700	12300	12800	13600	14300	14800	15200	16100	-	-	-	-	-
3150	3450	3875	4125	4375	4625	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	6000	6500	7100	7750	8250	8750	9250	9750	10300	10600	11200	11500	12150	12500	12850	13200	13600	14000	14500
-	13200	14300	15700	17100	18200	19300	20400	21500	22700	23400	24700	25400	26800	27600	28300	29100	30000	30900	32000
-	-	-	-	5600	6000	6500	6700	7100	7500	7750	8250	8500	9000	9250	-	-	-	-	-
-	-	-	-	12300	13200	14300	14800	15700	16500	17100	18200	18700	19800	20400	-	-	-	-	-
-	7500	8250	9000	9500	10300	10900	11500	12150	12850	13200	14000	14500	15000	15500	16000	16500	17000	18000	18500
-	16500	18200	19800	20900	22700	24000	25400	26800	28300	29100	30900	32000	33100	34200	35300	36400	37500	39700	40800
-	-	-	-	7100	7500	8000	8500	9000	9500	9750	10300	10600	11200	11500	-	-	-	-	-
-	-	-	-	15700	16500	17600	18700	19800	20900	21500	22700	23400	24700	25400	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	15500	16000	17000	17500	18000	19000	19500	20000	20600	21200
-	-	-	-	-	-	-	-	-	-	34200	35300	37500	38600	39700	41900	43000	44100	45400	46700
-	-	-	-	8500	9250	9750	10300	10900	11500	11800	12500	12850	13600	14000	-	-	-	-	-
-	-	-	-	18700	20400	21500	22700	24000	25400	26000	27600	28300	30000	30900	-	-	-	-	-



CAMSO WHL 776R

Formerly Solideal SRLS L5S

HARD SURFACE DURABILITY AT ITS BEST

TIRE SIZE	PR	TL/TT	RIM SIZE RECOMMENDED	ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE	APPLICATION
				O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.					
17.5R25	**	TL	14.00/1.5	1402	443	75	646	4211	182	A2	L-5	LOADER – DOZER	10 km/h
				55.2	17.4	94	25.4	165.8					5 mph
				1402	443	75	646	4211	167	B	E-5	EARTHMOVER	50 km/h
				55.2	17.4	94	25.4	165.8					30 mph
23.5R25	**	TL	19.50/2.5	1673	623	80	762	5025	201	A2	L-5	LOADER – DOZER	10 km/h
				65.9	24.5	101	30.0	197.8					5 mph
				1673	623	80	762	5025	185	B	E-5	EARTHMOVER	50 km/h
				65.9	24.5	101	30.0	197.8					30 mph
26.5R25	**	TL	22.00/3.0	1785	709	86	800	5361	209	A2	L-5	LOADER – DOZER	10 km/h
				70.3	27.9	108	31.5	211.1					5 mph
				1785	709	86	800	5361	193	B	E-5	EARTHMOVER	50 km/h
				70.3	27.9	108	31.5	211.1					30 mph

LOADER – DOZER
Max speed % change to loads in above 10 km/h

STATIONARY	+60%
CREEP	+30%
4 km/h	2.5 mph +15%
10 km/h	5 mph No change
15 km/h	10 mph -13%
25 km/h	15 mph -20%

One way distance up to 76 m (250 feet)

EARTHMOVER
Max speed % change to loads in above 50 km/h

50 km/h	30 mph	No change
65 km/h	40 mph	-12%

One way distance up to 4 km (2.5 miles)

CREEP: Movement of equipment at very slow speed (not over 60 m (200 feet) in 30 minutes). During creep motion, loads on the tire are very high and consideration must be given to the type of surface over which the equipment is travelling.

FEATURES

- Extra-deep smooth tread
- Robust Dual-Star carcass
- Flat tread profile
- Heavy-duty sidewall construction

BENEFITS

- Best durability and resistance to flat tires for extreme hard surface applications
- Provides excellent stability and enhanced loading capability
- Provides enhanced stability and even wear
- Protects against side impacts and deformation under heavy load

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



MAXIMUM TIRE LOAD AT REFERENCE SPEED [kg] [lb] AND MAXIMUM INFLATION PRESSURE [bar] [psi]																				
1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	
25	29	32	36	39	43	46	50	54	57	61	64	68	71	75	79	82	86	89	93	
-	3650	4000	4250	4625	4850	5300	5600	5800	6000	6150	6500	6700	7100	7300	7500	7750	8000	8250	8500	
-	8050	8800	9350	10200	10700	11700	12300	12800	13200	13600	14300	14800	15700	16100	16500	17100	17600	18200	18700	
-	-	-	-	3350	3550	3750	4000	4125	4375	4625	4750	5000	5150	5450	-	-	-	-	-	
-	-	-	-	7400	7850	8250	8800	9100	9650	10200	10500	11000	11400	12000	-	-	-	-	-	
-	6000	6500	7100	7750	8250	8750	9250	9750	10300	10600	11200	11500	12150	12500	12850	13200	13600	14000	14500	
-	13200	14300	15700	17100	18200	19300	20400	21500	22700	23400	24700	25400	26800	27600	28300	29100	30000	30900	32000	
-	-	-	-	5600	6000	6500	6700	7100	7500	7750	8250	8500	9000	9250	-	-	-	-	-	
-	-	-	-	12300	13200	14300	14800	15700	16500	17100	18200	18700	19800	20400	-	-	-	-	-	
-	7500	8250	9000	9500	10300	10900	11500	12150	12850	13200	14000	14500	15000	15500	16000	16500	17000	18000	18500	
-	16500	18200	19800	20900	22700	24000	25400	26800	28300	29100	30900	32000	33100	34200	35300	36400	37500	39700	40800	
-	-	-	-	7100	7500	8000	8500	9000	9500	9750	10300	10600	11200	11500	-	-	-	-	-	
-	-	-	-	15700	16500	17600	18700	19800	20900	21500	22700	23400	24700	25400	-	-	-	-	-	



CAMSO GRD 533R

OPTIMIZED TRACTION AND PERFORMANCE ON MULTIPLE SURFACES

FEATURES

- Non-directional tread pattern
- Wide flat tread profile
- Interconnected multi-block tread pattern
- Strong radial carcass

BENEFITS

- Optimizes durability and traction
- Provides enhanced grip, stability and flotation
- Improves self-cleaning and traction on soft soils
- Maximizes comfort, traction and durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



TIRE SIZE	STAR RATING	RIM SIZE		ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	TREAD CODE	INFLATION PRESSURE [bar] [PSI]	LOAD CAPACITY [kg] [lb]	
		RECOMMENDED	ALTERNATIVE	O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32°]	S.L.R. [mm] [in]	R.C. [mm] [in]					40 km/h 25 mph	50 km/h 31 mph
14.00R24	*	8.00TG (SDC)	9.00/1.5 (DC); 10.00VA (SDC)	1357	361	27	615	4038	153	A8	G-2	3.75	3650	3325
				53.4	14.2	34	24.2	159.0				54	8045	7330



CAMSO EMT 553R

OPTIMIZED ON-ROAD AND OFF-ROAD PERFORMANCE

FEATURES

- Non-directional tread pattern
- Interconnected multi-block tread pattern
- Strong radial carcass
- Low profile tyre size

BENEFITS

- Increases durability and versatility on mixed and hard surfaces
- Improves stability, self-cleaning and grip on soft soils
- Maximizes comfort, traction and durability
- Maximizes footprint, stability and wearable rubber volume

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	SR	ALLOWED RIM SIZES	ACTUAL TIRE DIMENSIONS					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
				O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32°]	S.L.R. [mm] [in]	R.C. [mm] [in]				
A	600/65R25	*	19.50/2.5; 17.00/2.0; 17.00/1.7	1410	605	36	623	4252	187	A2	L-3	LOADER - DOZER
				55.5	23.8	45	24.5	167.4				
B	650/65R25	*/**	19.50/2.5	1481	635	40	655	4467	193	A2	L-3	LOADER - DOZER
				58.3	25.0	50	25.8	175.9				
C	650/65R25	*/**	19.50/2.5	1481	635	40	655	4467	180	B	E-3	EARTHMOVER
				58.3	25.0	50	25.8	175.9				
D	750/65R25	**	22.00/3.0; 24.00/3.0; 25.00/3.0	1592	722	40	686	4801	209	A2	L-3	LOADER - DOZER
				62.7	28.4	50	27.0	189.0				
E	750/65R25	**	22.00/3.0; 24.00/3.0; 25.00/3.0	1592	722	40	686	4801	190	B	E-3	EARTHMOVER
				62.7	28.4	50	27.0	189.0				

#	APPLICATION	INFLATION PRESSURE [bar] [PSI]	MAXIMUM TIRE LOAD [kg] [lb]					
			5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	25 km/h 16 mph	50 km/h 31 mph	65 km/h 40 mph
A	*	4.75	11100	9750	8500	7800	6150	-
		69	24470	21495	18740	17195	13560	-
B	*	4.75	13100	11500	10000	9200	7250	-
		69	28880	25355	22045	20285	15985	-
C	**	4.25	-	-	8950	-	8000	7050
		62	-	-	19730	-	17635	15545
D	**	6.25	21100	18500	16100	14800	11700	-
		91	46520	40785	35495	32630	25795	-
E	**	4.25	-	-	11900	-	10600	9350
		62	-	-	26235	-	23370	20615



CAMSO LM L2

OFF-ROAD TRACTION AND DURABILITY

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
15.5-25	12	TL	12.00/1.3	13.00/1.4 (DC)	1283	403	26	574	3822	168	A2	L-2	LOADER-DOZER
					50.5	15.9	33	22.6	150.5				
					1283	403	26	574	3822	149	B	E-2	EARTHMOVER
					50.5	15.9	33	22.6	150.5				
					1283	403	26	574	3822				
50.5	15.9	33	22.6	150.5	142	A8	G-2	GRADER					
15.5-25	16	TL	12.00/1.3	-	1280	417	26	564	3834	175	A2	L-2	LOADER-DOZER
					50.4	16.4	33	22.2	150.9				
					1280	417	26	564	3834	156	B	E-2	EARTHMOVER
					50.4	16.4	33	22.2	150.9				
					1280	417	26	564	3834				
50.4	16.4	33	22.2	150.9	146	A8	G-2	GRADER					
17.5-25	12	TL	14.00/1.5	14.00/1.3 13.00/1.4 (DC)	1356	456	26	604	3972	171	A2	L-2	LOADER-DOZER
					53.4	18.0	33	23.8	156.4				
					1356	456	26	604	3972	153	B	E-2	EARTHMOVER
					53.4	18.0	33	23.8	156.4				
					1356	456	26	604	3972				
53.4	18.0	33	23.8	156.4	145	A8	G-2	GRADER					
17.5-25	16	TL	14.00/1.5	14.00/1.3 (DC)	1337	460	26	599	4013	177	A2	L-2	LOADER-DOZER
					52.6	18.1	33	23.6	158.0				
					1337	460	26	599	4013	158	B	E-2	EARTHMOVER
					52.6	18.1	33	23.6	158.0				
					1337	460	26	599	4013				
52.6	18.1	33	23.6	158.0	150	A8	G-2	GRADER					
17.5-25	24	TL	14.00/1.5	-	1357	460	26	*	*	188	A2	L-2	LOADER-DOZER
					53.4	18.1	33	*	*				
					1357	460	26	*	*	171	B	E-2	EARTHMOVER
					53.4	18.1	33	*	*				
20.5-25	16	TL	17.00/2.0	17.00/1.7	1497	540	30	645	4453	181	A2	L-2	LOADER-DOZER
					58.9	21.3	38	25.4	175.3				
					1497	540	30	645	4453	167	B	E-2	EARTHMOVER
					58.9	21.3	38	25.4	175.3				
					1497	540	30	645	4453				
58.9	21.3	38	25.4	175.3	156	A8	G-2	GRADER					

FEATURES

- Heavy-duty carcass
- Stepped tread design
- Deep and flat tread profile

BENEFITS

- Increases side impact resistance and stability
- Enhances tread cleanout for improved traction
- Reduces tread crowning for improved durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
4.00	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3530	-	-	-	
58	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7780	-	-	-	
2.50	-	-	-	-	3650	3575	3500	3450	3375	3350	3325	3250	3150	3000	2700	
36	-	-	-	-	8045	7880	7715	7605	7440	7385	7330	7165	6945	6615	5950	
2.25	-	-	-	-	-	-	-	-	-	2650	-	2400	-	2175	1925	
32	-	-	-	-	-	-	-	-	-	5840	-	5290	-	4795	4245	
5.50	11000	8950	7850	6900	6000	5800	5500	5300	5100	4825	4625	4350	-	-	-	
80	24250	19730	17305	15210	13230	12785	12125	11685	11245	10635	10195	9590	-	-	-	
3.25	-	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
47	-	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	
3.25	-	-	-	-	-	-	-	-	-	3550	-	3225	-	2900	2600	
47	-	-	-	-	-	-	-	-	-	7825	-	7110	-	6395	5730	
3.50	9850	8000	7000	6150	5350	5150	4925	4725	4550	4300	4120	3875	-	-	-	
51	21715	17635	15430	13560	11795	11355	10860	10415	10030	9480	9085	8545	-	-	-	
2.25	-	-	-	-	4100	4025	3950	3875	3800	3750	3725	3650	3550	3350	3025	
32	-	-	-	-	9040	8875	8710	8545	8380	8265	8210	8045	7825	7385	6670	
2.00	-	-	-	-	-	-	-	-	-	2900	-	2650	-	2375	2125	
29	-	-	-	-	-	-	-	-	-	6398	-	5840	-	5235	4685	
4.75	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4890	4600	-	-	-	
69	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10780	10140	-	-	-	
3.00	-	-	-	-	4750	4675	4600	4500	4425	4375	4325	4250	4125	3900	3525	
44	-	-	-	-	10470	10305	10140	9920	9755	9645	9535	9370	9095	8600	7770	
2.75	-	-	-	-	-	-	-	-	-	3350	-	3050	-	2750	2450	
40	-	-	-	-	-	-	-	-	-	7385	-	6725	-	6065	5400	
7.00	16000	13000	11400	10000	8700	8400	8000	7700	7400	7000	6700	6300	-	-	-	
102	35275	28660	25135	22045	19180	18520	17635	16975	16315	15430	14770	13890	-	-	-	
4.75	-	-	-	-	6890	6765	6640	6520	6395	6335	6275	6150	5950	5650	5100	
69	-	-	-	-	15190	14915	14640	14375	14100	13965	13835	13560	13120	12455	11245	
3.50	13200	10700	9400	8250	7200	6950	6600	6350	6100	5800	5530	5200	-	-	-	
51	29100	23590	20725	18190	15875	15320	14550	14000	13450	12785	12190	11465	-	-	-	
2.75	-	-	-	-	6100	6000	5900	5800	5650	5600	5550	5450	5300	5000	4525	
40	-	-	-	-	13450	13230	13005	12785	12455	12345	12235	12015	11685	11025	9975	
2.25	-	-	-	-	-	-	-	-	-	4000	-	3650	-	3275	2925	
32	-	-	-	-	-	-	-	-	-	8820	-	8045	-	7220	6450	



CAMSO LM L3

MULTI-SURFACE PERFORMANCE

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
15.5-25	12	TL	12.00/1.3	13.00/1.4 (DC)	1283	415	27	578	3852	168	A2	L-3	LOADER-DOZER
					50.5	16.4	34	22.8	151.7				
					1283	415	27	578	3852	149	B	E-3	EARTHMOVER
					50.5	16.4	34	22.8	151.7				
					1283	415	27	578	3852				
50.5	16.4	34	22.8	151.7	142	A8	G-3	GRADER					
15.5-25	16	TL	12.00/1.3	-	1276	414	27	576	3898	175	A2	L-3	LOADER-DOZER
					50.2	16.3	34	22.7	153.5				
					1276	414	27	576	3898	156	B	E-3	EARTHMOVER
					50.2	16.3	34	22.7	153.5				
					1276	414	27	576	3898				
50.2	16.3	34	22.7	153.5	152	A8	G-3	GRADER					
17.5-25	12	TL	14.00/1.5	14.00/1.3 13.00/1.4 (DC)	1390	470	27	625	4093	171	A2	L-3	LOADER-DOZER
					54.7	18.5	34	24.6	161.1				
					1390	470	27	625	4093	153	B	E-3	EARTHMOVER
					54.7	18.5	34	24.6	161.1				
					1390	470	27	625	4093				
54.7	18.5	34	24.6	161.1	145	A8	G-3	GRADER					
17.5-25	16	TL	14.00/1.5	14.00/1.3 (DC)	1391	460	26	628	4172	177	A2	L-3	LOADER-DOZER
					54.8	18.1	33	24.7	164.3				
					1391	460	26	628	4172	158	B	E-3	EARTHMOVER
					54.8	18.1	33	24.7	164.3				
					1391	460	26	628	4172				
54.8	18.1	33	24.7	164.3	150	A8	G-3	GRADER					
17.5-25	20	TL	14.00/1.5	14.00/1.3 (DC)	1363	477	28	619	4086	181	A2	L-3	LOADER-DOZER
					53.7	18.8	35	24.4	160.9				
					1363	477	28	619	4086	164	B	E-3	EARTHMOVER
					53.7	18.8	35	24.4	160.9				
20.5-25	16	TL	17.00/2.0	17.00/1.7	1503	545	32	661	4365	181	A2	L-3	LOADER-DOZER
					59.2	21.5	40	26.0	171.9				
					1503	545	32	661	4365	167	B	E-3	EARTHMOVER
					59.2	21.5	40	26.0	171.9				
					1503	545	32	661	4365				
59.2	21.5	40	26.0	171.9	156	A8	G-3	GRADER					

FEATURES

- Heavy-duty carcass
- Non-directional tread pattern with optimized lug-to-void ratio
- Stepped tread design
- Deep and flat tread profile

BENEFITS

- Increases side impact resistance and stability
- Ensures even tread wearing for greater durability
- Enhances tread cleanout for improved traction
- Reduces tread crowning for improved durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
4.00	8950	7300	6400	5600	4875	4700	4475	4300	4150	3925	3750	3530	-	-	-	
58	19730	16095	14110	12345	10750	10360	9865	9480	9150	8655	8265	7780	-	-	-	
2.50	-	-	-	-	3650	3575	3500	3450	3375	3350	3325	3250	3150	3000	2700	
36	-	-	-	-	8045	7880	7715	7605	7440	7385	7330	7165	6945	6615	5950	
2.25	-	-	-	-	-	-	-	-	-	2650	-	2400	-	2175	1925	
32	-	-	-	-	-	-	-	-	-	5840	-	5290	-	4795	4245	
5.50	11000	8950	7850	6900	6000	5800	5500	5300	5100	4825	4625	4350	-	-	-	
80	24250	19730	17305	15210	13230	12785	12125	11685	11245	10635	10195	9590	-	-	-	
3.25	-	-	-	-	4475	4400	4325	4250	4150	4125	4075	4000	3875	3675	3325	
47	-	-	-	-	9865	9700	9535	9370	9150	9095	8985	8820	8545	8100	7330	
3.25	-	-	-	-	-	-	-	-	-	3550	-	3225	-	2900	2600	
47	-	-	-	-	-	-	-	-	-	7825	-	7110	-	6395	5730	
3.50	9850	8000	7000	6150	5350	5150	4925	4725	4550	4300	4120	3875	-	-	-	
51	21715	17635	15430	13560	11795	11355	10860	10415	10030	9480	9085	8545	-	-	-	
2.25	-	-	-	-	4100	4025	3950	3875	3800	3750	3725	3650	3550	3350	3025	
32	-	-	-	-	9040	8875	8710	8545	8380	8265	8210	8045	7825	7385	6670	
2.00	-	-	-	-	-	-	-	-	-	2900	-	2650	-	2375	2125	
29	-	-	-	-	-	-	-	-	-	6398	-	5840	-	5235	4685	
4.75	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4890	4600	-	-	-	
69	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10780	10140	-	-	-	
3.00	-	-	-	-	4750	4675	4600	4500	4425	4375	4325	4250	4125	3900	3525	
44	-	-	-	-	10470	10305	10140	9920	9755	9645	9535	9370	9095	8600	7770	
2.75	-	-	-	-	-	-	-	-	-	3350	-	3050	-	2750	2450	
40	-	-	-	-	-	-	-	-	-	7385	-	6725	-	6065	5400	
5.75	13200	10700	9400	8250	7200	6950	6600	6350	6100	5800	5550	5200	-	-	-	
83	29100	23590	20725	18190	15875	15320	14550	14000	13450	12785	12235	11465	-	-	-	
4.00	-	-	-	-	5600	5500	5400	5300	5200	5150	5100	5000	4850	4600	4150	
58	-	-	-	-	12345	12125	11905	11685	11465	11355	11245	11025	10690	10140	9150	
3.50	13200	10700	9400	8250	7200	6950	6600	6350	6100	5800	5530	5200	-	-	-	
51	29100	23590	20725	18190	15875	15320	14550	14000	13450	12785	12190	11465	-	-	-	
2.75	-	-	-	-	6100	6000	5900	5800	5650	5600	5550	5450	5300	5000	4525	
40	-	-	-	-	13450	13230	13005	12785	12455	12345	12235	12015	11685	11025	9975	
2.25	-	-	-	-	-	-	-	-	-	4000	-	3650	-	3275	2925	
32	-	-	-	-	-	-	-	-	-	8820	-	8045	-	7220	6450	



CAMSO LM L3 (cont.)

MULTI-SURFACE PERFORMANCE

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
20.5-25	20	TL	17.00/2.0	-	1507	546	30	669	4478	186	A2	L-3	LOADER-DOZER
					59.3	21.5	38	26.3	176.3				
					1507	546	30	669	4478	170	B	E-3	EARTHMOVER
					59.3	21.5	38	26.3	176.3				
23.5-25	20	TL	19.50/2.5	-	1616	627	37	729	4835	191	A2	L-3	LOADER-DOZER
					63.6	24.7	47	28.7	190.4				
					1616	627	37	729	4835	177	B	E-3	EARTHMOVER
					63.6	24.7	47	28.7	190.4				
23.5-25	24	TL	19.50/2.5	-	1630	630	37	734	4865	196	A2	L-3	LOADER-DOZER
					64.2	24.8	47	28.9	191.5				
					1630	630	37	734	4865	180	B	E-3	EARTHMOVER
					64.2	24.8	47	28.9	191.5				
26.5-25	20	TL	22.00/3.0	-	1752	691	40	781	5229	198	A2	L-3	LOADER-DOZER
					69.0	27.2	50	30.7	205.9				
					1752	691	40	781	5229	181	B	E-3	EARTHMOVER
					69.0	27.2	50	30.7	205.9				
26.5-25	28	TL	22.00/3.0	-	1748	693	40	786	5274	203	A2	L-3	LOADER-DOZER
					68.8	27.3	50	30.9	207.6				
					1748	693	40	786	5274	188	B	E-3	EARTHMOVER
					68.8	27.3	50	30.9	207.6				
29.5-25	28	TL	25.00/3.5	-	1873	770	36	835	5590	207	A2	L-3	LOADER-DOZER
					73.7	30.3	45	32.9	220.1				
					1873	770	36	835	5590	193	B	E-3	EARTHMOVER
					73.7	30.3	45	32.9	220.1				

FEATURES

- Heavy-duty carcass
- Non-directional tread pattern with optimized lug-to-void ratio
- Stepped tread design
- Deep and flat tread profile

BENEFITS

- Increases side impact resistance and stability
- Ensures even tread wearing for greater durability
- Enhances tread cleanout for improved traction
- Reduces tread crowning for improved durability

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]														
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph
4.50	15200	12400	10800	9500	8250	8000	7600	7300	7050	6650	6365	5985	-	-	-
65	33510	27335	23810	20945	18190	17635	16755	16095	15545	14660	14030	13195	-	-	-
3.25	-	-	-	-	6720	6600	6480	6360	6240	6180	6120	6000	5800	5500	4975
47	-	-	-	-	14815	14550	14285	14020	13755	13625	13490	13230	12785	12125	10970
3.75	17400	14200	12400	10900	9500	9150	8700	8400	8050	7650	7305	6865	-	-	-
54	38360	31305	27335	24030	20945	20170	19180	18520	17745	16865	16105	15135	-	-	-
3.00	-	-	-	-	8200	8050	7900	7750	7600	7500	7450	7300	7100	6700	6050
44	-	-	-	-	18080	17745	17415	17085	16755	16535	16425	16095	15655	14770	13340
4.75	20000	16300	14300	12500	10900	10500	10000	9650	9250	8750	8375	7875	-	-	-
69	44090	35935	31525	27560	24030	23150	22045	21275	20395	19290	18465	17360	-	-	-
3.50	-	-	-	-	8950	8800	8650	8500	8300	8250	8150	8000	7750	7350	6650
51	-	-	-	-	19730	19400	19070	18740	18300	18190	17970	17635	17085	16205	14660
3.50	21100	17200	15000	13200	11500	11100	10600	10200	9750	9250	8845	8315	-	-	-
51	46520	37920	33070	29100	25355	24470	23370	22485	21495	20395	19500	18330	-	-	-
2.50	-	-	-	-	9250	9100	8900	8750	8600	8500	8400	8250	8000	7600	6850
36	-	-	-	-	20395	20060	19620	19290	18960	18740	18520	18190	17635	16755	15100
4.75	24800	20200	17700	15500	13500	13000	12400	11900	11500	10900	10385	9765	-	-	-
69	54675	44535	39020	34170	29760	28660	27335	26235	25350	24030	22895	21530	-	-	-
3.50	-	-	-	-	11200	11000	10800	10600	10400	10300	10200	10000	9700	9200	8300
51	-	-	-	-	24690	24250	23810	23370	22930	22710	22485	22045	21385	20285	18300
4.25	28000	22800	20000	17500	15200	14700	14000	13500	13000	12300	11725	11025	-	-	-
62	61730	50265	44090	38580	33510	32410	30865	29760	28660	27115	25850	24305	-	-	-
3.25	-	-	-	-	12880	12650	12420	12190	11960	11845	11730	11500	11155	10580	9545
47	-	-	-	-	28395	27890	27380	26875	26365	26115	25860	25355	24595	23325	21045



CAMSO WHL 773

RELIABLE PERFORMANCE IN HARSH APPLICATIONS

TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
			RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32 nd]	S.L.R.	R.C.				
17.5-25	16	TL	14.00/1.5	14.00/1.3 13.00/1.4 (DC)	1355	460	27	622	4087	177	A2	L-3	LOADER-DOZER
					53.3	18.1	34	24.5	160.9				
					1355	460	27	622	4087	158	B	E-3	EARTHMOVER
					53.3	18.1	34	24.5	160.9				
					1355	460	27	622	4087	150	A8	G-3	GRADER
					53.3	18.1	34	24.5	160.9				
20.5-25	20	TL	17.00/2.0	-	1489	541	28	674	4491	186	A2	L-3	LOADER-DOZER
					58.6	21.3	35	26.5	176.8				
					1489	541	28	674	4491	170	B	E-3	EARTHMOVER
					58.6	21.3	35	26.5	176.8				
					1489	541	28	674	4491	160	A8	G-3	GRADER
					58.6	21.3	35	26.5	176.8				
23.5-25	20	TL	19.50/2.5	-	1613	615	33	725	4865	191	A2	L-3	LOADER-DOZER
					63.5	24.2	42	28.5	191.5				
					1613	615	33	725	4865	177	B	E-3	EARTHMOVER
					63.5	24.2	42	28.5	191.5				
23.5-25	24	TL	19.50/2.5	-	1613	620	33	727	4865	196	A2	L-3	LOADER-DOZER
					63.5	24.4	42	28.6	191.5				
					1613	620	33	727	4865	180	B	E-3	EARTHMOVER
					63.5	24.4	42	28.6	191.5				
26.5-25	28	TL	22.00/3.0	-	1745	682	37	777	5263	203	A2	L-3	LOADER-DOZER
					68.7	26.9	47	30.6	207.2				
					1745	682	37	777	5263	188	B	E-3	EARTHMOVER
					68.7	26.9	47	30.6	207.2				

FEATURES

- Wide footprint
- High lug-to-void ratio
- Mono-block tread pattern

BENEFITS

- Excellent stability in abrasive and rocky conditions
- Provides excellent durability and tread impact resistance
- Resists rubber chipping and chunking

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]															
	STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph	55 km/h 34 mph	60 km/h 37 mph	65 km/h 40 mph	
4.75	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4890	4600	-	-	-	
69	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10780	10140	-	-	-	
3.00	-	-	-	-	4750	4675	4600	4500	4425	4375	4325	4250	4125	3900	3525	
44	-	-	-	-	10470	10305	10140	9920	9755	9645	9535	9370	9095	8600	7770	
2.75	-	-	-	-	-	-	-	-	-	3350	-	3050	-	2750	2450	
40	-	-	-	-	-	-	-	-	-	7385	-	6725	-	6065	5400	
4.50	15200	12400	10800	9500	8250	8000	7600	7300	7050	6650	6365	5985	-	-	-	
65	33510	27335	23810	20945	18190	17635	16755	16095	15545	14660	14030	13195	-	-	-	
3.25	-	-	-	-	6720	6600	6480	6360	6240	6180	6120	6000	5800	5500	4975	
47	-	-	-	-	14815	14550	14285	14020	13755	13625	13490	13230	12785	12125	10970	
2.75	-	-	-	-	-	-	-	-	-	4500	-	4100	-	3700	3275	
40	-	-	-	-	-	-	-	-	-	9920	-	9040	-	8155	7220	
3.75	17400	14200	12400	10900	9500	9150	8700	8400	8050	7650	7305	6865	-	-	-	
54	38360	31305	27335	24030	20945	20170	19180	18520	17745	16865	16105	15135	-	-	-	
3.00	-	-	-	-	8200	8050	7900	7750	7600	7500	7450	7300	7100	6700	6050	
44	-	-	-	-	18080	17745	17415	17085	16755	16535	16425	16095	15655	14770	13340	
4.75	20000	16300	14300	12500	10900	10500	10000	9650	9250	8750	8375	7875	-	-	-	
69	44090	35935	31525	27560	24030	23150	22045	21275	20395	19290	18465	17360	-	-	-	
3.50	-	-	-	-	8950	8800	8650	8500	8300	8250	8150	8000	7750	7350	6650	
51	-	-	-	-	19730	19400	19070	18740	18300	18190	17970	17635	17085	16205	14660	
4.75	24800	20200	17700	15500	13500	13000	12400	11900	11500	10900	10385	9765	-	-	-	
69	54675	44535	39020	34170	29760	28660	27335	26235	25350	24030	22895	21530	-	-	-	
3.50	-	-	-	-	11200	11000	10800	10600	10400	10300	10200	10000	9700	9200	8300	
51	-	-	-	-	24690	24250	23810	23370	22930	22710	22485	22045	21385	20285	18300	



CAMSO WHL 775

A PREMIUM WHEEL LOADER TIRE DURABILITY SOLUTION

FEATURES

- Extra-deep L5 lug tread
- Heavy-duty carcass
- Heavy-duty sidewall construction
- Contoured lug base

BENEFITS

- Enhances durability and resistance to flat tires for extreme mixed and hard surface applications
- Increases stability and side impact resistance
- Protects against side impacts and deformation under heavy load
- Promotes stone ejection and resistance to cracking

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



#	TIRE SIZE	PR	TL/TT	RIM SIZE		ACTUAL TIRE DIMENSIONS [mm] [inches]					LOAD INDEX	SPEED SYMBOL	TREAD CODE	SERVICE
				RECOMMENDED	ALTERNATIVE	O.D.	O.W.	O.T.D. [mm] [32"]	S.L.R.	R.C.				
A	17.5-25	16	TL	14.00/1.5	14.00/1.3 13.00/1.4 (DC)	1403	448	62	649	4231	177	A2	L-5	LOADER-DOZER
						55.2	17.6	78	25.6	166.6				
B	20.5-25	20	TL	17.00/2.0	-	1563	532	77	711	4714	186	A2	L-5	LOADER-DOZER
						61.5	20.9	97	28.0	185.6				
C	23.5-25	20	TL	19.50/2.5	-	1670	597	88	768	5037	191	A2	L-5	LOADER-DOZER
						65.7	23.5	111	30.2	198.3				
D	26.5-25	28	TL	22.00/3.0	-	*	*	*	*	*	203	A2	L-3	LOADER-DOZER
						*	*	*	*	*				

#	INFLATION PRESSURE [bar] [psi]	MAXIMUM TIRE LOAD [kg] [lb]											
		STATIC	CREEP	5 km/h 3 mph	10 km/h 6 mph	15 km/h 9 mph	20 km/h 12 mph	25 km/h 15 mph	30 km/h 18 mph	35 km/h 21 mph	40 km/h 24 mph	45 km/h 28 mph	50 km/h 31 mph
A	4.75	11700	9500	8300	7300	6350	6150	5850	5600	5400	5100	4890	4600
	69	25795	20945	18300	16095	14000	13560	12895	12345	11905	11245	10780	10140
B	4.50	15200	12400	10800	9500	8250	8000	7600	7300	7050	6650	6365	5985
	65	33510	27335	23810	20945	18190	17635	16755	16095	15545	14660	14030	13195
C	3.75	17400	14200	12400	10900	9500	9150	8700	8400	8050	7650	7305	6865
	54	38360	31305	27335	24030	20945	20170	19180	18520	17745	16865	16105	15135
D	4.75	24800	20200	17700	15500	13500	13000	12400	11900	11500	10900	10385	9765
	69	54675	44535	39020	34170	29760	28660	27335	26235	25350	24030	22895	21530

CONSTRUCTION TRACKS



CAMSO MEX HXD

EXTREME RESISTANCE TO SEVERE CONDITIONS

FEATURES

- Patented 3S internal iron core
- High-tensile, rubber sealed steel cables protected by heavy-duty carcass and tread
- Curbshield technology with heavy-duty carcass

BENEFITS

- Reduces unexpected downtime on the job site by preventing the initial degradation process
- Minimizes vibrations for better ride quality and lower maintenance cost
- Resists carcass punctures and cable corrosion to extend service life
- Maximizes service life prior to track degradation process triggered by edge cutting leading to iron core corrosion

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE




TRACTION




WIDTH	PITCH	TREAD	GUIDING	METAL PIECE NAME	CARCASS THICKNESS	LUG HEIGHT	METAL PIECE TYPE	METAL PIECE SPECIFICATION
230	48	AH	I	KA	26.5	24.5	3S	STANDARD
300	55	AH	I	SA	35	27.5	3S	NARROW
		AH	I	WA	35	27.5	3S	WIDE
350	52.5	AH	I	WA	34	25	3S	STANDARD
400	72.5	AH	I	WA	43	27.5	3S	NARROW
		AH	I	EA	43	27.5	3S	WIDE
		AH	J	EA	45.5	27.5	3S RAIL TYPE	STANDARD
		AH	J	WA	47	27.5	3S OFFSET RAIL TYPE	STANDARD
450	71	AH	I	JA	48.5	30	3S	STANDARD
		AH	I	JA	49	30	3S	STANDARD
		AH	I	OA	46.5	30.5	3S	NARROW
		AH	I	AA	46.5	30.5	3S	WIDE
		AH	J	UA	47	27.5	3S OFFSET RAIL TYPE	STANDARD
485	92	AH	I	D	62.5	27	OFFSET	STANDARD
500	92	AB	I	D	58	30	STANDARD	STANDARD
		AH	I	DA	56	33	3S	STANDARD

TREAD PATTERNS



AH




AB



CAMSO MEX SD

PREDICTABLE SERVICE LIFE AND PERFORMANCE

TREAD PATTERNS



FEATURES

- Patented 3S internal iron core
- High-tensile, rubber sealed steel cables
- Curbshield technology

BENEFITS

- Eliminates detracking to avoid unexpected downtime on job site and to extends life of undercarriage components
- Minimizes vibrations for better ride quality and lower maintenance cost
- Resists carcass punctures and cable corrosion to extend service life
- Extends service life prior to track degradation process triggered by edge cutting leading to iron core corrosion

PERFORMANCE



WIDTH	PITCH	TREAD	GUIDING	METAL PIECE NAME	CARCASS THICKNESS	LUG HEIGHT	METAL PIECE TYPE	METAL PIECE SPECIFICATION
130	72	A	A	RB	18	15	STANDARD	STANDARD
150	72	A	A	R	21	15	STANDARD	STANDARD
180	60	S	A	F	16	13	STANDARD	STANDARD
	72	X	A	R	20	15	STANDARD	STANDARD
		P	B	R	21	17	STANDARD	STANDARD
200	72	X	A	P	21	17	STANDARD	STANDARD
		A	A	R	20	15	STANDARD	STANDARD
		TF	A	P	22	15	STANDARD	STANDARD
		V4	J	P	23	10	STANDARD	STANDARD
230	48	V4	J	P	24.5	17	RAIL TYPE	STANDARD
		V1	I	KA	26	18	3S	STANDARD
		T1	J	K	22	22	RAIL TYPE	STANDARD
	72	ZZ	J	K	22.5	23	RAIL TYPE	STANDARD
		V4	J	P2	21.5	17	RAIL TYPE	STANDARD
		A	A	P	22	18	STANDARD	STANDARD
250	47	B	A	P	22	18	STANDARD	STANDARD
		V5	J	KA	26	18	3S RAIL TYPE	STANDARD
	48	V1	I	KA	27	20	3S	STANDARD
	48.5	OZ	J	KA	32	20	3S OFFSET RAIL TYPE	STANDARD
	52.5	V1	I	SA	29	24	3S	NARROW
		V1	J	SA	32.5	24	3S RAIL TYPE	STANDARD
	72	D	A	P	24	17	STANDARD	STANDARD
		B	A	P	24	17	STANDARD	STANDARD
		R1	A	PR	30	18	STANDARD	STANDARD
		V1	I	SA	31	23	3S	NARROW
300	52.5	V1	I	WA	31	23	3S	WIDE
		V1	I	WA	31	23	3S	WIDE
	53	V5	J	SA	32	25	3S RAIL TYPE	STANDARD
	55	Y2	J	SF	36	25	RAIL TYPE	STANDARD
	55.5	O	J	SA	34	20	3S OFFSET RAIL TYPE	STANDARD
V1		J	SA	32.5	24	3S RAIL TYPE	STANDARD	
320	100	Q	A	W	39	25	STANDARD	STANDARD
350	52.5	V1	I	WA	30	22	3S	STANDARD
	54.5	V1	J	WA	39	25	3S RAIL TYPE	STANDARD
400	72.5	V1	I	WA	40	25	3S	NARROW
		V1	I	EA	40	25	3S	WIDE
		V1	J	EA	42	25	3S RAIL TYPE	STANDARD
450	71	V1	I	JA	44	25	3S	STANDARD
		V1	I	OA	42	28	3S	NARROW
		V1	I	AA	42	28	3S	WIDE



CAMSO CTL HXD

THE BEST TRACK FOR DURABILITY AND PERFORMANCE

FEATURES

- Single-cure technology with next generation rubber compound
- Trackguard iron core with heavy-duty carcass
- Endless high-tensile steel cables
- Optimized tread pattern with next generation rubber compound

BENEFITS

- Promotes even tread wearing for long, predictable tread life
- Improves rolling path life for reduced failures and enhanced durability
- Eliminates unexpected downtime due to cable/track breakage
- Maintains excellent traction throughout tread life

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE







TRACTION



WIDTH	PITCH	TREAD	GUIDING	METAL PIECE NAME	CARCASS THICKNESS	LUG HEIGHT	METAL PIECE TYPE	METAL PIECE SPECIFICATION
180	72	TF	J	R	24	10	RAIL TYPE	STANDARD
		ST	J	R	23	18	RAIL TYPE	STANDARD
		HH	B	R	28	12	STANDARD	STANDARD
230	72	TF	J	R	24	10	RAIL TYPE	STANDARD
		ST	J	R	23	18	RAIL TYPE	STANDARD
250	72	HH	B	R	29	11	STANDARD	STANDARD
300	84	HH	B	E	42	25	STANDARD	STANDARD
320	86	HH	B	E	51	26	STANDARD	STANDARD
		HH	J	W	34	30	RAIL TYPE	STANDARD
400	86	HH	B	E	51	26	STANDARD	STANDARD
450	86	HH	B	E	51	26	STANDARD	STANDARD
		HA	B	E	53.5	26	STANDARD	STANDARD
	100	HH	J	E	34	30	RAIL TYPE	STANDARD

TREAD PATTERNS



CAMSO CTL SD

ALL-SEASON TRACTION AND DURABILITY

FEATURES

- Single-cure technology with advanced rubber compound
- Trackguard iron core
- Endless high-tensile steel cables
- Versatile self-cleaning stepped tread design

BENEFITS

- Promotes even tread wearing for long, predictable tread life
- Improves rolling path life for reduced failures and enhanced durability
- Eliminates unexpected downtime due to cable/track breakage
- Maintains good traction throughout tread life

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE




TRACTION



WIDTH	PITCH	TREAD	GUIDING	METAL PIECE NAME	CARCASS THICKNESS	LUG HEIGHT	METAL PIECE TYPE	METAL PIECE SPECIFICATION
320	86	B	J	W	37	25	RAIL TYPE	STANDARD
		B	B	E	47	27	STANDARD	STANDARD
400	86	B	B	E	49	25	STANDARD	STANDARD
450	86	B	B	E	52	25	STANDARD	STANDARD
	100	B	J	E	32	25	RAIL TYPE	STANDARD

TREAD PATTERNS



CAMSO CTL SPROCKET



DEM QUALITY AND PERFORMANCE AT AFTERMARKET PRICES

FEATURES

- Enhanced hardening with deeper penetration
- Premium quality design and engineering
- Optimized geometry and design

BENEFITS

- Provides longer sprocket wear
- Meets the toughest OEM specifications
- Ensures best fitment with tracks for longer track life

PERFORMANCE

WEAR RESISTANCE



IMPACT RESISTANCE



TRACK AND SPROCKET MATCH



PID	PART NUMBER	MACHINE BRAND	MODEL	NUMBER OF BOLT HOLES	NUMBER OF TEETH	PITCH (mm)	SHAPE B=BELL F=FLAT	ID	WEIGHT (kg)
147.14.14	SP-015086BB	Bobcat	T180*, T180H*, T190*, T190H*	6	15	86	B	B	23
147.6.6	SP-017086BA	Bobcat	864, T200, T250, T250H, T300, T300H, T320, T630, T650, T750, T770	12	17	86	B	A	28
147.11.11	SP-017086FE	Case New Holland	445CT, 450CT, TR270, TR310, TR320, TR340, TV380, C175, C185, C190, C227, C232, C238 LT175B, LT185B, LT190B	9	17	86	F	E	24
147.2.2	SP-015086FA	CAT	259, 259D	8	15	86	F	A	14
147.8.8	SP-017086FB	CAT	269C, 279C, 279C2, 279D, 289C, 289C2, 289D, 299C, 299D, 299D XHP	9	17	86	F	B	20
147.4.4	SP-016086FA	John Deere	CT 319D*, CT 322, CT 323D*	6	16	86	F	A	18
147.9.9	SP-017086FC	John Deere	CT 329D*, CT 332, CT 333D*	10	17	86	F	C	22
147.7.7	SP-017086FA	John Deere	CT 319D*, CT 323D*, CT 329D*, CT 333D*	12	17	86	F	A	20
147.3.3	SP-015086FB	Kubota	SVL75	8	15	86	F	B	17
147.10.10	SP-017086FD	Kubota	SVL90	9	17	86	F	D	22
147.5.5	SP-016086FB	Gehl Mustang Takeuchi	CTL 60, CTL 65 MTL 16, MTL 316 TL 130, TL 230	8	16	86	F	B	17

CAMSO MTL HXD



ENHANCED DURABILITY AND PROTECTION

FEATURES

- Single cure technology combined with duradrive internal fabric reinforced design
- Heavy duty carcass construction
- Versatile tread pattern matched with advanced rubber compound

BENEFITS

- Protects against drive lug failures to add an extra season and complete tread life utilization
- Increases lateral stability to eliminate detracking for less downtime
- Maintains good traction throughout tread life

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE



TRACTION



WIDTH		LENGTH		PITCH		NUMBER OF DRIVE LUGS	TREAD
[mm]	[inches]	[mm]	[inches]	[mm]	[inches]		
381	15	4216	166	100	4	42	MTL1
457	18	5080	200	100	4	51	MTL2
		5588	220			56	
		5105	201			51	

TREAD PATTERNS



*Verify exact fitment with the machine serial number at: <https://camso.co/en/products-solutions/construction>



CAMSO OTT HXD

QUICK MOUNT ATTACHMENT FOR TRACKED PERFORMANCE

FEATURES

- Full rubber track
- Embedded iron core with engineered wing design
- Full width, continuous rubber track footprint
- Internal traction rib

BENEFITS

- Allows operation on asphalt, concrete and turf surfaces without damage or marking
- Avoids detracking like a non-reinforced all rubber OTT
- Increases flotation by as much as 5 times that of tires and by, at least, twice as much as standard steel tracks
- Provides high traction between tire and track and prevents tire wear

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE




TRACTION



WIDTH		PITCH		LINKS	CARCASS THICKNESS	LUG HEIGHT
[mm]	[inches]	[mm]	[inches]			
254	10	152.4	6	26	25	32
				27		
				28		
				29		
				31		
304.8	12	152.4	6	29	25	32
				30		
				31		
				32		
				33		

TREAD PATTERNS



CAMSO HXD SMOOTH

DURABILITY AT ITS BEST

FEATURES

- Single-cure technology with next generation rubber compound
- Optimized multi layer internal construction
- Smooth tread pattern with heavy duty carcass

BENEFITS

- Promotes even tread wearing for long, predictable tread life
- Improves weight distribution with better lateral stiffness
- Increases track life

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE



TRACTION



WIDTH		LENGTH		CARCASS THICKNESS		TREAD THICKNESS		TOTAL THICKNESS		TREAD
[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	
400	15.75	8049	317	27.5	1.1	30.5	1.2	58	2.3	Smooth
406	16	6921	272.5	30	1.2	21	0.8	51	2	Smooth
457	18	8049	317	27.5	1.1	30.5	1.2	58	2.3	Smooth

SIDE VIEW





CAMSO HXD CHEVRON

DURABILITY MEETS TRACTION

FEATURES

- Single-cure technology with next generation rubber compound
- Optimized multi layer internal construction
- Chevron type tread pattern

BENEFITS

- Promotes even tread wearing for long, predictable tread life
- Improves weight distribution with better lateral stiffness
- Provides high traction in softer surfaces

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE



TRACTION



WIDTH		LENGTH		CARCASS THICKNESS		TREAD THICKNESS		TOTAL THICKNESS		TREAD
[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	
400	15.75	8049	317	23.5	0.9	38	1.5	61.5	2.4	Chevron
406	16	6921	272.5	23.5	0.9	38	1.5	61.5	2.4	Chevron
457	18	8049	317	23.5	0.9	38	1.5	61.5	2.4	Chevron

SIDE VIEW



CAMSO CARRIER HXD

TOP PERFORMANCE AND UPTIME

FEATURES

- First and only endless steel cable in the market
- Trackguard iron core
- Straight bar tread pattern
- Next generation rubber compound

BENEFITS

- Protects from joint failures to avoid unexpected downtime
- Improves rolling path life for reduced failures and enhanced durability
- Provides optimal traction
- Promotes even tread wearing for long, predictable tread life

PERFORMANCE

TREAD LIFE



FAILURE RESISTANCE




TRACTION




WIDTH	PITCH	TREAD	GUIDING	METAL PIECE	CARCASS THICKNESS	LUG HEIGHT	METAL PIECE TYPE	METAL PIECE SPECIFICATION
350	100	A1	B	E	42	27	STANDARD	STANDARD
700	100	A2	B	T	66	32	STANDARD	STANDARD
750	150	A2	B	T	80	36	STANDARD	STANDARD

TREAD PATTERNS



A1



A2

COMPLETE LINE OVERVIEW



SKID STEER LOADERS



CAMSO SKS 732 CAMSO SKS 532 CAMSO SKS 332 CAMSO SKS 753 CAMSO SKS 775 CAMSO HAULER SKS CAMSO XTRA WALL CAMSO HAULER SKZ



CAMSO SKS 774 CAMSO SKS 511 CAMSO SKS 792S CAMSO SKS 782S CAMSO SKS 793S CAMSO SKS 796S CAMSO SKS 786S

BACKHOE LOADERS



CAMSO SL R4 CAMSO BHL 532 CAMSO BHL 753 CAMSO BHL 530

TELESCOPIC HANDLERS AND MOTOR GRADERS



CAMSO TLH 732 CAMSO TLH 532 CAMSO TLH 753 CAMSO SL G2 CAMSO SL G3 CAMSO TLH 792S

TELESCOPIC HANDLERS, COMPACT WHEEL LOADERS AND MINI-DUMPERS



CAMSO MPT 552 CAMSO MPT 753 CAMSO TM R4 CAMSO 4L I3 CAMSO 4L R1 CAMSO TM R1 CAMSO MPT 793S CAMSO MPT 532R CAMSO MPT 553R

WHEEL EXCAVATORS



CAMSO WL CAMSO WEX 552 CAMSO WEX 583S

COMPACTION EQUIPMENT



CAMSO CMP 533 CAMSO CMP 576

MINE SERVICE

¹BY CAMSO MAGNUM SERIES



CAMSO MST 776 SOLIDEAL HAULER LT SOLIDEAL RES 550¹

WHEEL LOADERS, ARTICULATED DUMP TRUCKS AND MOTOR GRADERS



CAMSO WHL 753R CAMSO ADT 753R CAMSO WHL 775R CAMSO WHL 776R CAMSO GRD 533R CAMSO EMT 553R

RADIAL



CAMSO LM L2 CAMSO LM L3 CAMSO WHL 773 CAMSO WHL 775

TRACKS FOR MINI-EXCAVATORS



CAMSO MEX HXD CAMSO MEX SD

TRACKS FOR COMPACT TRACK LOADERS



CAMSO CTL HXD CAMSO CTL SD

SPROCKETS FOR CTL'S



CAMSO CTL SPROCKET

TRACKS FOR MULTI-TERRAIN LOADERS



CAMSO MTL HXD

OTT TRACKS FOR SKID STEER LOADERS



CAMSO OTT HXD

TRACKS FOR PAVERS





CAMSO HXD SMOOTH CAMSO HXD CHEVRON

TRACKS FOR CARRIERS



CAMSO CARRIER HXD



TOUGH IS OUR WAY OF LIFE

